



## EP Epoxy High Gloss Epoxy Pool Paint

TECHNICAL BULLETIN 11-13

- High solids, high gloss epoxy pool paint
- For bare concrete, fiberglass, plaster and previously painted epoxy.
- Up to 3 years service life
- Great for Koi ponds, hot tubs, spas and fountains.
- VOC compliant in US and Canada



EP Epoxy cures to a hard, tough, durable finish, providing stain, chemical and abrasion resistance for protection of concrete, plaster and fiberglass swimming pools, spas and slides. EP Epoxy cures to a high gloss-finish with excellent coverage rates, especially on previously painted epoxy surfaces. EP Epoxy has been a proven performer for more than 50 years. Because of their chemical cure, epoxies are the paints of choice for indoor pools.

### PHYSICAL DATA

VEHICLE TYPE: Epoxy Polyamide

FINISH: High Gloss

COLORS:

AquaGreen, White, Black, Dawn Blue, Monument Gray,  
Dark Blue, Vermillion, Royal Blue

COMPONENTS: 2

Mix Ratio 2:1 by volume A:B

Pot Life—8 Hours

CURING MECHANISM: Chemical Cure

SOLIDS (theoretical):

By weight...73 +/- 2%

By volume...60 +/- 3%

COVERAGE: 500 sq. ft/gal.

VOC: 340 g/l max. (as supplied)

FLASH POINT: 60°F (SETA)

### APPLICATION DATA

METHOD: Brush, Use no thicker than 3/8" Mohair or Lambskin Roller, Airless or Conventional Spray.

NUMBER OF COATS: 2 (Product is self-priming)

DRY FILM THICKNESS PER COAT: Minimum 1.7 mils; 2.9 wet mils. Maximum 2 mils; 3.3 wet mils.

APPLICATION TEMP: 50° F. Min. / 90°F. Max.

DRY TIME\* 5-7 Days Outdoor pool to fill pool

10-14 Days Indoor pool to fill pool

To Recoat: 12-72 Hours

THINNER:

Ramuc Thinner