

- Formulated to provide the longest lasting finish of any pool paint.
- For bare concrete, fiberglass, plaster, gunite and previously painted epoxy.
- Self-priming, satin finish
- Up to 8 years service life
- Great for Koi ponds, hot tubs, spas and fountains and slides.
- VOC compliant in US and Canada



Ramuc EP Hi Build epoxy is the superior product of all pool paint. With its hard, tough durable finish, epoxy provides unsurpassed stain, chemical and abrasion resistance. Packaged in an easy-to-use 1-to-1 mix ratio, EP Hi Build Epoxy rolls easily and builds up to 8 mils dry per coat rendering “smoothing” qualities on rough surfaces.

PHYSICAL DATA

VEHICLE TYPE: Epoxy Polyamide
 FINISH: Satin
 COLORS:
 White, Black, Dawn Blue, Beach Beige
 COMPONENTS: 2
 Mix ratio 1:1 by volume (A:B)
 CURING MECHANISM: Chemical Cure
 Pot Life: 3 Hours
 SOLIDS (theoretical):
 By weight...80%+/- 2% mixed
 By volume...66 +/- 2% mixed
 COVERAGE: 250sq ft/mixed kit on bare surface
 250-450sq ft/mixed kit on recoats
 VOC: 280 g/l max. (as supplied)
 FLASH POINT: 78°F (SETA)

APPLICATION DATA

METHOD: Brush, Use no thicker than 3/8" Mohair or Lambskin Roller, Airless or Conventional Spray.
 NUMBER OF COATS: 2 Product is self-priming
 DRY FILM THICKNESS PER COAT: Minimum 5 mils (7.5 wet mils) Maximum 8 Mil 12.5 wet mils
 APPLICATION TEMP: 50° F. Min. / 90°F. Max.
 DRY TIME* (5-7 Days to fill Outdoor pool
 10-14 Days to fill Indoor pool
 To Recoat: 16-72 Hours
 THINNER:
 Ramuc Thinner