Material Safety Data Sheet

WHMIS	TDG Road/Rail

Health Hazard	*	2
Fire Hazard		0
Reactivity		1
Personal Protection		C

This MSDS is providen as information only. The product is not WHIMS regulated. The product is regulated under the PCP act and packaged as a consumer product.

1. Product and company identification

Product name : **STAB CHLOR GRANULES**

Code : 30-60210

Date of issue (dd/mm/yyyy) : **2012-10-16.**

Material uses : Consumer products: Pool & Spa water treatment product

Supplier : Alliance Trading inc.
109 north Park Blvd 4th floor
Covington, LA, USA, 70433

Manufacturer : Manufactured for:
Alliance Trading inc.
109 north Park Blvd 4th floor
Covington, LA, USA, 70433

In case of emergency : **Emergency phone: CANUTEC (613) 996-6666 (Collect calls accepted)**

2. Hazards identification

Potential hazards described in this section are not expected when manufacturer's direction for use and proper security measures are observed.

Physical state : Solid.

Odor : Chlorine
[Strong]

Emergency overview : **DANGER!**
Harmful by inhalation and if swallowed. Corrosive to the eyes, skin and respiratory system. Causes burns. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Routes of entry : Inhalation. Ingestion.

Potential acute health effects

Inhalation : Toxic by inhalation. Corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. Not a usual way of absorbtion Do not breathe dust/fume/gas/mist/vapors/spray.

Ingestion : Toxic if swallowed. May cause burns to mouth, throat and stomach.

Skin : Corrosive to the skin. Causes burns.

Eyes : Corrosive to eyes. Causes burns.

See toxicological information (Section 11) for more details.

3. Composition/information on ingredients

Name	CAS number	% (w/w)
Dichloroisocyanuric acid sodium salt	2893-78-9	60 - 100

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 20 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

5. Fire-fighting measures

Flammability of the product : Strong oxidizing agent. Contact with combustible material may cause fire.

Extinguishing media

Suitable : Do not use water jet Use flooding quantities of water. Do not use dry chemical extinguishers containing ammonium compounds. May reacts explosively with calcium hypochlorite in the presence of water.

Not suitable : Do not use water jet Do not use dry chemical extinguishers containing ammonium compounds.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards : Contact with small amounts of water may result in an exothermic reaction with the liberation of toxic fumes. May reacts explosively with calcium hypochlorite in the presence of water.

:

6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill : Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage : Do not store above the following temperature: 60°C (140°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Keep container dry. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
No exposure limit value known.											

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required. No monitoring equipment are required if no occupationnal exposure limit values are suggested.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Personal protection

Respiratory : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Recommended: disposable particulate mask

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Chemical-resistant, impervious gloves
4 - 8 hours (breakthrough time): Chemical-resistant, impervious gloves
1 - 4 hours (breakthrough time): Chemical-resistant, impervious gloves
< 1 hour (breakthrough time): Chemical-resistant, impervious gloves

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Recommended: Safety Glasses

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Recommended: safety apron

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

8. Exposure controls/personal protection

Personal protective equipment (Pictograms) :



9. Physical and chemical properties

Physical state	: Solid.	**Molecular formula**	: Not applicable.	**Flammable limits**	: Not available.
Color	: White.	**Molecular weight**	: Not applicable.	**Burning rate**	: Not available.
Odor	: Chlorine [Strong]	**Vapor pressure**	: Not available.	**Burning time**	: Not available.
Relative density	: Not available.	**Vapor density**	: Not available.	**Critical temperature**	: Not available.
pH	: 6 [Conc. (% w/w): 1%]	**Volatility**	: Not available.	**Auto-ignition temperature**	: Not available.
Viscosity	: Not available.	**Evaporation rate**	: Not available.	**Flash point**	: [Product does not sustain combustion.]
Odor threshold	: Not available.	**Ionicity (in water)**	: Not available.	**Dispersibility properties**	: Not available.

Solubility : Not available.

Melting/freezing point : Not available.

Boiling/condensation point : Not available.

10. Stability and reactivity

Chemical stability : The product is stable.

Conditions to avoid : STRONG OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. Keep away from water.

Materials to avoid : CALCIUM HYPOCHLORITE HYDRATED MIXTURE Amine. Ammonium salt. Reducing agents Water Combustible material. Peroxide. Strong oxidizer
Avoid materials likes: nitrogen containing materials, oils, grease, sawdust, dry fire extinguishers containing monoammonium compounds.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous reactions : Hazardous reactions or instability may occur under certain conditions of storage or use.

11. Toxicological information

The symptoms, hazards and situations described in this section are not expected when manufacturer's direction for use, proper security measures and given professionnal exposure limits are correctly followed.

Potential chronic health effects

Chronic effects :

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: mucous membranes, upper respiratory tract, skin, eyes.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Ingestion : Adverse symptoms may include the following:
stomach pains

Skin : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur

Eyes : Adverse symptoms may include the following:
pain
watering
redness

Medical conditions aggravated by over-exposure :

Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dichloroisocyanuric acid sodium salt	LC50 Inhalation Vapor	Rat	847.5 mg/m³	4 hours
	LD50 Oral	Rat	1420 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dichloroisocyanuric acid sodium salt	Eyes - Mild irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	0.1 Grams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Severe irritant	Rabbit	-	500 milligrams	-

11. Toxicological information

Carcinogenicity Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Dichloroisocyanuric acid sodium salt	-	4	E	-	-	None.

12. Ecological information

Ecotoxicity : Do not contaminate water by cleaning of equipment or disposal of wastes. Toxic to aquatic organisms. When used according to the label instructions, hazards to non-target plants and aquatic organisms are very low.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Exposure	Species
Dichloroisocyanuric acid sodium salt	-	Acute EC50 0.11 ppm Fresh water	48 hours	Daphnia - Water flea - Daphnia magna
	-	Acute LC50 0.217 ppm Fresh water	96 hours	Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

Toxicity of the products of biodegradation : The products of biodegradation are less toxic than the original product.

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste stream : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations.
Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	2465	UN2465 DICHLOROISOCYANURIC ACID DRY (Dichloroisocyanuric acid sodium salt)	5.1	II		-
TDG Classification	2465	UN2465 DICHLOROISOCYANURIC ACID DRY (Dichloroisocyanuric acid sodium salt)	5.1	II		-

PG* : Packing group

15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.
WHMIS (Canada) : Not controlled under WHMIS (Canada).
Canadian lists : **CEPA Toxic substances**: None of the components are listed.
Canadian ARET: None of the components are listed.
Canadian NPRI: None of the components are listed.
Alberta Designated Substances: None of the components are listed.
Ontario Designated Substances: None of the components are listed.
Quebec Designated Substances: None of the components are listed.
Canada inventory : At least one component is not listed.
Other certification :

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

16. Other information on the product

Label requirements : CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. HARMFUL IF INHALED OR SWALLOWED.

References : - Manufacturer's Material Safety Data Sheet.

Date of printing (YYYY-MM-DD) : 2012-10-16.
Date of issue (YYYY-MM-DD) : **2012-10-16.**

Note: MSDS are valid for a 3 years period after the date of issue

Indicates information that has changed from previously issued version.

MSDS prepared by:
QA and Documentation Department

Manufactured for:
Alliance Trading inc.
109 north Park Blvd 4th floor
Covington, LA, USA, 70433

Notice to reader

16. Other information on the product

There are potential hazards to people and goods associated with the use of this product which are detailed in the present Material Safety Data Sheet (MSDS). To minimize potential hazards associated with this product it is of users responsibility to conform the directions for use and all other instructions provided in the Material Safety Data Sheet (MSDS) of this product. The manufacturer, distributors and suppliers of this product are exonerating themselves and consequently shall not be liable for any prejudice or damage of any kind, resulting from the use of this product which may not be in accordance with the directions for use or all the instructions provided in the present Material Safety Data Sheet (MSDS) or resulting from an unadvised use of the present product..

Emergency phone: CANUTEC (613) 996-6666 (Collect calls accepted)