

FCA501 FLANGED COUPLING ADAPTER

SUBMITTAL INFORMATION



STANDARD

Romac 501 couplings meet the specifications set forth in the AWWA Standard C219 coupling spec.

MATERIALS

CASTINGS

The end ring and flanged body are cast from ductile (nodular) iron, meeting or exceeding ASTM A 536.

FLANGE

Compatible with ANSI Class 125 and 150 bolt circles.

GASKETS

Gaskets are made from virgin Styrene Butadiene Rubber (SBR) compounded for water and sewer service in accordance with ASTM D 2000 MBA 710. Other compounds available for petroleum, chemical, or high temperature service.

BOLTS AND NUTS

High strength low alloy steel trackhead and T-head bolt National coarse rolled thread and heavy hex nuts. Steel meets AWWA C111 composition specifications. The 10" size uses electro-galvanized mild steel flange bolts and nuts with a hex head, and ductile iron through bolts. The 12" size uses electro-galvanized mild steel flange bolts and nuts with a hex head, and mild steel through bolts (AWWA C111 composition specifications). All above nuts and bolts are corrosion resistant. Stainless steel bolts and nuts available on request.

COATINGS

Shop coat applied to cast parts for corrosion protection in transit. Fusion bonded epoxy, liquid epoxy and other coatings available on request.

PRESSURE

When properly installed on a pipe that is within the correct outside diameter range, the FCA 501 couplings can be used at working pressures up to 260 psi.

ANCHOR PINS

Anchor pins to restrain fitting available as option.

SIZES & RANGES

See Catalog.

11/27/2024

Document # 20-8-0006