



## Features

- High impact polymer exterior
- Aluminum fully reinforced interior
- Tubing: 1.90" OD, 1.38" ID
- Wall thickness: .25"

| Model    | Description   | Shipping Wt. | L    | W   | H  |
|----------|---------------|--------------|------|-----|----|
| TDTP-148 | 48" W x 35" H | 16 lbs.      | 83"  | 42" | 3" |
| TDTP-160 | 60" W x 35" H | 19 lbs.      | 98"  | 42" | 2" |
| TDTP-172 | 72" W x 35" H | 21 lbs.      | 110" | 45" | 2" |

All measurements on center. Escutcheons are included. When ordering, add the color to the end of the model number: (W) White, (B) Beige, (G) Gray, (GG) Graphite Gray, (T) Taupe, (BK) Black. Safron ladders and rails are available in custom bends, sizes, and colors.



Technical drawing of a curved structural member, likely a pipe or duct, showing dimensions and annotations. The drawing includes a side view and a cross-sectional view.

**Dimensions:**

- Overall height:  $34\frac{3}{16}$ "
- Overall width:  $36$ "
- Horizontal distance from left edge to centerline:  $48$ "
- Horizontal distance from centerline to right edge:  $60$ "
- Horizontal distance from left edge to right edge:  $72$ "
- Vertical distance from bottom edge to centerline:  $26$ "
- Vertical distance from centerline to top edge:  $35\frac{5}{16}$ "
- Vertical distance from bottom edge to top edge:  $35\frac{5}{16}$ "
- Horizontal distance from centerline to right edge:  $4$ "
- Horizontal distance from centerline to right edge:  $4$ "
- Horizontal distance from centerline to right edge:  $4$ "

**Annotations:**

- Ø1.90"
- 4"
- 4"
- 4"