



SUREBOND

SureStrip Fast Acting Sealer Stripper

★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

SUITABLE SUBSTRATES:

Ideal for concrete and clay pavers, concrete flat work and retaining walls. It can be used on manufactured and natural stone, concrete block and wet cast products. It works on both horizontal and vertical applications. Not for use on asphalt.

PRODUCT DESCRIPTION:

SureStrip is a technologically advanced stripper designed for removal of acrylics, acrylic latex, polyurethane, and other resin coatings and sealers. SureStrip can also be used as a spot cleaner to remove paint spots.

SureStrip's unique Clean Rinse Technology quickly and easily rinses away residue with a high or low pressure washer (protect plant materials from overspray and contact).

SureStrip is the sealer stripper of choice by contractors for both routine maintenance and restoration. It can be used to prepare your surface for sealing in tandem with S.R.B. (Stain & Rust Buster) for spot stain cleaning, Oil Extractor for oil stains, SureClean for surface cleaning and Efflo Off for efflorescence removal.

Features	Benefits
What makes SureStrip different?	
Powerful	• Strips a Variety of Sealers/Coatings
Fast Acting	• Works in Minutes
Clean Rinse Technology	• Does Not Leave Cleaner Residue on Surface
Ready to Use	• No Dilution Necessary

SURFACE & AIR TEMPERATURES:

Excessively high or low temperatures will produce poor results. Best stripping results are obtained when air and surface temperatures are 40°F or above. Do not use stripper when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90°F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface. Always rinse thoroughly while SureStrip is still wet on surface.

PREPARATION/ PRE-TESTING:

Sweep and remove all loose soil and debris from the surface. Protect adjacent and surrounding surfaces not intended to be stripped from stripper, old sealer and rinse water. Cover foliage with polyethylene or other proven protective material. Prior to stripping, test stripper on a small, inconspicuous area to determine the suitability of this product for a specific sealer and surface. Testing should confirm effectiveness of stripper and desired surface dwell time on each type of surface and sealer designated to be removed. Allow test areas to dry thoroughly before evaluating final appearance and results. It may be necessary to manage rinse water containing old sealer and stripper by reclamation to prevent run-off into storm sewer. Small scale projects can be dammed and residue removed with a shop vac. Large projects or volume of residue can be removed with a reclamation unit.

DILUTION:

SureStrip is a concentrated sealer stripper that is ready to use. No dilution is necessary.

APPLICATION INSTRUCTIONS:

Apply SureStrip using a low-pressure sprayer such as a garden sprayer or it can be brushed, wiped, or rolled onto the surface. Depending on the sealer or coating, more than one application may be needed. If surface is sloped, apply SureStrip from the bottom of the slope working up using a side-to-side motion. Allow SureStrip to dwell for at least five to ten minutes before doing a scratch test. Scratch at the sealer or coating with a sharp object to see if the substrate is visible. If the substrate is visible where tested then it is ready to be rinsed. Improve results by scrubbing surface with a brush to agitate and loosen sealer. If the substrate is not visible or if the coating is gummy but not released, re-apply and let dwell for an additional ten minutes before re-testing. Rinse surface thoroughly with a cold water pressure washer with a 25° to 40° fan tip or a garden hose with nozzle. Only use as much pressure as needed to thoroughly clean as excessive high





pressures can damage substrates. It may be necessary to do a secondary cleaning to remove old, heavier sealers. Do not allow SureStrip to dry on the surface during dwell time. Always rinse-off the surface while it is still thoroughly wet. It may be necessary to lightly re-apply SureStrip during the dwell time to keep the surface wet with product.

COVERAGE*:

APPLICATION	SQ FEET	SQ METERS
All Surfaces	125 - 250	11.6 - 23.2

*Coverage rates will vary from 125-250 sf per gallon depending on the surface porosity, texture, age & amount of sealer, application method and other local conditions. Coverage based on single treatment. Some applications may require additional treatments.

PACKAGING / SIZES:

4 – 1 gallon containers per case
5 gallon pails

CONTAINER HANDLING/STORAGE: Keep container tightly closed in a dry, well-ventilated place. Keep cool. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not allow to freeze.

DISPOSAL: Dispose of contents and container to appropriate waste site or reclaimer in accordance with all applicable laws, regulations, and product characteristics at time of disposal.

SHELF LIFE: Two years if properly stored

PRECAUTIONARY INFORMATION:

KEEP OUT OF REACH OF CHILDREN • Read label and obtain special instructions before use • Do not handle until all safety precautions have been read and understood • Keep container tightly closed when not in use • Wash thoroughly after handling • Do not eat, drink or smoke when using this product • Wear protective gloves, clothing, face and eye protection • Avoid breathing mist, vapors or spray • Keep away from hot surfaces, sparks, open flames and other ignition sources • Use only outdoors or in a well ventilated area. Avoid release to the environment (See Safety Data Sheet for complete information.)

EMERGENCY & FIRST AID MEASURES:

Get medical attention if exposed and feel unwell, or are concerned. **IF INHALED:** Remove victim to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if feel unwell. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** Take off all contaminated clothing and wash before reuse. Wash skin with plenty of water or shower. If skin irritation occurs or you feel unwell get medical attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IN CASE OF FIRE:** Use water fog, dry chemical, CO₂ or alcohol resistant foam to extinguish. (See Safety Data Sheet for complete information)

WARRANTY:

SEK-Surebond warrants its products to substantially conform to its published specifications at the time of purchase. The foregoing is the sole limited warranty applicable to the products. **SEK-SUREBOND HEREBY DISCLAIMS ALL OTHER WARRANTIES OF ANY KIND OR NATURE, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER WARRANTY OTHER THAN THE WARRANTY SET FORTH ABOVE.** The user is solely responsible for determining suitability of the products for their particular use. While the actual application of this product is out of the control of SEK-Surebond, it is recommended that the application guidelines be followed completely and accurately. SEK-Surebond's liability for any damage shall not exceed the purchase price of the product used, and it shall have no liability for consequential, incidental or punitive damages.

ASSISTANCE & ADDITIONAL INFORMATION:

For sales, specification assistance, technical questions, detailing, etc., please contact:



3925 Stern Ave.
St. Charles, IL 60174
Email: info@sek.us.com
Fax: 630-762-0607
800-932-3343
www.sek.us.com

