

Robinets à papillon - Gamme Performance



PAPILLON
FONTE GJS-500-7
revêtu Epoxy

CORPS FONTE EN GJS-400-15

Certificat
matière 3.1
sur demande

TS : -10 °C à +110 °C.

Utilisation :

- Eaux : froide et chaude, potable.



ACS N° 14 ACC LY 224



1170 OREILLES DE CENTRAGE

Ø nominal	32/40	50	65	80	100	125	150	200	250	300
PS	16	16	16	16	16	16	16	16	16	16
PN	10/16 et CLASS 150 PN20 (sauf DN32)									
Code levier	1170040	1170050	1170065	1170080	1170100	1170125	1170150	1170200	1170250	1170300

PRIX € H.T.

Ø nominal	350	400	450	500	600
PS	10	10	10	10	10
PN	10/16 et CLASS 150 (PN20)				
Code avec réducteur	1170350	1170400	1170450	1170500	1170600

PRIX € H.T.

→ Fig. 1170 : 4 oreilles de centrage sauf pour le DN80 avec 8 oreilles de centrage.

ACS N° 14 ACC LY 224



1175 OREILLES TARAUDÉES

Ø nominal	40	50	65	80	100	125	150	200/ PN10	200/ PN16	250/ PN10	250/ PN16	300/ PN10	300/ PN16
PS	16	16	16	16	16	16	16	10	16	10	16	10	16
PN	10/16	10/16	10/16	10/16	10/16	10/16	10/16	10	16	10	16	10	16
Code levier	1175040	1175050	1175065	1175080	1175100	1175125	1175150	1175200	1175201	1175250	1175251	1175300	1175301

PRIX € H.T.

Ø nominal	350/ PN10	350/ PN16	400/ PN10	400/ PN16	450/ PN10	450/ PN16	500/ PN10	500/ PN16	600/ PN10	600/ PN16
PS	10	10	10	10	10	10	10	10	10	10
PN	10	16	10	16	10	16	10	16	10	16
Code avec réducteur	1175350	1175351	1175400	1175401	1175450	1175451	1175500	1175501	1175600	1175601

PRIX € H.T.

→ À partir du DN350 : produit sur demande.