



1. Identification

1. Identification			
Product identifier	Mortar Mix		
Other means of identification	None.		
Recommended use	Cement is used as a binder in concrete and mortars that are widely used in construction.		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Suppliier			
Company name	Southern Grouts and Mortars, Inc.		
Address	1502 SW 2nd Place		
	Pompano Beach, Florida 33069		
Telephone number	(954) 943-2288		
Fax	(954) 943-2402		
Contact name	Technical Manager		
Website	WWW.SGM.CC		
Emergency telephone number	(954) 943-2288		
2. Hazard(s) identification			
Physical hazards	Not classified.		
Health hazards	Skin corrosion/irritation	Category 2	
	Serious eye damage/eye irritation	Category 1	
	Sensitization, skin	Category 1	
	Carcinogenicity	Category 1A	
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation	
	Specific target organ toxicity, repeated exposure	Category 2 (Lung)	
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement		nage. May cause an allergic skin reaction. May . May cause damage to organs (Lung) through	
Precautionary statement			
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.		
Response	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.		
Disposal	Dispose of contents/container in accordance v	vith local/regional/national/international regulations.	

Product becomes alkaline when exposed to moisture.

3. Composition/information on ingredients

Chemical name		CAS number	%
Quartz		14808-60-7	30-75
Portland Cement		65997-15-1	15-40
Composition comments	All concentrations are in percent by weight un percent by volume.	less ingredient is a gas. Gas	s concentrations are in
4. First-aid measures			
Inhalation	Inhalation of wet product not foreseeable route remove the affected person immediately to free if you feel unwell.	e of exposure. If dust from the shair. Call a POISON CEN	ne material is inhaled, TER or doctor/physicia
Skin contact	Remove contaminated clothing immediately a eczema or other skin disorders: Seek medical contaminated clothing before reuse.		
Eye contact	Do not rub eyes. Immediately flush eyes with contact lenses, if present and easy to do. Con		
Ingestion	Never give anything by mouth to a victim who is unconscious or is having convulsions. DO NOT INDUCE VOMITING. Rinse mouth thoroughly with water and give large amounts of water, if person is conscious. Get medical attention.		
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include a vision. Permanent eye damage including blind tract, skin and eyes. Coughing. Discomfort in cause redness and pain. May cause an allerg exposure may cause chronic effects.	ness could result. Dusts mathe chest. Shortness of brea	y irritate the respiratory th. Skin irritation. May
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treas Symptoms may be delayed.	at symptomatically. Keep vic	tim under observation.
General information	IF exposed or concerned: Get medical advice of the material(s) involved, and take precautio clothing before reuse.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbo appropriate for surrounding fire.	on dioxide (CO2). Use fire-e	xtinguishing media
Unsuitable extinguishing media	None known.		
Specific hazards arising from the chemical	During fire, hazardous combustion products a	re released that may include	e: Carbon oxides (COx
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full pr	rotective clothing must be wo	orn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do s	o without risk.	
Specific methods	Use standard firefighting procedures and cons	sider the hazards of other inv	volved materials.
General fire hazards	No unusual fire or explosion hazards noted.		

6. Accidental release measures

Personal precautions,
protective equipment and
emergency proceduresKeep unnecessary personnel away. Wear appropriate protective equipment and clothing during
clean-up. Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved
respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not
touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Prevent entry into waterways, sewer, basements or confined areas. For a dry material spill, use a HEPA (high efficiency particle air) vacuum to collect material and place in a sealable container for disposal. Avoid dust formation. For a wet spill, absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for disposal. Neutralize the spill area. Use materials that can withstand the potentially corrosive nature of this product. Do not get water inside containers. Following product recovery, flush area with water.
Environmental precautions	Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Static electricity and formation of sparks must be prevented. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.
·		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CF	R 1910.1000)		
Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	50 mppcf	
Quartz (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide t	o Chemical Hazards		
Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted fo	r the ingredient(s).	
osure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
propriate engineering trols	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.		

Individual protection measures, such as personal protective equipment

individual protection measure	s, such as personal protective equipment
Eye/face protection	In situations where there is potential splash or puff exposure of cement products, wear safety glasses with side shields or goggles. In extremely dusty or unpredictable environments wear unvented or indirectly vented goggles. Contact lenses should not be worn when working with cement or cement products.
Skin protection	
Hand protection	Wear protective gloves.
Skin protection	
Other	Prevention is essential to avoiding potentially severe skin injury. Avoid contact with unhardened wet Portland cement products. If contact occurs, promptly wash affected area with soap and water. Where prolonged exposure to unhardened Portland cement products might occur, wear impervious clothing and gloves to prevent skin contact. Wear sturdy boots that are impervious to water and eliminate foot and ankle exposure. Do not rely on barrier crèmes; barrier crèmes should not be used in place of gloves.
Respiratory protection	Avoid tasks which cause dust to become airborne. Use local or general ventilation to control exposure below applicable exposure limits. Use NIOSH/MSHA approved (30 CFR 11) or NIOSH approved (42 CFR 84) respirators in poorly ventilated areas, or if an applicable exposure limit is exceeded, or when dust causes discomfort or irritation.
Thermal hazards	Not available.
General hygiene considerations	Periodically wash affected areas contacted by dry or wet cement products with a pH neutral soap. When using, do not eat, drink, or smoke. Wash again at the end of work. If clothing becomes saturated with wet cement products, it should be removed and replace with clean dry clothing.

9. Physical and chemical properties

, appearance	
Physical state	Solid.
Form	Powder. Coarse Textured Powder.
Color	Gray/white.
Odor	Odorless.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	2.5
Solubility(ies)	
Solubility (water)	Miscible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

Other informationNot explosive.Explosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

10. Stability and reactivity

Reactivity Chemical	The product is stable and non-reactive under normal conditions of use, storage and transport.
stability Possibility of	Material is stable under normal conditions.
hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Moisture.
Incompatible materials	Powerful oxidizers. Chlorine. Mineral acid.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

internation on intery routed of a		
Inhalation	Dust may irritate respiratory system. Contact with moist mucous membranes of the respiratory system can cause a caustic condition resulting in burns. May cause damage to organs through prolonged or repeated exposure by inhalation.	
Skin contact	Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet cement/mixture may cause burns.	
Eye contact	Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.	
Ingestion	Irritating. May cause nausea, stomach pain and vomiting. Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.	
Information on toxicological effects		
Acute toxicity	May cause respiratory irritation. May cause an allergic skin reaction.	
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitizatior		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

Carcinogenicity May cause cancer by inhalation. This product has the potential for generation of respirable dust during handling and use. Dust may contain respirable crystalline silica. Crystalline silica (inhaled in the form of cristobalite or quartz) has been classified by IARC, NTP and ACGIH as a known human carcinogen and suspected human carcinogen respectively. Overexposure to dust may result in pneumocononiosis, a respiratory disease caused by inhalation of mineral dust, which can lead to fibrotic changes to the lung tissue, or silicosis, a respiratory disease caused by inhalation of silica dust, which can lead to inflammation and fibrosis of the lung tissue. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. May cause delayed lung injury.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) NTP Report on Carcinogens	
Quartz (CAS 14808-60-7) OSHA Specifically Regulate) Known To Be Human Carcinogen. d Substances (29 CFR 1910.1001-1050)
Not regulated.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	May cause damage to organs (Lung) through prolonged or repeated exposure.

Aspiration hazard	Not an aspiration hazard.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Other adverse effects	None known.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.		

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations		
Clean Air Act (CAA) Sect	ion 112 Hazardous Air Pollutants (HAPs) List	
Not regulated. Clean Air Act (CAA) Secti	ion 112(r) Accidental Release Prevention (40 CFR 68.130)	
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	
US state regulations		
US. Massachusetts RTK	Substance List	
Portland Cement (CAS Quartz (CAS 14808-60		
US. New Jersey Worker a	nd Community Right-to-Know Act	
Portland Cement (CAS Quartz (CAS 14808-60	D-7)	
US. Pennsylvania Worker	r and Community Right-to-Know Law	
Portland Cement (CAS Quartz (CAS 14808-60		
US. Rhode Island RTK		
Not regulated.		
US. California Propositio	n 65 uct contains a chemical known to the State of California to cause cancer	
•	sition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed sub	
Quartz (CAS 1480		Stance
International Inventories	55-50-77	
Country(s) or region Australia	Inventory name Australian Inventory of Chemical Substances (AICS)	On inventory (yes/no)* Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	Yes
Luiope	Substances (EINECS)	165
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

Philippine Inventory of Chemicals and Chemical Substances

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Mortar Mix 933654 Version #: 01 Revision date: - Issue date: 23-May-2016

New Zealand Inventory

(PICCS)

16. Other information, including date of preparation or last revision

23-May-2016

Flammability: 0 Physical hazard: 0

-

01 Health: 3*

New Zealand

United States & Puerto Rico

Philippines

country(s).

Issue date

Version #

Revision date

HMIS® ratings

NFPA ratings

Yes

No

Yes

Southern Grouts and Mortars cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.