



TRANSITION FITTINGS OVERVIEW

Spears® Transition fittings are designed primarily for adapting plastic-to-metal systems. These fittings, especially the Special Reinforced (SR) Female Plastic Thread style, can also be used for superior strength in make-up of plastic threaded joints. Spears® offers a variety of transition adapter fittings specified below. All have standard ASTM socket sizes for IPS pipe and NPT threads, except for the Gasket Sealed style that uses a straight thread with elastomer seal. All other threads should be assembled with a quality grade thread sealant that is compatible with plastics.

Warning: Some pipe joint compounds or PTFE pastes may contain substances that could cause stress cracking in thermoplastic materials. Spears® recommends the use of Spears® **BLUE 75™** thread sealant that has been tested for compatibility with Spears® products. Choice of any other appropriate thread sealant is at the discretion of the installer.

Special Reinforced (SR) Thread Fittings: This patented fitting features all-plastic female thread construction that reduces problems associated with over-tightening of female plastic pipe threads. The external reinforcing collar is not just an added reinforcement ring, this unique precompression design compensates for expansion forces generated from tapered pipe thread joint make-up. Radial stress is reduced in normal installations and contained in severe over-tightening situations. The all-plastic internal construction provides for the maximum in chemical and corrosion benefits. Its solid construction and reliability make the SR our best transition design for all applications.

Brass Thread Fitting: This patented fitting features a molded-in-place brass thread with external reinforcing collar as an integral part of each fitting for superior strength. An internal form-compressed O-ring seal compensates for expansion and contraction variations between materials. Excellent as a metal-to-plastic transition adapter fitting.

Male Brass Thread Fitting: Developed for Copper Tube Size (CTS) hot-and-cold water distribution systems, this male brass thread alternative is the only metal thread design of its type that has the metal component lined with plastic for improved fitting construction and minimal exposure. Excellent for transition to female metal threads in a CTS system.

Gasket Sealed Thread Fittings: Also developed for Copper Tube Size (CTS) hot-and-cold water distribution systems, this female threaded fitting features all plastic internal construction for maximum corrosion resistance. The fitting incorporates straight-threads for mechanical connection, while sealing is accomplished through an internal elastomer gasket or O-ring against the pipe face. No sealants are used.

APPROVALS

Except where otherwise specified, Spears® Transition Fittings/Materials are approved for use in potable water systems by NSF® International under ANSI/NSF® Standard 61, Drinking Water System Components - Health Effects.


CPVC Orange Fittings in this price schedule (4200 series part numbers) are approved by Underwriters Laboratories, FM Global, and LPCB for use in CPVC Fire Sprinkler Systems. When installed in these system, installation must be made in accordance with Spears® publication FG-3, *FlameGuard® CPVC Fire Sprinkler Products Installation Manual*, and local codes. However, these fittings can also be used in many other types of installations. CPVC fittings may also be used on PVC pipe when installed using a quality CPVC solvent cement meeting the requirements of ASTM F 493, Standard Specification for Solvent Cements for Chlorinated Poly (Vinyl Chloride)(CPVC) Plastic Pipe and Fittings.



Transition Fittings & Adapters PVC White Special Reinforced (SR) Fittings


Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Female Adapter Soc x SR Fipt - Stainless Steel Collar




435-002SR	1/4	25	450	046	5.59
435-003SR	3/8	25	300	046	5.59
435-005SR	1/2	25	300	046	3.11
435-007SR	3/4	25	300	046	4.52
435-010SR	1	25	200	046	6.72
435-012SR	1-1/4	10	60	046	10.86
435-015SR	1-1/2	10	80	046	13.37
435-020SR	2	10	0	046	23.32
435-025SR	2-1/2	5	0	046	36.79
435-030SR	3	10	0	046	41.45
435-040SR	4	5	0	046	71.24

Special Reinforced Tee Soc x SR Fipt - Stainless Steel Collar




402-005SR	1/2	25	200	046	8.06
402-012SR	1-1/4	25	0	046	15.85

Special Reinforced Reducing Tee Soc x SR Fipt - Stainless Steel Collar




402-072SR	1/2X1/4	25	150	046	8.06
402-098SR	3/4X1/4	25	100	046	10.47
402-101SR	3/4X1/2	50	0	046	10.47
402-166SR	1-1/4X1/2	15	0	046	17.52
402-168SR	1-1/4X1	10	0	046	17.87
402-212SR	1-1/2X1-1/4	10	0	046	19.35
402-287SR	2-1/2X1/2	10	0	046	23.55
402-288SR	2-1/2X3/4	10	0	046	24.88
402-289SR	2-1/2X1	10	0	046	25.13
402-290SR	2-1/2X1-1/4	10	0	046	24.74
402-291SR	2-1/2X1-1/2	10	0	046	25.72
402-292SR	2-1/2X2	10	0	046	25.93
402-333SR	3X1/2	10	0	046	31.40
402-334SR	3X3/4	10	0	046	31.40
402-335SR	3X1	10	0	046	32.03
402-336SR	3X1-1/4	10	0	046	32.78
402-337SR	3X1-1/2	10	0	046	32.49
402-338SR	3X2	6	0	046	34.42
402-417SR	4X1	6	0	046	41.59
402-419SR	4X1-1/2	10	0	046	45.68
402-420SR	4X2	10	0	046	47.17
402-422SR	4X3	6	0	046	74.11

Special Reinforced Reducing Tee Soc x SR Fipt-Stainless Steel Collar x Soc



403-095SR	3/4X1/2X3/4	50	0	046	2.73
-----------	-------------	----	---	-----	------

Special Reinforced 90° El & Reducing 90° El Soc x SR Fipt - Stainless Steel Collar




407-005SR	1/2	50	400	046	7.15
407-007SR	3/4	75	0	046	9.18
407-010SR	1	50	0	046	9.28
407-012SR	1-1/4	25	0	046	11.22
407-131SR	1X3/4	50	0	046	3.94
407-168SR ¹	1-1/4X1	25	0	046	15.55
407-249SR	2X1	10	0	046	17.68
407-251SR	2X1-1/2	10	0	046	18.65

Sized with SR Adapter


Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Coupling SR Fipt - Stainless Steel Collar




430-005SR	1/2	25	300	046	3.69
430-007SR	3/4	25	300	046	5.25
430-010SR	1	25	200	046	5.61
430-012SR	1-1/4	10	120	046	6.99
430-015SR	1-1/2	10	60	046	15.47
430-020SR	2	10	0	046	16.22

Special Reinforced Reducer Coupling SR Fipt - Stainless Steel Collar




430-101SR	3/4X1/2	50	200	046	7.96
-----------	---------	----	-----	-----	------

Special Reinforced Spigot Female Adapter Spig x SR Fipt - Stainless Steel Collar



478-005SR	1/2	50	600	046	4.08
478-007SR	3/4	25	300	046	4.81
478-010SR	1	50	0	046	7.41
478-012SR	1-1/4	25	0	046	11.80
478-015SR	1-1/2	25	0	046	14.15
478-020SR	2	15	0	046	23.55
478-030SR	3	5	0	046	43.28
478-040SR	4	5	0	046	66.85


Special Reinforced Reducing Spigot Female Adapter Spig x SR Fipt - Stainless Steel Collar



478-072SR	1/2X1/4	25	450	046	11.35
478-098SR	3/4X1/4	50	300	046	16.53
478-128SR	1X1/4	50	400	046	17.04


Spears® SR Series reinforced spigot adapters can be user-installed in a variety of socket type tees, elbows and reducer bushings for superior thread reinforcement demanding applications.

Special Reinforced Reducing Female Adapter Soc x SR Fipt - Stainless Steel Collar



435-072SR	1/2X1/4	50	600	046	4.06
435-074SR	1/2X3/4	50	400	046	4.52
435-101SR	3/4X1/2	50	400	046	4.52
435-102SR	3/4X1	50	0	046	6.72
435-130SR	1X1/2	50	0	046	6.72
435-131SR	1X3/4	25	200	046	6.72

Special Reinforced Reducer Bushing Flush Style Spig x SR Fipt - Stainless Steel Collar



438-128SR	1X1/4	25	150	046	3.31
438-166SR	1-1/4X1/2	25	100	046	6.04
438-207SR	1-1/2X1/4	25	100	046	8.43
438-209SR	1-1/2X1/2	25	100	046	8.43
438-210SR	1-1/2X3/4	25	100	046	8.43
438-247SR	2X1/2	10	80	046	10.32
438-248SR	2X3/4	10	80	046	10.32
438-249SR	2X1	10	80	046	10.32
438-334SR	3X3/4	10	0	046	40.38
438-335SR	3X1	10	0	046	40.38
438-336SR	3X-1/4	10	0	046	40.38
438-337SR	3X1-1/2	10	0	046	40.38
438-420SR	4X2	6	0	046	62.07
438-421SR	4X2-1/2	6	0	046	69.86
438-528SR	6X2	5	0	046	71.48
438-530SR	6X3	5	0	046	64.35

Transition Fittings & Adapters
PVC White Special Reinforced (SR) Fittings & PVC White Brass Thread Fittings



PVC White Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Reducer Bushing Flush Style

(continued)


Spig x SR Fipt - Stainless Steel Collar

438-532SR	6X4	5	0	046	71.48
-----------	-----	---	---	-----	-------

Special Reinforced Reducer Bushing Flush Style

Mipt X SR Fipt - Stainless Steel Collar

439-209SR	1-1/2X1/2	25	300	046	8.74
439-248SR	2X3/4	10	60	046	7.91
439-249SR	2X1	10	120	046	12.83



Special Reinforced Cap
SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	6.74
-----------	-------	----	-----	-----	------




Special Reinforced Union

Soc x SR Fipt with Buna O-ring Seal - Stainless Steel Collar

235 psi @ 73°F (23°C)

459-002SR	1/4	25	150	046	15.32
459-003SR	3/8	25	100	046	15.32
459-005SR	1/2	10	60	046	8.32
459-007SR	3/4	10	40	046	11.45
459-010SR	1	10	40	046	15.24




Special Reinforced Union (continued)

Soc x SR Fipt with Buna O-ring Seal - Stainless Steel Collar

459-012SR	1-1/4	5	20	046	29.09
459-015SR	1-1/2	5	0	046	36.01
459-020SR	2	5	0	046	55.46
459-030SR	3	5	0	046	130.95
459-040SR	4	4	0	046	150.35
459-060SR	6	1	0	046	334.11

Special Reinforced Union

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi @ 73°F (23°C)

499-002SR	1/4	25	150	046	16.82
499-003SR	3/8	25	100	046	16.82
499-005SR	1/2	10	60	046	9.14
499-007SR	3/4	10	40	046	12.59
499-010SR	1	10	40	046	16.73
499-012SR	1-1/4	5	20	046	31.97
499-015SR	1-1/2	5	0	046	39.58
499-020SR	2	5	0	046	60.95
499-030SR	3	5	0	046	143.91
499-040SR	4	4	0	046	165.21
499-060SR	6	1	0	046	367.16

PVC White Brass Thread Fittings


Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Transition Union

Soc x Fipt with Brass Thread Insert & Buna-N O-ring Seal

235 psi @ 73°F (23°C)

459-010BR	1	10	0	046	64.74
459-012BR	1-1/4	5	20	046	108.76
459-015BR	1-1/2	5	0	046	143.89
459-020BR	2	5	0	046	191.94




Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Union

Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi @ 73°F (23°C)

499-010BR	1	10	0	046	64.74
499-012BR	1-1/4	5	20	046	108.76
499-015BR	1-1/2	5	0	046	143.89
499-020BR	2	5	0	046	191.94



Not intended to convey or dispense water for human consumption through drinking or cooking




Transition Fittings & Adapters PVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Tee


Soc x SR Fipt - Stainless Steel Collar



802-005SR	1/2	25	200	086	8.06
802-007SR	3/4	15	120	086	11.40
802-010SR	1	15	0	086	13.39
802-012SR	1-1/4	25	0	086	15.93
802-015SR	1-1/2	10	0	086	16.83
802-020SR	2	10	0	086	32.93
802-030SR	3	5	0	086	71.16
802-040SR	4	5	0	086	133.45

Special Reinforced Tee


SR Fipt - Stainless Steel Collar



805-002SR	1/4	25	150	086	9.38
805-003SR	3/8	25	150	086	9.38
805-005SR	1/2	25	150	086	9.68
805-007SR	3/4	25	100	086	10.64
805-010SR	1	15	0	086	25.29
805-015SR	1-1/2	10	0	086	29.60
805-020SR	2	10	0	086	31.12

Special Reinforced Reducing Tee

Soc x SR Fipt - Stainless Steel Collar




802-072SR	1/2X1/4	25	150	086	8.06
802-098SR	3/4X1/4	25	100	086	10.47
802-101SR	3/4X1/2	50	0	086	10.47
802-128SR ¹	1X1/4	10	80	086	24.79
802-130SR	1X1/2	50	0	086	12.92
802-131SR	1X3/4	15	0	086	24.79
802-164SR ¹	1-1/4X1/4	5	0	086	26.43
802-166SR	1-1/4X1/2	25	0	086	17.52
802-168SR	1-1/4X1	10	0	086	17.87
802-207SR ¹	1-1/2X1/4	10	0	086	30.84
802-211SR	1-1/2X1	10	0	086	19.35
802-212SR	1-1/2X1-1/4	10	0	086	19.35
802-245SR ¹	2X1/4	10	0	086	35.62
802-247SR	2X1/2	10	0	086	35.62
802-248SR	2X3/4	10	0	086	35.62
802-287SR	2-1/2X1/2	10	0	086	26.25
802-331SR ¹	3X1/4	5	0	086	68.00
802-333SR ¹	3X1/2	5	0	086	69.97
802-413SR ¹	4X1/4	5	0	086	93.64
802-415SR ¹	4X1/2	5	0	086	101.77

¹ Sized with Bushing

Special Reinforced Reducing Tee

Soc x SR Fipt - Stainless Steel Collar x Soc




(See also Gauge & Instrument Fittings for additional configurations)

803-095SR	3/4X1/2X3/4	15	0	086	13.19
-----------	-------------	----	---	-----	-------

Special Reinforced 90° EII


Soc x SR Fipt - Stainless Steel Collar



807-005SR	1/2	20	240	086	7.72
807-007SR	3/4	75	0	086	9.18
807-010SR	1	50	0	086	9.28
807-012SR	1-1/4	25	0	086	12.47
807-015SR	1-1/2	10	0	086	15.41
807-020SR	2	10	0	086	17.68
807-030SR	3	5	0	086	44.89
807-040SR	4	5	0	086	79.32

Special Reinforced 90° EII


SR Fipt - Stainless Steel Collar



808-003SR	3/8	25	150	086	4.51
808-005SR	1/2	20	120	086	4.51
808-007SR	3/4	20	120	086	5.67
808-010SR	1	50	0	086	6.60
808-012SR	1-1/4	25	0	086	7.05
808-015SR	1-1/2	10	0	086	11.00
808-020SR	2	10	0	086	12.39

Special Reinforced Reducing 90° EII

Soc x SR Fipt - Stainless Steel Collar



807-101SR	3/4X1/2	50	0	086	9.16
807-130SR	1X1/2	50	0	086	10.28

Special Reinforced 45° EII


SR Fipt - Stainless Steel Collar



819-007SR	3/4	10	120	086	7.76
-----------	-----	----	-----	-----	------

Special Reinforced Coupling


SR Fipt - Stainless Steel Collar



830-005SR	1/2	25	150	086	3.69
830-007SR	3/4	25	150	086	5.25
830-010SR	1	25	200	086	5.61
830-012SR	1-1/4	10	120	086	6.99
830-015SR	1-1/2	10	80	086	15.47
830-020SR	2	10	0	086	16.22

Special Reinforced Reducer Coupling


SR Fipt - Stainless Steel Collar



830-101SR	3/4X1/2	50	200	086	4.78
830-130SR	1X1/2	50	0	086	7.09
830-131SR	1X3/4	25	200	086	7.09
830-168SR	1-1/4X1	25	0	086	15.22
830-210SR	1-1/2X3/4	25	0	086	22.59
830-211SR	1-1/2X1	10	80	086	22.59
830-212SR	1-1/2X1-1/4	10	80	086	22.59
830-249SR	2X1	25	0	086	29.94
830-251SR	2X1-1/2	10	0	086	29.94

Special Reinforced Female Adapter

Soc x SR Fipt - Stainless Steel Collar




835-002SR	1/4	25	450	086	5.59
835-003SR	3/8	25	300	086	5.59
835-005SR	1/2	25	300	086	3.11
835-007SR	3/4	25	300	086	4.52
835-010SR	1	25	200	086	6.72
835-012SR	1-1/4	10	60	086	10.86
835-015SR	1-1/2	10	80	086	13.37
835-020SR	2	10	0	086	23.32
835-025SR	2-1/2	5	0	086	36.79
835-030SR	3	15	0	086	41.45
835-040SR	4	5	0	086	71.24
835-060SR	6	6	0	086	92.56

Encapsulated Special Reinforced Female

Adapter

Soc x ESR Fipt




835-002ESR	1/4	25	450	086	8.09
------------	-----	----	-----	-----	------

Transition Fittings & Adapters PVC Gray Special Reinforced (SR) Fittings




Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
Encapsulated Special Reinforced Female Adapter (continued) Soc x ESR Fipt					
835-003ESR	3/8	25	300	086	8.09
835-005ESR	1/2	25	300	086	5.02
835-007ESR	3/4	25	300	086	7.41
835-010ESR	1	25	200	086	9.81
835-012ESR	1-1/4	10	80	086	15.83
835-015ESR	1-1/2	10	80	086	22.87
835-020ESR	2	10	0	086	34.00

Special Reinforced Spigot Female Adapter Spig x SR Fipt - Stainless Steel Collar




878-005SR	1/2	50	600	086	4.08
878-007SR	3/4	25	300	086	4.81
878-010SR	1	50	0	086	7.41
878-012SR	1-1/4	25	0	086	11.80
878-015SR	1-1/2	25	0	086	14.15
878-020SR	2	15	0	086	23.55
878-030SR	3	5	0	086	43.28
878-040SR	4	5	0	086	73.48

Encapsulated Special Reinforced Spigot Female Adapter Spig x ESR Fipt




878-005ESR	1/2	50	600	086	5.57
878-007ESR	3/4	25	300	086	7.67
878-010ESR	1	50	0	086	10.53
878-012ESR	1-1/4	25	0	086	16.20
878-015ESR	1-1/2	25	0	086	23.00
878-020ESR	2	15	0	086	34.66

Special Reinforced Reducing Female Adapter Soc x SR Fipt - Stainless Steel Collar



835-074SR	1/2X3/4	50	400	086	4.52
835-101SR	3/4X1/2	50	400	086	4.52
835-102SR	3/4X1	50	0	086	6.72
835-130SR	1X1/2	50	0	086	6.72
835-131SR	1X3/4	25	200	086	6.72

Special Reinforced Reducing Spigot Female Adapter Spig x SR Fipt - Stainless Steel Collar



878-072SR	1/2X1/4	25	450	086	11.35
878-098SR	3/4X1/4	50	400	086	15.64
878-128SR	1X1/4	50	400	086	16.13

Reinforced Male Adapter R Mipt x Soc - Stainless Steel Sleeve




836-005R	1/2	25	150	086	3.84
836-007R	3/4	25	300	086	4.21
836-010R	1	10	60	086	7.38

Special Reinforced Reducer Bushing Mipt x SR Fipt - Stainless Steel Collar



839-128SR	1X1/4	25	150	086	5.98
839-209SR	1-1/2X1/2	25	300	086	8.74
839-210SR	1-1/2X3/4	25	300	086	8.74
839-247SR	2X1/2	10	60	086	12.83
839-248SR	2X3/4	10	60	086	12.83
839-249SR	2X1	10	120	086	12.83
839-420SR	4X2	6	0	086	48.59

Special Reinforced Reducer Bushing Flush Style



Spig x SR Fipt - Stainless Steel Collar

838-128SR	1X1/4	25	150	086	3.31
838-166SR	1-1/4X1/2	25	100	086	6.04
838-207SR	1-1/2X1/4	25	200	086	8.43
838-209SR	1-1/2X1/2	10	60	086	8.43
838-210SR	1-1/2X3/4	25	200	086	8.43
838-247SR	2X1/2	10	80	086	10.32
838-248SR	2X3/4	10	80	086	10.32
838-249SR	2X1	10	80	086	10.32
838-334SR	3X3/4	10	0	086	40.38
838-335SR	3X1	10	0	086	40.38
838-336SR	3X1-1/4	10	0	086	40.38
838-337SR	3X1-1/2	10	0	086	40.38
838-528SR	6X2	5	0	086	71.48
838-530SR	6X3	5	0	086	64.35
838-532SR	6X4	5	0	086	71.48

Special Reinforced Cap SR Fipt - Stainless Steel Collar



848-002SR	1/4	25	500	086	4.03
848-003SR	3/8	25	450	086	4.03
848-005SR	1/2	50	300	086	4.41
848-007SR	3/4	25	300	086	5.65
848-030SR	3	5	0	086	34.84

Special Reinforced Union 2000 Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005SR	1/2	20	160	086	8.00
8099-007SR	3/4	20	80	086	11.40
8099-010SR	1	15	90	086	14.71
8099-012SR	1-1/4	10	0	086	25.58
8099-015SR	1-1/2	10	0	086	33.15
8099-020SR	2	5	0	086	53.35
8099-025SR	2-1/2	5	0	086	114.12
8099-030SR	3	5	0	086	127.04
8099-040SR	4	4	0	086	144.99
8099-060SR	6	1	0	086	322.21

Special Reinforced Union 2000 Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005SR	1/2	20	160	086	8.32
8059-007SR	3/4	20	80	086	11.45
8059-010SR	1	15	90	086	14.88
8059-012SR	1-1/4	10	0	086	28.44
8059-015SR	1-1/2	10	0	086	35.09
8059-020SR	2	5	0	086	53.59
8059-025SR	2-1/2	5	0	086	115.19
8059-030SR	3	5	0	086	130.95
8059-040SR	4	4	0	086	150.35
8059-060SR	6	1	0	086	334.11

Special Reinforced Union 2000 SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005SR	1/2	20	120	086	8.43
8098-007SR	3/4	20	80	086	11.48
8098-010SR	1	15	90	086	15.20



Transition Fittings & Adapters PVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Union 2000 (continued)

SR Fipt with EPDM O-ring Seal - Stainless Steel Collar

8098-012SR	1-1/4	10	0	086	28.26
8098-015SR	1-1/2	10	0	086	35.55
8098-020SR	2	5	0	086	55.86
8098-025SR	2-1/2	5	0	086	112.75
8098-030SR	3	5	0	086	132.97
8098-040SR	4	4	0	086	152.65
8098-060SR	6	1	0	086	339.26

Special Reinforced Union 2000

SR Fipt with FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005SR	1/2	20	120	086	8.56
8058-007SR	3/4	20	80	086	11.59
8058-010SR	1	15	90	086	15.51
8058-012SR	1-1/4	10	0	086	29.54
8058-015SR	1-1/2	10	0	086	36.35
8058-020SR	2	5	0	086	56.44
8058-025SR	2-1/2	5	0	086	118.02
8058-030SR	3	5	0	086	134.25
8058-040SR	4	4	0	086	158.04
8058-060SR	6	1	0	086	351.19

Special Reinforced Union (Old Style)

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002SR	1/4	25	150	086	15.11
899-003SR	3/8	25	100	086	15.11
899-005SR	1/2	10	60	086	8.00
899-007SR	3/4	10	40	086	11.40
899-010SR	1	10	40	086	14.71
899-012SR	1-1/4	5	20	086	25.58
899-015SR	1-1/2	5	0	086	33.15
899-020SR	2	5	0	086	53.35
899-030SR	3	5	0	086	127.04
899-040SR	4	4	0	086	144.99

Special Reinforced Union (Old Style)

Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-005SR	1/2	10	60	086	8.32
859-007SR	3/4	10	40	086	11.45
859-010SR	1	10	40	086	14.88
859-012SR	1-1/4	5	20	086	28.44
859-015SR	1-1/2	5	0	086	35.09
859-020SR	2	5	0	086	53.59
859-030SR	3	5	0	086	130.95
859-040SR	4	4	0	086	150.35

Special Reinforced Flange One Piece

Threaded

SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005SR	1/2	25	0	086	11.91
852-007SR	3/4	25	0	086	13.99
852-010SR	1	15	0	086	15.29
852-012SR	1-1/4	15	0	086	21.07
852-015SR	1-1/2	15	0	086	23.06
852-020SR	2	10	0	086	23.62
852-025SR	2-1/2	10	0	086	54.09
852-030SR	3	10	0	086	55.69
852-040SR	4	5	0	086	104.69

PVC New Style Special Reinforced (SR)

Threaded Tank Adapters with Neoprene Gaskets



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002SR	1/4	25	150	100	35.58
8171-003SR	3/8	25	200	100	35.58
8171-005SR	1/2	25	0	100	35.58
8171-007SR	3/4	25	0	100	41.22
8171-010SR	1	25	0	100	46.42
8171-012SR	1-1/4	20	0	100	57.06
8171-015SR	1-1/2	20	0	100	65.49
8171-020SR	2	15	0	100	93.86
8171-025SR	2-1/2	4	0	100	151.13
8171-030SR	3	4	0	100	179.89
8171-040SR	4	2	0	100	332.76
8171-060SR	6	1	0	100	622.77

PVC New Style Special Reinforced (SR)

Threaded Tank Adapters with EPDM Gaskets



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002SR	1/4	25	150	100	36.83
8171E-003SR	3/8	25	200	100	36.83
8171E-005SR	1/2	25	0	100	36.83
8171E-007SR	3/4	25	0	100	42.00
8171E-010SR	1	25	0	100	51.06
8171E-012SR	1-1/4	20	0	100	61.86
8171E-015SR	1-1/2	20	0	100	70.31
8171E-020SR	2	15	0	100	100.36
8171E-025SR	2-1/2	4	0	100	156.03
8171E-030SR	3	4	0	100	185.76
8171E-040SR	4	2	0	100	340.58
8171E-060SR	6	1	0	100	644.19

PVC New Style Special Reinforced (SR)

Threaded Tank Adapters with FKM Gaskets



Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002SR	1/4	25	150	100	59.79
8171V-003SR	3/8	25	200	100	59.79
8171V-005SR	1/2	25	0	100	59.79
8171V-007SR	3/4	25	0	100	65.61
8171V-010SR	1	25	0	100	80.87
8171V-012SR	1-1/4	20	0	100	90.56
8171V-015SR	1-1/2	20	0	100	102.08
8171V-020SR	2	15	0	100	156.33
8171V-025SR	2-1/2	4	0	100	238.00
8171V-030SR	3	4	0	100	283.32
8171V-040SR	4	2	0	100	680.71
8171V-060SR	6	2	0	100	1206.42

PVC New Style Special Reinforced (SR)

Threaded Tank Adapters with Neoprene Gaskets



Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002SR	1/4	25	150	100	47.57
8172-003SR	3/8	25	200	100	47.57
8172-005SR	1/2	25	0	100	47.57
8172-007SR	3/4	25	0	100	52.66
8172-010SR	1	25	0	100	58.24
8172-012SR	1-1/4	20	0	100	78.43
8172-015SR	1-1/2	20	0	100	88.39
8172-020SR	2	15	0	100	114.53
8172-025SR	2-1/2	4	0	100	174.37

Transition Fittings & Adapters PVC Gray Special Reinforced (SR) Fittings




Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets (continued)

Fipt x SR Fipt - Stainless Steel Collar

8172-030SR	3	4	0	100	207.59
8172-040SR	4	2	0	100	369.57
8172-060SR	6	1	0	100	714.88

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with EPDM Gaskets




Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002SR	1/4	25	150	100	48.94
8172E-003SR	3/8	25	200	100	48.94
8172E-005SR	1/2	25	0	100	48.94
8172E-007SR	3/4	25	0	100	53.65
8172E-010SR	1	25	0	100	64.19
8172E-012SR	1-1/4	20	0	100	85.21
8172E-015SR	1-1/2	20	0	100	95.06
8172E-020SR	2	15	0	100	122.60
8172E-025SR	2-1/2	4	0	100	180.17
8172E-030SR	3	4	0	100	214.46
8172E-040SR	4	2	0	100	378.38
8172E-060SR	6	1	0	100	739.66

PVC New Style Special Reinforced (SR) Threaded Tank Adapters with FKM Gaskets



Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002SR	1/4	25	150	100	72.79
8172V-003SR	3/8	25	200	100	72.79
8172V-005SR	1/2	25	0	100	72.79
8172V-007SR	3/4	25	0	100	78.15
8172V-010SR	1	25	0	100	89.78
8172V-012SR	1-1/4	20	0	100	103.21
8172V-015SR	1-1/2	20	0	100	120.48
8172V-020SR	2	15	0	100	175.36
8172V-025SR	2-1/2	4	0	100	257.49
8172V-030SR	3	4	0	100	306.62
8172V-040SR	4	2	0	100	714.88
8172V-060SR	6	2	0	100	1349.89

PVC Elastomer Expansion Joint

with Neoprene Bellows SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ01-007SR	3/4	10	0	085	200.62
EJ01-010SR	1	10	0	085	228.47
EJ01-012SR	1-1/4	15	0	085	248.49
EJ01-015SR	1-1/2	10	0	085	317.23
EJ01-020SR	2	8	0	085	381.13
EJ01-025SR	2-1/2	4	0	085	555.41
EJ01-030SR	3	2	0	085	746.94

PVC Elastomer Expansion Joint

with EPDM Bellows SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ21-007SR	3/4	10	0	085	204.69
EJ21-010SR	1	10	0	085	233.14
EJ21-012SR	1-1/4	15	0	085	253.59
EJ21-015SR	1-1/2	10	0	085	323.68
EJ21-020SR	2	8	0	085	388.92
EJ21-025SR	2-1/2	4	0	085	563.59
EJ21-030SR	3	2	0	085	762.18



Transition Fittings & Adapters PVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Transition Tee

Soc x Fipt With Brass Thread Insert




802-005BR	1/2	20	160	086	32.92
802-007BR	3/4	20	80	086	65.97

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Reducing Tee

Soc x Fipt With Brass Thread Insert




802-101BR	3/4X1/2	50	0	086	41.08
-----------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition 90° El

Soc x Fipt With Brass Thread Insert



807-005BR	1/2	20	240	086	28.92
807-007BR	3/4	20	160	086	51.19

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Reducing 90° El

Soc x Fipt With Brass Thread Insert




807-101BR	3/4X1/2	20	120	086	36.09
-----------	---------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter

Soc x Fipt With Brass Thread Insert




835-005BR	1/2	25	150	086	24.97
835-007BR	3/4	25	150	086	35.86
835-010BR	1	15	90	086	61.80
835-012BR	1-1/4	15	60	086	101.77
835-015BR	1-1/2	10	40	086	133.69
835-020BR	2	8	32	086	165.59

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter

Spig x Fipt With Brass Thread Insert




878-005BR	1/2	25	150	086	21.00
878-010BR	1	15	90	086	66.81

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Reducing Female Adapter

Soc x Fipt With Brass Thread Insert




835-101BR	3/4X1/2	50	0	086	37.07
-----------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter

Soc x Fipt With 316 Stainless Steel Thread Insert



835-005SS	1/2	25	300	086	48.93
835-007SS	3/4	15	90	086	70.32
835-010SS	1	15	90	086	119.65
835-012SS	1-1/4	15	60	086	199.83
835-015SS	1-1/2	10	40	086	261.04
835-020SS	2	8	32	086	334.87

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Transition Male Adapter w/ Brass Thread


Brass Mipt x Socket



836-005BR	1/2	40	160	086	27.48
836-007BR	3/4	40	160	086	41.44
836-010BR	1	10	60	086	67.39
836-012BR	1-1/4	10	60	086	113.52
836-015BR	1-1/2	10	40	086	150.63
836-020BR	2	8	32	086	187.13

Union

Soc x Fipt with Brass Thread Insert & FKM O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007BR	3/4	10	40	086	53.19
859-010BR	1	10	0	086	65.64
859-012BR	1-1/4	5	20	086	113.29
859-015BR	1-1/2	5	0	086	149.94
859-020BR	2	5	0	086	199.26

Not intended to convey or dispense water for human consumption through drinking or cooking

Union

Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007BR	3/4	10	40	086	47.96
899-010BR	1	10	0	086	64.68
899-012BR	1-1/4	5	20	086	108.77
899-015BR	1-1/2	5	0	086	143.96
899-020BR	2	5	0	086	191.89

Not intended to convey or dispense water for human consumption through drinking or cooking


Transition Fittings & Adapters CPVC Gray Special Reinforced (SR) Fittings



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

Special Reinforced Tee


Soc x SR Fipt - Stainless Steel Collar



802-005CSR	1/2	50	0	096	19.67
802-007CSR	3/4	15	120	096	28.75
802-010CSR	1	15	0	096	36.17
802-012CSR	1-1/4	15	0	096	41.96
802-015CSR	1-1/2	10	0	096	41.96
802-020CSR	2	10	0	096	68.59
802-030CSR	3	5	0	096	98.78
802-040CSR	4	5	0	096	186.09

Special Reinforced Tee


SR Fipt - Stainless Steel Collar



805-002CSR	1/4	20	160	096	17.60
805-003CSR	3/8	25	150	096	17.60
805-005CSR	1/2	25	150	096	23.55
805-007CSR	3/4	25	100	096	26.98
805-010CSR	1	15	0	096	40.29
805-015CSR	1-1/2	10	0	096	42.78
805-020CSR	2	10	0	096	50.94

Special Reinforced Reducing Tee

Soc x SR Fipt - Stainless Steel Collar



802-072CSR	1/2X1/4	25	200	096	19.67
802-098CSR	3/4X1/4	25	100	096	26.29
802-101CSR	3/4X1/2	50	0	096	26.29
802-128CSR ¹	1X1/4	15	0	096	40.60
802-130CSR	1X1/2	50	0	096	16.06
802-131CSR	1X3/4	15	0	096	40.60
802-164CSR ¹	1-1/4X1/4	5	0	096	53.99
802-166CSR	1-1/4X1/2	15	0	096	42.77
802-168CSR	1-1/4X1	10	0	096	43.64
802-207CSR ¹	1-1/2X1/4	15	0	096	77.31
802-211CSR	1-1/2X1	10	0	096	51.24
802-212CSR	1-1/2X1-1/4	10	0	096	51.24
802-245CSR ¹	2X1/4	10	0	096	88.80
802-247CSR	2X1/2	10	0	096	79.93
802-248CSR	2X3/4	10	0	096	88.80
802-287CSR	2-1/2X1/2	10	0	096	61.07
802-331CSR ¹	3X1/4	5	0	096	169.62
802-413CSR ¹	4X1/4	5	0	096	184.06

¹ Sized with Bushing

Special Reinforced Reducing Tee

Soc x SR Fipt - Stainless Steel Collar x Soc




(See also Gauge & Instrument Fittings for additional configurations)

803-095CSR	3/4X1/2X3/4	15	0	096	16.20
------------	-------------	----	---	-----	-------

Special Reinforced 90° El

Soc x SR Fipt - Stainless Steel Collar



807-005CSR	1/2	20	240	096	9.55
807-007CSR	3/4	75	0	096	11.22
807-010CSR	1	50	0	096	13.51
807-012CSR	1-1/4	25	0	096	27.89
807-015CSR	1-1/2	10	0	096	33.53
807-020CSR	2	10	0	096	41.95

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

Special Reinforced 90° El


SR Fipt - Stainless Steel Collar



808-003CSR	3/8	25	150	096	5.77
808-005CSR	1/2	20	120	096	5.77
808-007CSR	3/4	20	160	096	8.45
808-010CSR	1	50	0	096	10.83
808-012CSR	1-1/4	25	0	096	20.84
808-015CSR	1-1/2	10	0	096	24.54
808-020CSR	2	10	0	096	32.87

Special Reinforced Reducing 90° El

Soc x SR Fipt - Stainless Steel Collar



807-101CSR	3/4X1/2	50	0	096	12.17
807-130CSR	1X1/2	50	0	096	13.12

Special Reinforced 45° El


SR Fipt - Stainless Steel Collar



819-007CSR	3/4	10	120	096	13.19
------------	-----	----	-----	-----	-------

Special Reinforced Coupling


SR Fipt - Stainless Steel Collar



830-005CSR	1/2	25	300	096	9.31
830-007CSR	3/4	25	300	096	15.04
830-010CSR	1	25	200	096	17.08
830-012CSR	1-1/4	10	120	096	18.15
830-015CSR	1-1/2	10	80	096	19.46
830-020CSR	2	10	0	096	23.00

Special Reinforced Reducer Coupling


SR Fipt - Stainless Steel Collar



830-101CSR	3/4X1/2	50	200	096	16.68
830-130CSR	1X1/2	50	0	096	20.14
830-131CSR	1X3/4	25	200	096	20.14
830-168CSR	1-1/4X1	25	0	096	27.39
830-210CSR	1-1/2X3/4	25	0	096	39.17
830-211CSR	1-1/2X1	10	80	096	39.17
830-212CSR	1-1/2X1-1/4	10	80	096	39.17
830-249CSR	2X1	25	0	096	96.42
830-251CSR	2X1-1/2	15	0	096	96.42

Special Reinforced Female Adapter


Soc x SR Fipt - Stainless Steel Collar



835-002CSR	1/4	25	450	096	13.06
835-003CSR	3/8	25	300	096	13.06
835-005CSR	1/2	25	300	096	5.61
835-007CSR	3/4	25	150	096	6.06
835-010CSR	1	25	200	096	13.82
835-012CSR	1-1/4	10	60	096	14.18
835-015CSR	1-1/2	10	80	096	16.46
835-020CSR	2	10	0	096	23.39
835-025CSR	2-1/2	5	0	096	54.39
835-030CSR	3	15	0	096	111.75
835-040CSR	4	5	0	096	185.99
835-060CSR	6	6	0	096	290.55

Encapsulated Special Reinforced (SR) Female Adapter

Soc x ESR Fipt



835-002CESR	1/4	25	450	096	16.57
-------------	-----	----	-----	-----	-------



Transition Fittings & Adapters CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Encapsulated Special Reinforced (SR) Female Adapter


(continued)

Soc x ESR Fipt

835-003CESR	3/8	25	300	096	16.57
835-005CESR	1/2	25	300	096	8.60
835-007CESR	3/4	25	300	096	9.08
835-010CESR	1	25	200	096	20.01
835-012CESR	1-1/4	10	80	096	20.48
835-015CESR	1-1/2	10	0	096	26.52
835-020CESR	2	10	0	096	41.22

Special Reinforced Spigot Female Adapter


Spig x SR Fipt - Stainless Steel Collar



878-005CSR	1/2	50	600	096	5.98
878-007CSR	3/4	25	300	096	6.31
878-010CSR	1	50	0	096	14.19
878-012CSR	1-1/4	25	0	096	14.68
878-015CSR	1-1/2	25	0	096	17.04
878-020CSR	2	15	0	096	31.04
878-030CSR	3	5	0	096	113.15
878-040CSR	4	5	0	096	189.95

Special Reinforced Reducing Female Adapter


Soc x SR Fipt - Stainless Steel Collar



835-074CSR	1/2X3/4	50	400	096	6.06
835-101CSR	3/4X1/2	50	400	096	6.06
835-102CSR	3/4X1	50	0	096	13.82
835-130CSR	1X1/2	50	0	096	13.82
835-131CSR	1X3/4	25	200	096	13.82

Encapsulated Special Reinforced (SR) Female Adapter


Spig x ESR Fipt



878-005CESR	1/2	50	600	096	8.85
878-007CESR	3/4	25	300	096	9.42
878-010CESR	1	50	0	096	20.20
878-012CESR	1-1/4	25	0	096	20.75
878-015CESR	1-1/2	25	0	096	27.05
878-020CESR	2	15	0	096	41.81

Special Reinforced Reducing Spigot Female Adapter


Spig x SR Fipt - Stainless Steel Collar



878-072CSR	1/2X1/4	25	450	096	17.14
878-098CSR	3/4X1/4	50	400	096	19.95
878-128CSR	1X1/4	50	400	096	22.33

Reinforced Male Adapter


R Mipt x Soc - Stainless Steel Sleeve



836-005CR	1/2	25	150	096	8.62
836-007CR	3/4	25	300	096	9.87
836-010CR	1	10	120	096	11.71

Special Reinforced Reducing Bushing

Mipt x SR Fipt - Stainless Steel Collar




839-209CSR	1-1/2X1/2	25	300	096	22.11
839-210CSR	1-1/2X3/4	25	300	096	22.11
839-247CSR	2X1/2	10	60	096	24.43
839-248CSR	2X3/4	10	60	096	24.43
839-249CSR	2X1	10	120	096	24.43
839-420CSR	4X2	6	0	096	135.66

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Special Reinforced Reducer Bushing

Spig x SR Fipt - Stainless Steel Collar



838-128CSR	1X1/4	25	150	096	12.74
838-207CSR	1-1/2X1/4	25	200	096	21.55
838-209CSR	1-1/2X1/2	10	120	096	22.46
838-210CSR	1-1/2X3/4	10	120	096	22.46
838-247CSR	2X1/2	10	80	096	30.86
838-248CSR	2X3/4	10	80	096	30.86
838-249CSR	2X1	10	80	096	30.86
838-334CSR	3X3/4	10	0	096	130.68
838-335CSR	3X1	10	0	096	130.68
838-336CSR	3X1-1/4	10	0	096	130.68
838-337CSR	3X1-1/2	10	0	096	130.68
838-528CSR	6X2	5	0	096	449.27
838-530CSR	6X3	5	0	096	449.27

Special Reinforced Cap

SR Fipt - Stainless Steel Collar



848-002CSR	1/4	25	500	096	7.06
848-003CSR	3/8	25	450	096	7.06
848-007CSR	3/4	25	300	096	11.00
848-030CSR	3	5	0	096	122.80

Special Reinforced Union 2000

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005CSR	1/2	20	160	096	15.81
8099-007CSR	3/4	20	160	096	28.07
8099-010CSR	1	15	90	096	38.87
8099-012CSR	1-1/4	10	0	096	73.64
8099-015CSR	1-1/2	10	0	096	80.09
8099-020CSR	2	5	0	096	84.34
8099-025CSR	2-1/2	5	0	096	144.66
8099-030CSR	3	5	0	096	234.95
8099-040CSR	4	4	0	096	275.93
8099-060CSR	6	1	0	096	613.20

Special Reinforced Union 2000

Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005CSR	1/2	25	200	096	16.13
8059-007CSR	3/4	20	160	096	28.45
8059-010CSR	1	15	90	096	39.20
8059-012CSR	1-1/4	10	0	096	74.74
8059-015CSR	1-1/2	10	0	096	81.24
8059-020CSR	2	5	0	096	84.58
8059-030CSR	3	5	0	096	237.94
8059-040CSR	4	4	0	096	277.60

Special Reinforced Union 2000

SR Fipt with FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005CSR	1/2	20	160	096	16.55
8058-007CSR	3/4	20	80	096	28.85
8058-010CSR	1	15	90	096	39.65
8058-012CSR	1-1/4	10	0	096	74.74
8058-015CSR	1-1/2	10	0	096	81.56
8058-020CSR	2	5	0	096	85.94
8058-030CSR	3	5	0	096	242.85
8058-040CSR	4	4	0	096	284.51

Transition Fittings & Adapters CPVC Gray Special Reinforced (SR) Fittings



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------


Special Reinforced Union 2000 (continued)

SR Fipt with FKM O-ring Seal - Stainless Steel Collar

8058-060CSR	6	1	0	096	640.73
-------------	---	---	---	-----	--------

Special Reinforced Union 2000

SR Fipt with EPDM O-ring Seal - Stainless Steel Collar




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005CSR	1/2	20	160	096	16.00
8098-007CSR	3/4	20	80	096	28.59
8098-010CSR	1	15	90	096	39.20
8098-012CSR	1-1/4	10	0	096	74.01
8098-015CSR	1-1/2	10	0	096	80.93
8098-020CSR	2	5	0	096	85.09
8098-025CSR	2-1/2	5	0	096	147.05
8098-030CSR	3	5	0	096	239.09
8098-040CSR	4	4	0	096	276.79
8098-060CSR	6	1	0	096	615.09

Special Reinforced Union (Old Style)

Soc x SR Fipt with EPDM O-ring Seal - Stainless Steel Collar




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002CSR	1/4	25	150	096	25.21
899-003CSR	3/8	25	100	096	25.21
899-005CSR	1/2	10	60	096	15.81
899-007CSR	3/4	10	40	096	28.07
899-010CSR	1	10	40	096	38.87
899-012CSR	1-1/4	5	20	096	73.64
899-015CSR	1-1/2	5	0	096	80.09
899-020CSR	2	5	0	096	84.34
899-030CSR	3	5	0	096	234.95
899-040CSR	4	4	0	096	275.93

Special Reinforced Union (Old Style)

Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002CSR	1/4	25	150	096	25.38
859-003CSR	3/8	25	100	096	25.38
859-005CSR	1/2	10	60	096	16.13
859-007CSR	3/4	10	40	096	28.45
859-010CSR	1	10	40	096	39.20
859-012CSR	1-1/4	5	20	096	74.74
859-015CSR	1-1/2	5	0	096	81.24
859-020CSR	2	5	0	096	84.58
859-030CSR	3	5	0	096	237.94
859-040CSR	4	4	0	096	277.60

Special Reinforced Flange One Piece Threaded


SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005CSR	1/2	25	0	096	20.65
852-007CSR	3/4	25	0	096	25.05
852-010CSR	1	15	0	096	27.41
852-012CSR	1-1/4	15	0	096	37.93
852-015CSR	1-1/2	15	0	096	40.21
852-020CSR	2	10	0	096	41.19
852-025CSR	2-1/2	10	0	096	66.27
852-030CSR	3	10	0	096	65.76
852-040CSR	4	5	0	096	123.22

CPVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets




Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	49.80
8171-003CSR	3/8	25	200	101	49.80
8171-005CSR	1/2	25	0	101	49.80
8171-007CSR	3/4	25	0	101	59.60
8171-010CSR	1	25	0	101	67.42
8171-012CSR	1-1/4	20	0	101	86.97
8171-015CSR	1-1/2	20	0	101	97.64
8171-020CSR	2	15	0	101	135.02
8171-025CSR	2-1/2	4	0	101	205.39
8171-030CSR	3	4	0	101	244.46
8171-040CSR	4	2	0	101	392.88
8171-060CSR	6	1	0	101	1037.65

CPVC New Style Special Reinforced (SR) Threaded Tank Adapters with EPDM Gaskets




Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	56.44
8171E-003CSR	3/8	25	200	101	56.44
8171E-005CSR	1/2	25	0	101	56.44
8171E-007CSR	3/4	25	0	101	63.79
8171E-010CSR	1	25	0	101	76.27
8171E-012CSR	1-1/4	20	0	101	95.32
8171E-015CSR	1-1/2	20	0	101	103.13
8171E-020CSR	2	15	0	101	145.79
8171E-025CSR	2-1/2	4	0	101	214.24
8171E-030CSR	3	4	0	101	255.05
8171E-040CSR	4	2	0	101	408.93
8171E-060CSR	6	2	0	101	1079.93

CPVC New Style Special Reinforced (SR) Threaded Tank Adapters with FKM Gaskets




Soc x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	73.54
8171V-003CSR	3/8	25	200	101	73.54
8171V-005CSR	1/2	25	0	101	73.54
8171V-007CSR	3/4	25	0	101	85.01
8171V-010CSR	1	25	0	101	98.89
8171V-012CSR	1-1/4	20	0	101	122.59
8171V-015CSR	1-1/2	20	0	101	130.91
8171V-020CSR	2	15	0	101	194.93
8171V-025CSR	2-1/2	4	0	101	287.26
8171V-030CSR	3	4	0	101	342.05
8171V-040CSR	4	2	0	101	730.36
8171V-060CSR	6	2	0	101	1803.22

CPVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets



Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	65.97
8172-003CSR	3/8	25	200	101	65.97
8172-005CSR	1/2	25	0	101	65.97
8172-007CSR	3/4	25	0	101	76.61
8172-010CSR	1	25	0	101	84.41
8172-012CSR	1-1/4	20	0	101	119.75
8172-015CSR	1-1/2	20	0	101	133.78
8172-020CSR	2	15	0	101	165.40
8172-025CSR	2-1/2	4	0	101	240.05



Transition Fittings & Adapters CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------


CPVC New Style Special Reinforced (SR) Threaded Tank Adapters with Neoprene Gaskets (continued)

Fipt x SR Fipt - Stainless Steel Collar

8172-030CSR	3	4	0	101	285.78
8172-040CSR	4	2	0	101	438.93
8172-060CSR	6	2	0	101	1175.97

CPVC New Style Special Reinforced (SR) Threaded Tank Adapters with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar




150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	68.55
8172E-003CSR	3/8	25	200	101	68.55
8172E-005CSR	1/2	25	0	101	68.55
8172E-007CSR	3/4	25	0	101	81.17
8172E-010CSR	1	25	0	101	88.12
8172E-012CSR	1-1/4	20	0	101	124.38
8172E-015CSR	1-1/2	20	0	101	144.60
8172E-020CSR	2	15	0	101	177.48
8172E-025CSR	2-1/2	4	0	101	267.74
8172E-030CSR	3	4	0	101	318.73
8172E-040CSR	4	2	0	101	515.99
8172E-060CSR	6	2	0	101	1193.37

CPVC New Style Special Reinforced (SR) Threaded Tank Adapters with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	105.26
8172V-003CSR	3/8	25	200	101	105.26
8172V-005CSR	1/2	25	0	101	105.26
8172V-007CSR	3/4	25	0	101	119.08
8172V-010CSR	1	25	0	101	137.53
8172V-012CSR	1-1/4	20	0	101	169.80
8172V-015CSR	1-1/2	20	0	101	178.83
8172V-020CSR	2	15	0	101	274.84
8172V-025CSR	2-1/2	4	0	101	397.14
8172V-030CSR	3	4	0	101	472.79
8172V-040CSR	4	2	0	101	1206.41
8172V-060CSR	6	2	0	101	2190.53

CPVC Elastomer Expansion Joint

with EPDM Bellows SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ21-007CSR	3/4	10	0	085	208.22
EJ21-010CSR	1	10	0	085	239.45
EJ21-012CSR	1-1/4	15	0	085	264.60
EJ21-015CSR	1-1/2	10	0	085	337.27
EJ21-020CSR	2	8	0	085	445.81
EJ21-025CSR	2-1/2	4	0	085	619.13
EJ21-030CSR	3	2	0	085	824.60


Transition Fittings & Adapters CPVC Gray Brass Thread Fittings



Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Transition Tee

Soc x Fipt With Brass Thread Insert




802-005CBR	1/2	20	160	096	58.38
802-007CBR	3/4	25	0	096	116.75

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Reducing Tee

Soc x Fipt With Brass Thread Insert




802-101CBR	3/4X1/2	50	0	096	72.36
------------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition 90° El

Soc x Fipt With Brass Thread Insert




807-005CBR	1/2	20	240	096	51.33
807-007CBR	3/4	20	160	096	89.61

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Reducing 90° El

Soc x Fipt With Brass Thread Insert




807-101CBR	3/4X1/2	20	120	096	64.19
------------	---------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter

Soc x Fipt With Brass Thread Insert




835-005CBR	1/2	25	150	096	31.64
835-007CBR	3/4	15	90	096	65.48
835-010CBR	1	15	90	096	114.92
835-012CBR	1-1/4	15	60	096	187.47
835-015CBR	1-1/2	10	80	096	247.18
835-020CBR	2	8	32	096	308.72

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Female Adapter


Soc x Fipt With Type 316 Stainless Steel Thread Insert



835-005CSS	1/2	25	150	096	62.13
835-007CSS	3/4	15	90	096	86.74
835-010CSS	1	15	90	096	151.81
835-012CSS	1-1/4	15	0	096	246.72
835-015CSS	1-1/2	10	60	096	321.87
835-020CSS	2	8	32	096	376.68

Transition Male Adapter w/Brass Thread

Brass Mipt x Socket




836-005CBR	1/2	40	160	096	70.14
836-007CBR	3/4	40	160	096	98.75
836-010CBR	1	10	60	096	171.99
836-012CBR	1-1/4	10	60	096	279.76
836-015CBR	1-1/2	10	40	096	363.71
836-020CBR	2	8	32	096	426.20

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Union

Soc x Fipt with Brass Thread Insert & FKM O-ring Seal




235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007CBR	3/4	10	20	096	146.17
859-010CBR	1	10	0	096	162.80
859-012CBR	1-1/4	5	0	096	272.91
859-015CBR	1-1/2	5	0	096	310.13
859-020CBR	2	5	0	096	350.51

Not intended to convey or dispense water for human consumption through drinking or cooking

Union

Soc x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007CBR	3/4	10	40	096	143.69
899-010CBR	1	10	0	096	160.80
899-012CBR	1-1/4	5	20	096	269.46
899-015CBR	1-1/2	5	0	096	306.17
899-020CBR	2	5	0	096	346.21

Not intended to convey or dispense water for human consumption through drinking or cooking



Transition Fittings & Adapters CPVC Orange Special Reinforced (SR) Fittings

The CPVC Orange fittings in this section (4200 series part numbers) are approved by Underwriters Laboratories, FM Global, and LPCB for use in CPVC Fire Sprinkler Systems. When installed in these systems, installation must be made in accordance with Spears® publication FG-3, *FlameGuard® CPVC Fire Sprinkler Products Installation Instructions*, and local codes. However, these fittings can also be used in many other types of installations, such as hot water distribution. CPVC fittings may also be used on PVC pipe when installed with a quality CPVC solvent cement meeting the requirements of ASTM F 493, Standard Specification for Solvent Cements for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe and Fittings.

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Sprinkler Head Tee - Special Reinforced Plastic Thread Style with Wrench Flats


Socket x Socket x SR FIPT - Zinc Collar



4202-010SR	1	15	0	076	20.40
4202-130SR	1X1/2	50	0	076	7.95

Sprinkler Head Tee - Special Reinforced Plastic Thread Style


Socket x Socket x SR FIPT - Stainless Steel Collar



4202-101SR	3/4X1/2	50	0	076	7.36
4202-124SR	1X3/4X1/2	50	0	076	7.95
4202-156SR	1-1/4X1X1/2	15	0	076	13.25
4202-166SR	1-1/4X1/2	15	0	076	13.25
4202-168SR	1-1/4X1	15	0	076	28.48
4202-199SR	1-1/2X1-1/4X1/2	10	0	076	17.44
4202-209SR	1-1/2X1/2	25	0	076	17.44
4202-211SR	1-1/2X1-1/2X1	10	0	076	17.44
4202-237SR	2X1-1/2X1/2	10	0	076	24.61
4202-247SR	2X1/2	10	0	076	24.61
4202-287SR	2-1/2X1/2	10	0	076	33.73

Sprinkler Head Tee - Special Reinforced Plastic Thread Style


Socket x SR FIPT x Socket - Stainless Steel Collar



4203-122SR	1X1/2X1	50	0	076	8.54
------------	---------	----	---	-----	------

Sprinkler Head 90° Ell - Special Reinforced Plastic Thread Style


Socket x SR FIPT - Stainless Steel Collar



4207-101SR	3/4X1/2	20	180	076	4.85
4207-130SR	1X1/2	10	150	076	6.84
4207-131SR	1X3/4	50	0	076	8.27
4207-166SR	1-1/4X1/2	25	0	076	8.69

Female Adapter - Special Reinforced Plastic Thread Style


Socket x SR FIPT - Stainless Steel Collar



4235-007SR	3/4	25	300	076	8.65
4235-010SR	1	25	200	076	15.21
4235-012SR	1-1/4	10	60	076	24.76

Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style


Socket x SR FIPT - Stainless Steel Collar



4235-101SR	3/4X1/2	50	200	076	5.28
4235-130SR	1X1/2	50	0	076	5.65
4235-131SR	1X3/4	50	0	076	8.95

Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Socket Body Wrench Flats


Socket x SR FIPT - Stainless Steel Collar



W4235-101SR	3/4X1/2	50	0	076	6.03
W4235-130SR	1X1/2	50	0	076	6.45

Female Sprinkler Head Adapter - Special Reinforced Plastic Thread with Metal Thread Start


Socket x SR FIPT - Zinc Collar



Z4235-101SR	3/4X1/2	50	200	076	5.28
-------------	---------	----	-----	-----	------

Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Positioning Ring


Socket x SR FIPT - Stainless Steel Collar



R4235-101SR	3/4X1/2	25	300	076	5.97
-------------	---------	----	-----	-----	------

Spigot Female Sprinkler Head Adapters - Special Reinforced Plastic Threaded Style

Spigot x SR FIPT - Stainless Steel Collar



4238-101SR	3/4X1/2	50	400	076	5.28
4238-130SR	1X1/2	50	0	076	5.72

Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Socket x SR FIPT - Stainless Steel Collar



42001SR	3/4X1/2	12	0	076	13.49
42011SR	1X1/2	12	0	076	13.49

Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style


Socket x SR FIPT - Stainless Steel Collar



42004SR	3/4X1/2	12	0	076	13.49
42014SR	1X1/2	12	0	076	13.49

Spigot Female Adapter - Special Reinforced Plastic Thread Style

Spigot x SR FIPT - Stainless Steel Collar



4278-007SR	3/4	25	300	076	9.08
4278-010SR	1	50	0	076	16.17


Transition Fittings & Adapters CPVC Orange Brass Thread Fittings



The CPVC Orange fittings in this section (4200 series part numbers) are approved by Underwriters Laboratories, FM Global, and LPCB for use in CPVC Fire Sprinkler Systems. When installed in these systems, installation must be made in accordance with Spears® publication FG-3, *FlameGuard® CPVC Fire Sprinkler Products Installation Instructions*, and local codes. However, these fittings can also be used in many other types of installations, such as hot water distribution. CPVC fittings may also be used on PVC pipe when installed with a quality CPVC solvent cement meeting the requirements of ASTM F 493, Standard Specification for Solvent Cements for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe and Fittings.

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------


Sprinkler Head Tee - Brass Thread Insert Style Socket x Socket x FIPT



4202-101	3/4X1/2	50	0	076	13.83
4202-124	1X3/4X1/2	50	0	076	14.93
4202-130	1X1/2	50	0	076	14.93
4202-010	1	10	40	076	38.39
4202-156	1-1/4X1X1/2	15	0	076	24.89
4202-166	1-1/4X1/2	15	0	076	24.89
4202-199	1-1/2X1-1/4X1/2	10	0	076	32.79
4202-209	1-1/2X1/2	10	0	076	32.79
4202-237	2X1-1/2X1/2	10	0	076	46.24
4202-247	2X1/2	10	0	076	46.24

Not intended to convey or dispense water for human consumption through drinking or cooking


Sprinkler Head Tee - Brass Thread Insert Style Socket x FIPT x Socket



4203-122	1X1/2X1	50	0	076	24.52
----------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking


Sprinkler Head 90° Ell - Brass Thread Insert Style Socket x FIPT



4207-101	3/4X1/2	20	120	076	9.14
4207-130	1X1/2	15	90	076	12.84
4207-131	1X3/4	25	0	076	15.54
4207-166	1-1/4X1/2	10	60	076	17.88

Not intended to convey or dispense water for human consumption through drinking or cooking


Female Adapter - Brass Thread Insert Style Socket x FIPT



4235-007	3/4	15	90	076	18.23
4235-010	1	15	90	076	31.99
4235-012	1-1/4	15	60	076	52.15
4235-015	1-1/2	10	40	076	69.57
4235-020	2	8	32	076	87.19

Not intended to convey or dispense water for human consumption through drinking or cooking

Spigot Female Adapter - Brass Thread Insert Style Spigot x FIPT



4278-007	3/4	25	150	076	17.05
4278-010	1	15	90	076	30.37

Not intended to convey or dispense water for human consumption through drinking or cooking

TorqueSafe™ Female Sprinkler Head Adapter - Gasket Sealed Brass Thread Insert Style Socket x Gasket FIPT




4235-130GS	1X1/2	50	0	076	10.63
------------	-------	----	---	-----	-------

FIPT With Elastomer Seal - Use NO Thread Sealant. Not intended to convey or dispense water for human consumption through drinking or cooking

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------


Female Sprinkler Head Adapter - Brass Thread Insert Style Socket x FIPT



4235-101	3/4X1/2	50	0	076	9.96
4235-130	1X1/2	50	0	076	10.63
4235-131	1X3/4	50	0	076	16.80

Not intended to convey or dispense water for human consumption through drinking or cooking


Female Sprinkler Head Adapter - Brass Thread Insert Style with Long Body Socket x FIPT



L4235-130	1X1/2	50	0	076	15.07
-----------	-------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking


Female Sprinkler Head Adapter - Brass Thread Insert Style with Positioning Ring Socket x FIPT



R4235-101	3/4X1/2	50	0	076	9.96
-----------	---------	----	---	-----	------

Not intended to convey or dispense water for human consumption through drinking or cooking

Spigot Female Sprinkler Head Adapters - Brass Thread Insert Style Spigot x FIPT



4238-101	3/4X1/2	50	0	076	9.96
4238-130	1X1/2	50	0	076	10.63

Not intended to convey or dispense water for human consumption through drinking or cooking


Bushing - with Brass Thread Insert Spigot x FIPT



4238-130BR	1X1/2	50	300	076	13.76
------------	-------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Male Adapter MIPT x Socket



4236-007	3/4	40	160	076	41.02
4236-010	1	10	60	076	62.72
4236-012	1-1/4	10	60	076	75.00
4236-015	1-1/2	10	40	076	136.12
4236-020	2	8	32	076	181.14



Transition Fittings & Adapters
CPVC Orange Brass Grooved Coupling Adapter

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

Grooved Coupling Adapter
Brass Groove End x Socket



4233-012	1-1/4	10	40	076	103.14
4233-015	1-1/2	10	40	076	109.31
4233-020	2	8	32	076	126.60
4233-025	2-1/2	5	0	076	162.39
4233-030	3	5	0	076	180.53

Not intended to convey or dispense water for human consumption through drinking or cooking

Transition Fittings & Adapters
CTS CPVC Tan Special Reinforced (SR) Fittings & CTS CPVC Tan Brass Thread Fittings




CTS CPVC Tan Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

SPECIAL REINFORCED 90° ELL

Socket x SR Fipt - Stainless Steel Collar



4107-005SR	1/2	50	300	035	9.01
------------	-----	----	-----	-----	------

**ZINC DROP EAR REINFORCED CTS 90° ELL
(One Piece Unit)**

Socket x SR Fipt - Zinc Collar



DEZ4107-005SR	1/2	10	150	035	20.26
---------------	-----	----	-----	-----	-------

**DROP EAR SPECIAL REINFORCED 90° ELL
(Fitting Plus Bracket)**


Socket x SR Fipt - Stainless Steel Collar



DE4107-005SR	1/2	10	200	035	13.93
--------------	-----	----	-----	-----	-------

SPECIAL REINFORCED FEMALE ADAPTER

Socket x SR Fipt - Stainless Steel Collar



4135-005SR	1/2	25	200	035	6.96
------------	-----	----	-----	-----	------


SPECIAL REINFORCED FEMALE ADAPTER (continued)

Socket x SR Fipt - Stainless Steel Collar

4135-007SR	3/4	25	300	035	7.65
4135-010SR	1	5	100	035	9.71

SPECIAL REINFORCED REDUCING FEMALE ADAPTER


Socket x SR Fipt - Stainless Steel Collar



4135-131SR	1X3/4	25	150	035	15.28
------------	-------	----	-----	-----	-------

**REINFORCED MALE ADAPTER (Internal
Stainless Steel Reinforced)**

R Mipt x Socket - Stainless Steel Sleeve




4136-005R	1/2	25	300	035	8.93
4136-007R	3/4	25	300	035	9.93
4136-010R	1	10	120	035	14.79

CTS CPVC Tan Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

**GASKET SEALED BRASS THREAD
TRANSITION FEMALE ADAPTER**

Socket x Gasket FPT - Use NO Thread Sealant



NSF Certified Lead Free

4135-005BRG	1/2	25	150	035	40.21
4135-007BRG	3/4	25	150	035	44.28
4135-010BRG	1	15	90	035	132.09
4135-012BRG	1-1/4	15	60	035	250.97
4135-015BRG	1-1/2	10	40	035	327.12
4135-020BRG	2	8	32	035	480.95

**GASKET SEALED BRASS THREAD
TRANSITION REDUCING FEMALE ADAPTER**

Socket x Gasket FPT - Use NO Thread Sealant



NSF Certified Lead Free

4135-101BRG	3/4X1/2	25	150	035	43.77
4135-130BRG	1X1/2	50	0	035	69.15

**TRANSITION MALE ADAPTER w/BRASS
THREAD**

Brass Mipt x Socket



NSF Certified Lead Free

4136-005BR	1/2	60	360	035	40.21
4136-007BR	3/4	40	160	035	44.28
4136-010BR	1	10	60	035	132.09
4136-012BR	1-1/4	10	60	035	162.92
4136-015BR	1-1/2	10	40	035	215.06
4136-020BR	2	8	32	035	357.49




Transition Fittings & Adapters
CTS CPVC Tan Gasket Sealed Thread Fittings & Blue 75™ Thread Sealant

CTS CPVC Tan Gasket Sealed Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

FEMALE ADAPTER with Gasket
Socket x NPSC



For Cold Water Service Only

4135-005OR	1/2	25	200	035	4.71
------------	-----	----	-----	-----	------

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------

FEMALE ADAPTER with Gasket (continued)
Socket x NPSC

4135-007OR	3/4	25	300	035	6.68
4135-010OR	1	5	100	035	7.62

Blue 75™ Thread Sealant

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	-----------	-------------	--------------	---------------



Blue 75™ Thread Sealant

SB75-005	1/4 Pint	24	0	895	10.46
SB75-010	1/2 Pint	24	0	895	16.66
SB75-020	Pint	12	0	895	26.94
SB75-030	Quart	12	0	895	48.41