

SKIMMER DOOR™



WINTERIZE YOUR SKIMMER – WITH AN EASY SNAP-ON DOOR!

- ◆ Skimmer Door™ lets you drain your skimmer, not your pool, and prevents costly freeze damage to the skimmer.
- ◆ The recessed design prevents shifting ice from removing the door once it is snapped in place.
- ◆ **Guaranteed not to leak!** UV and chemical-resistant, good to minus 80°F below zero.
- ◆ Optional snap-on Skimmer Guard™ is available to prevent toys, floats, etc. from blocking your skimmer during the swim season (sold separately).



This kit includes:
1x Skimmer Door
1x Skimmer Door Faceplate

See reverse side for installation instructions. US & Foreign Patents - 4,913,810 / 7,011,747 / 7,390,401 / 7,413,651. **Made in the USA.**

**MODEL #
AG1090**

Fits most standard 6" skimmers, including:
Hayward® SP1090, 1092, 1094, American Products, Jacuzzi® Deckhand, Muskin®, Olympic®, Seasonmaster®, Sta-Rite® and others.

KIT PACKAGE INSERT



This package includes:
1x Replacement Skimmer Door

SKIMMER DOOR™



WINTERIZE YOUR SKIMMER – WITH AN EASY SNAP-ON DOOR!

- ◆ Skimmer Door™ lets you drain your skimmer, not your pool, and prevents costly freeze damage to the skimmer.
- ◆ The recessed design prevents shifting ice from removing the door once it is snapped in place.
- ◆ **Guaranteed not to leak!** UV and chemical-resistant, good to minus 80°F below zero.

US & Foreign Patents - 4,913,810 / 7,011,747 / 7,390,401 / 7,413,651. **Made in the USA.**

**MODEL #
AG1090**

Fits most standard 6" skimmers, including:
Hayward® SP1090, 1092, 1094, American Products, Jacuzzi® Deckhand, Muskin®, Olympic®, Seasonmaster®, Sta-Rite® and others.

LID PACKAGE HEADER CARD

NOTE: Skimmer gaskets **DO NOT** come with the **SKIMMER DOOR™**. On new pool installations simply install the new gaskets that came with your skimmer. On existing pools it is highly recommended that you replace your skimmer gaskets when installing **SKIMMER DOOR™**.

* If gaskets are torn or show any wear they **MUST** be replaced.

** **SKIMMER DOOR™** mounting plate seals exposed metal walls (aluminum and steel) when installed using silicone seal per the

directions below. Non-metal walls do not need the silicone seal.

ITEMS REQUIRED:

#3 Phillips head screwdriver

O-Ring lubricant

New skimmer gaskets *see recommendations above

Marine grade silicone sealant **aluminum or steel walls - see above

INSTALLATION:

(1) Remove existing skimmer faceplate using a #3 Phillips head screwdriver.

(2) Keep the screws; you will be using them to reinstall your **SKIMMER DOOR™** mounting plate.

(3) Inspect gaskets and replace if necessary.

See above recommendations.

(4) Metal-walled pools only: should apply a liberal bead of silicone seal to the four sides of the exposed pool wall at the skimmer cutout. *Proceed with Step #4 before silicone cures.*

No need to drain your water again! In the future, the **SKIMMER DOOR™** will simply snap on and peel off. The **SKIMMER DOOR™** mounting plate will remain permanently installed on your skimmer. Use the **SKIMMER DOOR™** during the swim season.

INSTALLATION INSTRUCTIONS

PREPARATION:

NEW POOLS: **SKIMMER DOOR™** should be installed prior to completely filling your pool with water.

EXISTING POOLS: Drain pool water just below the skimmer's opening, 1" - 2". Assemble required items.

4) Align gaskets and new **SKIMMER DOOR™** mounting plate against skimmer opening and reinstall existing screws. Hand-tighten using a #3 Phillips head screwdriver. **DO NOT OVER TIGHTEN.**

5) Once the new mounting plate is securely in place, wipe away and excess silicone from the area where the mounting plate and skimmer join.

6) Apply a thin bead of o-ring lubricant along the inside lip of the flexible lid to ensure a water tight seal.

7) Now when you are ready to seal off your skimmer - simply snap on the lid by pressing firmly around the entire perimeter for a positive seal.