54377 Traveler Safety Cover



| TESTING ITEM | TESTING RESULT* | TESTING METHOD |
|------------------------------|---------------------------------------|---|
| Item | PVC/Texturized Polyester 600 x 300 | _ |
| Thickness | 0.55mm | _ |
| Tear Strength | 26 x 11 lbs. | ASTM D 5733-95 |
| Tensile Strength | 314 x 160 lbs. | ASTM D 5034-95 |
| Colorfastness to Water/Light | Poly - GS 2-3 PVC- GS 4 | AATCC Method 136- 1991 |
| Surface Abrasion | 5,792 cycles | ASTM D 3884-80 |
| Cold Crack | No indications of cracking/flaking | FTMS 191A Method 5874, '(20F ± 2F for 30 minutes) |

^{*}The above values are based on laboratory tests and are for your guidance only. We offer no guarantee and assume no liability or obligation in connection with this information.

Description

The optional PVC/texturized polyester safety cover protects the lift from unauthorized use and from environmental elements. The cover includes a warning sign clearly visible from the pool/spa deck.

Product Description

54377 Traveler Safety Cover

Warranty

Two year limited warranty.



7100 Spectrum Lane • Missoula, Montana 59808

800.791.8056 • 406.542.9781

Fax: 406-542-1158

www.spectrumproducts.com