
## System: 3<sup>®</sup> Mod D.E. Filters for Inground Pools by Sta-Rite





## The world's finest pool filtration

To enjoy the clearest, cleanest water in your pool, install the Sta-Rite<sup>®</sup> System :3 Mod D.E. filter, the latest advance in diatomaceous earth (D.E.) filtration. Diatomaceous earth, a natural substance, is so fine it traps dirt and debris as small as five microns (1/10 the width of a human hair). That means body oils, suntan lotions, pollens, dust and even some bacteria are trapped in the filter, leaving behind sparkling clear, healthier water.



The System 3 Mod D.E. filter also has a clear advantage over traditional-style D.E. filters:

- Single module replaces complicated multi-grid assemblies that are difficult to clean and reassemble.
- Balanced-flow tank design maximizes the use of the module's surface area to trap more dirt and reduce the frequency of cleaning.

## An Eco Select<sup>®</sup> Brand Product

The Eco Select brand identifies our "greenest" and most efficient equipment choices. Water flows very efficiently through the System 3 Mod D.E. filter, often allowing the use of smaller pumps or lower pump speeds to minimize energy use. And, it helps significantly reduce water use by allowing you to rinse the cartridges rather than backwash.

# System: 3<sup>®</sup> Mod D.E. Filters for Inground Pools



#### An up-close look Top-mounted pressure gauge is conveniently positioned for easy reading.

#### Stands tough year after year

Dura-Glas<sup>™</sup> Composite Resin, Sta-Rite's high-density composite resin, will never corrode and weathers the elements.

Easy access Posi-Lok<sup>™</sup> Clamps provide easy access to the filter module. 50/50 split-tank design permits rinse-in-place cleaning. Fast in, fast out!

#### Smooth running

2" plumbing ports improve hydraulic flow for greater efficiency.

Easy on the eyes Sleek, contemporary styling blends beautifully with any poolscape.



## Superior in every way

The System 3 Mod D.E. filter removes dirt particles up to 10 times smaller than the particles removed by sand and cartridge filters. Compared to other D.E. filters, the System 3 Mod D.E. filter is far less complicated to service. If you're the do-it-yourself type, you save time. If you leave the maintenance to a pool service, saving time means saving money!



## Less maintenance...YES!

The balanced-flow tank design directs water through both sides of the filter module, which increases dirt-loading without clogging. Holding more dirt means a longer time between cleanings.



## Easy, two-way cleaning

For quick cleaning, simply move the valve lever to the backwash position—that's it! For more thorough cleaning, remove the tool-free tank lid and spray-rinse the module<sup>\*</sup> while it's still in place. In minutes, it's ready for another season.

\*Modules used in conjunction with certain pool/spa sanitizers may require soaking in special cleaning solutions.



# STA-RITE Simply Smarter.

www.staritepool.com Phone: 800-831-7133

## pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / water features / maintenance products

All Pentair trademarks and logos are owned by Pentair, Inc. Sta-Rite®, System:3®, Dura-Glas<sup>®</sup>, Posi-Lok<sup>®</sup>, and Eco Select<sup>®</sup> are trademarks and/or registered trademarks of Pentair Water Pool and Spa, Inc. and/or its affiliated companies in the United States and/or other countries. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

### **Filter Performance**

Model	For Pools up to (Gal.) 8 Hr. Turnover	Filter Area (Sq. Ft.)	Optimal Performance at this GPM	D.E. Required <sup>1</sup> (lbs.)
S7MD60	43,200	60	60 - 90	9
s7MD72	5 1,800	72	72 – 108	П

<sup>1</sup>Do not use more D.E. than shown here. Mixed results with D.E. alternatives.

Operating Limits - Maximum continual operating pressure is 50 PSI. For pool/ spa (bather) applications, the maximum operating water temperature within the filter is 104°F (40°C).

One-year limited warranty. See warranty for details.

## Available from: