


304 S.S. / 304 S.S. IMPELLER DURABLE LONGLIFE CONSTRUCTION

Materials of Construction						
Item No.	Description		Material			
1	Motor					
2	Water Slinger		Neoprene			
3	Seal Plate		AISI 304 S.S.			
5	Impeller		AISI 304 S.S.			
6	Impeller Locking Screw		18-8 S.S. (3 Phase Only)			
7	Casing		AISI 304 S.S.			
8	Base		Powder Painted Steel			
9	Isolator		Natural Rubber			
10	Socket Head Capscrew		AISI 304 S.S.			
11	Socket Head Capscrew		18-8 S.S.			
12	Vent/Drain Plug (Top & Bottom)		AISI 304 S.S.			
13	Gasket (Top & Bottom)		Teflon®			
14	O-Ring		Viton			
4	Mechanical Seal					
	Seal Option	Crane Type	Rotary	Stationary	Elastomer	Metal Parts
	2	2100	Carbon	Ceramic	Viton	18-8 S.S.
	3	2100	Carbon	Silicon-Carbide	Viton	18-8 S.S.
	4	2100	Silicon-Carbide	Silicon-Carbide	Viton	18-8 S.S.



Materials of Construction						
Item No.	Description			Material		
1	Motor					
2	Water Slinger			Neoprene		
3	Seal Plate			AISI 304 S.S.		
5	Impeller			Noryl®/AISI 316 S.S.		
6	Impeller Locking Screw			18-8 S.S. (3 Phase Only)		
7	Casing			AISI 304 S.S.		
8	Base			Powder Painted Steel		
9	Isolator			Natural Rubber		
10	Socket Head Capscrew			AISI 304 S.S.		
11	Socket Head Capscrew			18-8 S.S.		
12	Vent/Drain Plug (Top & Bottom)			AISI 304 S.S.		
13	Gasket (Top & Bottom)			Teflon		
14	O-Ring			Buna-N		
4	Mechanical Seal					
	Seal Option	Crane Type	Rotary	Stationary	Elastomer	Metal Parts
	1	6	Carbon	Ceramic	Buna-N	18-8 S.S.
	2	2100	Carbon	Ceramic	Viton	18-8 S.S.
	3	2100	Carbon	Silicon-Carbide	Viton	18-8 S.S.
	4	2100	Silicon-Carbide	Silicon-Carbide	Viton	18-8 S.S.

SSCX SERIES CENTRIFUGAL PUMPS

CHEMICAL COMPATIBILITY						
Chemical Name	Concentration	Temperature Degree F°	Noryl®	304 SS	Buna	Viton
Acetic Acid	10%	78	A	A	B	A
	10%	185	A	A	B	B
	90%	78	A	A	D	B
	90%	185	A	A	D	D
Ammonia		78	A	A	D	A
	10%	78	A	A	A	A
Ammonium Hydroxide		185	A	A	A	A
	10%	78	A	A	A	A
Ammonium Phosphate		78	A	A	A	A
	Sat.	185	A	A	A	A
Antifreeze		78	A	A	A	A
		185	A	A	A	A
Cascade		78	A	A	A	A
	10%	185	A	A	A	A
Chlorox		78	A	A	B	A
		185	A	A	B	A
Corn Oil		78	A	A	A	A
		185	A	A	A	A
Ethylene Glycol		78	A	A	A	A
		78	A	A	D	A
Isopropyl Alcohol		185	B	A	D	A
		78	A	A	D	A
Kerosene		78	A	A	D	A
		185	A	A	D	A
Lestoil		78	A	A		
	2%	78	A	A	A	A
Linseed Oil		78	A	A	A	A
		78	A	A	A	A
Methyl Alcohol		78	A	A	B	D
		78	B	A	A	A
White Mineral Oil		185	B	A	A	A
		78	A	A	D	A
Nitric Acid		185	A	A	D	A
		78	A	A	D	B
Oleic Acid		78	A	A	D	B
		78	A	A	D	A
Phosphoric Acid		60%	78	A	A	A
	Sat.	185	A	A	A	A
Potassium Bicarbonate		Sat.	78	A	A	A
	Sat.	185	A	A	A	A
Potassium Hydroxide		50%	78	A	A	B
	50%	185	A	A	B	B
Silicon		78	A	A	A	A
		185	A	A	A	A
Sodium Bicarbonate		Sat.	78	A	A	A
	Sat.	185	A		A	A
Sodium Chloride		Sat.	78	A	A	A
	Sat.1	85	A	B	A	A
Sodium Hydroxide		10%	78	A	A	B
		50%	78	A	B	D
Transmission Fluid		98%	78	A	D	A
		78	A	A	A	A
Water		185	A	A	A	A
		78	A	A	A	A
			212	B	A	B

A-No Effect - Excellent B-Minor Effect - Good C-Moderate to Severe Effect D-Not Recommended



293 WRIGHT STREET, DELAVAN, WI 53115 WWW.BERKELEYPUMPS.COM
PH: 888-237-5353 ORDERS FAX: 800-321-8793
Noryl® is a registered trademark of GE. Teflon® is a registered trademark of E. I. duPont de Nemours and Co. All other brand or product names are trademarks or registered trademarks of Pentair Ltd.
Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

© 2012 Pentair Ltd. All Rights Reserved.

B2022BK (11/06/12)



The Berkeley® difference – Everything we do shows up in the way Berkeley pump users look at us: with confidence. It's a confidence that goes from ordering to delivery to installation, on through years of trouble-free performance. It's a confidence that allows our customers to cure common pump worries and troubles with one simple phrase: Relax, it's a Berkeley.™



BEC2: a Berkeley advantage – Berkeley's Electronic Catalog puts powerful pump specification, application and installation software right at our customer's fingertips 24 hours a day, every day. For more information about BEC2, the SSCX or any other Berkeley product, contact your Berkeley distributor or a Berkeley service representative at: 1-888-BERKELEY.

BEC2 ELECTRONIC CATALOG
Powerful pump selection and application software.
Visit www.berkeleypumps.com
and click the BEC2 icon to get started.

The Chemical Compatibility Chart is not intended to be a complete list. For more information on additional chemical compatibilities, consult with an authorized Berkeley Customer Service Representative.

For more information, call our toll-free number or visit our website at www.berkeleypumps.com



BERKELEY® SSCX SERIES CENTRIFUGAL PUMPS

WWW.BERKELEYPUMPS.COM

