



PRODUCT SPECIFICATIONS	
Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, DWV, and sewer
Maximum Diameter	For pipe sizes with interference fit thru 12" (300mm) all classes and schedules. For use on non-pressure applications thru 18" (450mm)
Color	Gray
Relative Set Time	Medium Set
Body	Heavy Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372 CSA B137.3, CSA B181.2
Brookfield Viscosity	Minimum 1,600 cP @73°F +/- 2°F 23°C +/- 1°C
Specific Gravity	Typical 0.968 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	510 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

## GRAY HEAVY BODY PVC CEMENT

Christy's **GRAY HEAVY BODY PVC CEMENT** is an industrial grade, heavy bodied, medium set high strength PVC solvent cement designed for large diameter applications or where more working time is required. For use in agricultural, irrigation, pool and spa, plumbing, industrial, municipal and electrical applications

- **Industrial grade, high strength PVC cement for large diameter applications or where more working time is required. Also recommended for hot weather applications**
- **Heavy body formulation delivers superior gap filling capacity between pipe & fittings**
- **Gray color enables visual confirmation that cement has been applied**
- **For pipe sizes with interference fit thru 12" (300mm) all classes and schedules. For use on non-pressure applications thru 18" (450mm)**
- **For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer**
- **Low VOC**

CASE PACK CONFIGURATIONS			
Item #	Can Size	Cans/Cs	Can UPC
RH-BGLV-HP-24	½ Pint, 8 oz (237 ml)	24	044752410083
RH-BGLV-PT-12	Pint, 16 oz (473 ml)	12	044752410168
RH-BGLV-QT-12	Quart, 32 oz (946 ml)	12	044752410328
RH-BGLV-GL-6	Gallon, 128 oz (3.785 l)	6	044752411288

**SPECIAL CONSIDERATIONS:** Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. **DO NOT USE** a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

**THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR BEING TESTED WITH COMPRESSED AIR OR GASSES.**

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE