






PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, DWV, and sewer
Maximum Diameter	For pressure system pipe sizes with interference fit thru 4" (100mm) all classes and schedules. For use on non-pressure applications thru 6" (150mm)
Color	Clear
Relative Set Time	Very Fast Set
Body	Medium Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	Minimum 500 cP @73°F +/- 2°F 23°C +/- 1°C
Specific Gravity	Typical 0.955 +/- 0.04
Industry Listing	 U.P. Code PW-DWV-SW
Max VOC Emissions	510 g/l per SCAQMD Rule 1168 Method 316A 
Shelf Life	3 Years
LEED Compliant	Low VOC formulation can earn credit toward the U.S. Green Building Council's LEED certification for green buildings. 

RED HOT CLEAR GLUE®

The "Hottest" solvent formula on the market

Christy's RED HOT CLEAR GLUE® is a very aggressive, clear, medium bodied, very fast setting PVC solvent cement. Christy's Red Hot Clear Glue® is the industry's highest quality PVC cement, from the leading producer of high performance solvent cements. For use in plumbing, industrial, irrigation, agricultural, municipal, or pool and spa applications including PVC foam core.

- **Contractor Preferred...** Quickly bonds PVC pipe fittings for fast pressurization and maximum productivity
- **Clear formulation of Red Hot Blue Glue.** Industry's fastest acting cement with the most active ingredients designed to bond in wet, dry and humid conditions
- **Clear formulation for clean joints in exposed installations**
- **Can be used without a primer for non-pressure systems up to 6" (150mm) and pressure systems below 4" (100mm) if local codes permit**
- **For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer**
- **Low VOC**

CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-RHCV-PT-12	Pint, 16 oz (473 ml)	12	044752322492
RH-RHCV-QT-12	Quart, 32 oz (946 ml)	12	044752200325
RH-RHCV-GL-6	Gallon, 128 oz (3.785 l)	6	044752201285

SPECIAL CONSIDERATIONS: Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. DO NOT USE a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR BEING TESTED WITH COMPRESSED AIR OR GASSES.

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE