


Graphix

DESCRIPTION: Wall double-sided
TEXTURE: Smooth & split face



PALLET OVERVIEW



APPLICATIONS

Versatile units that can be used to build planters, double and single walls, steps, edge restraints, pillars, fireplaces and exterior kitchen components.

COMPATIBLE CAPS

Piedimonte & Raffinato cap.

NOTES

See page 162 for more technical information and installation details.

Specifications per pallet	Imperial	Metric
Cubing	26.25 ft²	2.44 m²
	107.67 lin. ft	32.51 m lin.
Weight	2 773 lbs	1 258 kg
Number of rows	8	
Coverage per row	3.28 ft²/row	0.30 m²/row
Linear coverage per row	13.33 lin. ft/row	4.06 lin. m/row

	Unit dimensions	in	mm	Units/pallet
 1	Height Depth Length	2 15/16 9 1/16 20	75 230 508	8 units
 2	Height Depth Length	2 15/16 10 1/16 20	75 255 508	8 units
 3	Height Depth Length	2 15/16 11 20	75 280 508	8 units
 4	Height Depth Length	2 15/16 8 1/16 20	75 205 508	8 units split on one side
 1A	Height Depth Length	2 15/16 9 1/16 20	75 230 508	8 units Left corner unit
 2A	Height Depth Length	2 15/16 10 1/16 20	75 255 508	8 units Right corner unit
 3A	Height Depth Length	2 15/16 11 20	75 280 508	8 units Left corner unit
 4A	Height Depth Length	2 15/16 8 1/16 20	75 205 508	8 units Right corner unit, split on one side

greyed nickel

onyx black

beige cream

