




VILLAGIO

DESCRIPTION: Paver **TEXTURE:** Beveled

PALLET OVERVIEW



The Villagio paver allows for gentle curves and winding pathways, eliminating the need for cuts.

NOTES

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.


See page 30 for more information about applications.

JOINT WIDTH: 3/8" TO 9/16" (9 TO 15 mm)
% OF SURFACE OPENING: 8.0 %
INFILTRATOIN RATE: 896 in./hr
 (22 750 mm/hr)


Specifications per pallet	Imperial	Metric
Cubing	117 ft²	10.88 m²
Approx. Weight	2 960 lbs	1 342 kg
Number of rows	11	
Coverage per row	10.64 ft²	0.99 m²
Linear coverage per row	24.94 lin. ft	7.61 lin. m

	A	Unit dimensions	in	mm	Units/pallet
		Height	2 $\frac{3}{8}$	60	77 units
		Width	5 $\frac{1}{8}$	130	
		Length	5 $\frac{1}{8}$	130	
B		Height	2 $\frac{3}{8}$	60	77 units
		Width	5 $\frac{1}{8}$	130	
		Length	6 $\frac{5}{16}$	160	
	C		Height	2 $\frac{3}{8}$	60
		Width	5 $\frac{1}{8}$	130	
		Length	7 $\frac{5}{16}$	185	
	D		Height	2 $\frac{3}{8}$	60
		Width	5 $\frac{1}{8}$	130	
		Length	8 $\frac{7}{16}$	215	


01 | Linear pattern




02 | Herringbone pattern



03 | Herringbone pattern



04 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

