




BLU 60 mm

DESCRIPTION: Slab **TEXTURE:** Smooth and HD² smooth

PALLET OVERVIEW



NOTES

See page 26 to 28 for more technical information. When used in a permeable pavement application, see page 93 to 100 for more technical information.

See page 20 for more information about applications.

JOINT WIDTH: 9/32" (7 mm)

% OF SURFACE OPENING: 4.5%**

INFILTRATION RATE: 570 in./hr
(14 475 mm/hr)


*For this application, it is recommended that this product be installed on a concrete base as designed by a local Engineer.

**For permeable application, the installation should be combined with BLU 6x13 in a modular pattern. A min. of 4.5% opening surface requires 75% of BLU 6x13 and 25% of BLU.


Specifications per pallet	Imperial	Metric
Cubing	116.82 ft²	10.96 m ²
Approx. Weight Smooth	3 170 lbs	1 438 kg
Approx. Weight HD ² Smooth	3 295 lbs	1 495 kg
Number of rows	11	
Coverage per row	10.62 ft ²	0.99 m ²
Linear coverage per row	9.81 lin. ft	3.02 lin. m

Unit dimensions	in	mm	Units/pallet
A			
Height	2 3/8	60	44 units
Width	13	330	
Length	6 1/2	165	
B			
Height	2 3/8	60	44 units
Width	13	330	
Length	13	330	
C			
Height	2 3/8	60	22 units
Width	13	330	
Length	19 1/2	495	


01 | Modular pattern



02 | Modular pattern



03 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown

HD² Smooth
Smooth



Champlain Grey

HD² Smooth
Smooth




Beige Cream

HD² Smooth
Smooth



Greyed Nickel

HD² Smooth
Smooth




Shale Grey

HD² Smooth
Smooth



Onyx Black

HD² Smooth
Smooth



Caffè Crema

HD² Smooth

