INDUSTRIA SLAB

DESCRIPTION: Slab **TEXTURE:** HD² Smooth, HD² Granitex or HD² Polished

PALLET OVERVIEW















EXPANDING DESIGN HORIZONS WITH LIVEABLE ROOFTOPS.

COOL ROOF

High Solar Reflectivity

LENGTHENS ROOF LIFE SPAN

Protects the waterproofing membrane from UV rays and accidental perforations.

EASY ACCESS FOR MAINTENANCE

When installed on pedestals, INDUSTRIA slab can be moved for roof system maintenance.

NOTES

See page 26 to 28 for more technical information.

See page 20 for more information about applications.

HD² Polished and HD² Granitex is made-to-order, minimum order of 500 sq. ft.


Deposit required.

Allowable load Capacity of slab on pedestal set (including a safety factor of 2): 1441 lb (653 kg)

*For this application, it is recommended that this product be installed on a concrete base as designed by a local Engineer.

**Salt & Pepper HD² Smooth and HD² Granitex are made-to-order, minimum order of 2,000 sq. ft.

Spe	cifications per pallet		Imperial	Metric
Smooth and Granitex	Cubing		85.25 ft ²	7.92 m ²
	Approx. Weight		2 432 lbs	1 103 kg
	Number of rows		11	
	Coverage per row		7.75 ft ²	0.72 m ²
	Linear coverage per row	Depth	3.94 lin. ft	1.20 lin. m
		Length	3.94 lin. ft	1.20 lin. m




Unit dimensions	in	mm	Units/pallet
Height	2 3/8	60	22 units
Width	23 %	600	
Length	23 %	600	

Spe	cifications per pallet		Imperial	Metric
Polished	Cubing		85.25 ft ²	7.92 m ²
	Approx. Weight		2 432 lbs	1 103 kg
	Number of rows		11	
	Coverage per row		7.75 ft ²	0.72 m ²
	Linear coverage per row	Depth	3.94 lin. ft	1.20 lin. m
		Length	3.94 lin. ft	1.20 lin. m

H A	

Unit dimensions	in	mm	Units/pallet
Height	2 5/16	58	22 units
Width	23 %	600	
Length	23 %	600	

29 | Linear pattern 100% 600x600



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of

