




Part No.	Description	Size
SFTM22	SFTM Sand Filter Top Mount / 1½" Valve	22"
SFTM25	SFTM Sand Filter Top Mount / 1½" Valve	25"

Specifications for SFTM Top Mount Filters

Model No.	SFTM22	SFTM25
Filter Area	2.64 ft²	3.30 ft²
Design Flow Rate	25 gpm/ft²	25 gpm/ft²
Maximum Flow	66 gpm	83 gpm
Six (6) Hr Turn Over Rate	23,760 gallons	29,880 gallons
Eight (8) Hr Turn Over Rate	31,680 gallons	39,840 gallons
Max Working Pressure	35 psi	35 psi
Sand Required	250 lbs.	350 lbs.
Sand Requirements	#20 Silica Sand 40–55mm	#20 Silica Sand 40–55mm
Dimension ('A')	30.75"	34"
Dimension ('B')	33.25"	36.5"
Dimension ('C')	37.5"	40.75"
Dimension ('D')	22.5"	25"
Dimension ('E')	11.5"	13.5"

Sand Requirements

Filter Model	Maximum Flow Rate gpmE sq. ft.(m h m)	Filtration Rate gpm (m h)	Sand Required Weight ' BS (' ilograms)	Maximum Pressure PS (Bars)
SFTM22	25,0 60	66 15,0	250 215	50 3,45
SFTM25	25,0 60	83 18,9	350 160	50 3,45

SFTM Filter Pressure Drop Curve

