

Irritrol® Get more done™

Rain Dial® - R

Irrigation System Controller



User's Guide

- **Setup**
- **Installation**
- **Programming**
- **Troubleshooting**

❖ Indoor and Outdoor 6-, 9-, and 12-station Models ❖

Table of Contents

Getting to Know your Rain Dial-R Controller	2
Getting Started.....	4
Battery Installation & Armchair Programming	4
Overview: Control Module Interface.....	6
Overview: Internal Controller Components.....	8
Installation Procedures.....	10
Installing the Controller Cabinet	10
Connecting the Valve Control Wiring.....	10
Connecting a Rain Sensor (optional)	12
Connecting a Remote Control Unit (optional)	13
Connecting an Earth Ground Device	14
Connecting the Power Source	15
Controller Station Test Feature.....	17
Getting the Most From Your Rain Dial-R Controller	18
What the Display Indicates.....	20
Programming Mode	20
Basic Programming Procedures	23
Setting the Current Time and Day	23
Setting the Valve Run Time Duration.....	23
Setting the Program Cycle Start Time(s).....	24
Setting the Program Watering Day Schedule.....	24

Special Functions	27
Rain Delay	27
Water Budget.....	27
Stack/Overlap	29
Station Delay	30
Pump Control During Station Delay	30
Pump Control Option.....	31
Diagnostic Circuit Breaker	31
Fuse Replacement	31
Manual Operations	32
Semi-Automatic Program Operation	32
Manual Station Operation.....	32
Clear Program Memory	33
Restore Factory Default Settings	34
Troubleshooting Guide.....	35
Contact Information.....	36
Specifications	36
FCC Rules	37

Getting to Know your Rain Dial-R Controller

To take full advantage of your new Rain Dial-R controller, take a few moments to become familiar with its many features:

- **Modular design** – Provides easy access to valve connection terminals and battery storage. Snap-out design enables the control module to be easily removed for “Armchair Programming.”
- **CLIMATE LOGIC® ready** - Built-in RJ-11 jack for direct connection of the CLIMATE LOGIC weather sensing system. (CLIMATE LOGIC automatically alters the controller’s watering time based on the weather. Using the CLIMATE LOGIC accessory earns the Rain Dial-R controller the EPA WaterSense® label.)
- **Remote control ready** – Built-in RJ-11 jack for direct connection to Irritrol R-100-KIT handheld remote control systems.
- **Non-volatile memory** – Keeps all user-defined watering programs stored in memory for several years—without power!
- **“Super Cap”** – Provides a backup power source to sustain current time and date during a power outage lasting up to 24 hours.
- **Battery back-up** – Maintains the current time and date during a power outage lasting longer than 24 hours. Enables “Armchair Programming” of the controller prior to installation.
- **Three independent watering Programs** – Enables automatic watering Programs to be specifically tailored for various portions of the landscape; e.g., lawns, shrubs and trees.
- **Three Start Times per Program** – Enables operation of each automatic Program up to three times per scheduled watering day.
- **Skip Days scheduling** – Enables watering days to be scheduled by interval, ranging from 1 (everyday) to 31 (once every 31 days).
- **Odd/Even date scheduling** – Enables a watering day schedule to be defined by all odd- or even-numbered calendar days.
- **Day Exclusion** – Enables specific weekdays to be excluded from an Odd/Even date or Skip Days watering schedule.
- **Program Stack/Overlap** – Provides the option to limit operation to one Program/station at a time (Stack), or enable up to three Programs or stations to operate concurrently.
- **Station Test Feature** – A convenient test-cycle feature operates each valve station in sequence for a selected run time from 1–10

minutes. Perfect for new installations!

- **Live programming** – Enables programming changes to be made at any time—even during watering!
- Fully automatic, semi-automatic and manual station operations.
- **Manual Advance** – Enables station sequence to be advanced manually during operation (manual or automatic).
- **Off or Stop** – Immediately stops and prevents all watering activity without disturbing Programs.
- **Four places available to quickly remove start times** – Four “OFF” positions are provided within the time display to remove unwanted start times; significantly reducing the amount of scrolling required.
- **Rain Delay** – Enables automatic watering to be postponed from 1 to 9 days; then resume automatically watering as scheduled.
- **Water Budget** – Enables the run time of all stations within a Program to be scaled up to 200% or down to 0% (Off). In addition, a Water Budget value can be applied to individual Programs by specific months when seasonal water budgeting is preferred.
- **MV/Pump control by station** – Enables automatic Master Valve/ Pump operation to be controlled by individual stations.
- **Station sequence delay** – Provides an adjustable delay period between stations during the operating sequence to accommodate slow-closing valves or a required well-recovery period.
- **MV/Pump control during station delay** – Enables Master Valve/ Pump operation to be active or inactive during a station delay period. — Rain Dial-R provides the choice!
- **Built-in circuit protection** – Helps protect the controller’s electronic components from damage due to power and nearby lightning surges.
- **Diagnostic Circuit Breaker** – Enables the controller to detect and bypass any station with a short circuit or faulty solenoid. Displays “FUS” and the bypassed station number for easy troubleshooting.
- **Clear Program Memory** – Enables Program memory to be cleared and reset independently of other Programs.
- **Reset to Factory Program Defaults** – Enables factory default Program settings to be easily restored if required.

Getting Started

Battery Installation & Armchair Programming

Installing a 9V battery (user-provided) serves two important functions: first, it enables the Rain Dial-R to be fully programmed prior to installation, and second, it keeps the control module synchronized with current time and date during a main power interruption lasting up to 24 hours.

Note: *The battery is not capable of operating the sprinkler valves. Main AC power must be applied to the controller to enable operation.*

The control module is designed to be easily removed for complete programming in a more convenient setting, such as your favorite armchair. To remove the control module, simply unplug the ribbon cable connector from the printed circuit board, then carefully remove the module from its snap-in hinges. The Rain Dial-R features non-volatile memory, which keeps the programming information intact, even if the battery dies or is disconnected.

Installing the Battery


1. Open the controller door.
2. Pull the control module open by grasping it from the right edge (press the module release tab on the outdoor model).
3. Press down and outward on top of the battery compartment cover to remove. See **Figure 1**.
4. Attach the battery clip to a 9V Alkaline battery.
5. Stow the battery into the compartment and reinstall the cover.
6. The display will begin flashing **12:00 AM**. (Press any button to halt.)

Note: *To begin setting up a watering Program, refer to "Basic Programming Procedures" on page 10.*

⚠ Caution: To avoid hazards from improper battery type installation, always replace the battery with the same or equivalent battery type.

Always dispose of used batteries properly, as recommended by the battery manufacturer.

Figure 1



Overview: Control Module Interface

1 - Program Switch

Three-position slide switch used to select Program A, B or C for setup, program review and manual operation.

2 - LCD Display

High-contrast LCD panel displays all controller programming and operating information.

3 - Plus and Minus Buttons

Push buttons used to increase and decrease display values during controller setup, programming and manual operations. Adjusts values incrementally (press and release) or by rapid scrolling (press and hold).

4 - Dial

A 25-position rotary switch used to select stations, start times, watering days and special functions for setup, programming and manual operations.

5 - Manual Button

Push button used to start and control manual operations by station. Also serves as a "Next" button to step forward through various setup, programming and manual operations.

6 - Function Switch

A three-position slide switch used to select one of three controller function modes:

- Off or Stop** - Stops all current watering operations, and prevents all automatic and manual operations.
- Set Programs** - Enables automatic watering program setup values to be selected and changed.
- Run or Manual** - Normal switch position for all automatic and manual watering operations.

7 - Semi-Auto Start Button

Push button used to manually start an automatic watering Program. Also used to initiate the Station Test Run operation.

Figure 2



Overview: Internal Controller Components

1 - Battery Compartment

Snap-in cover provides easy access to 9V alkaline battery.

2 - Control Module Ribbon Cable

Quick disconnect cable control module from cabinet for Armchair Programming or service.

3 - Earth Ground Terminal

Wire connection terminal for earth ground conductor.

4 - Sensor Bypass Switch

Switch controls (optional) rain/freeze sensor input.

5 - Safety Fuse

2A Slow-blow fuse protects against short-circuit overload on the 24 VAC input power.

6 - Power Transformer Connection Terminals (24 VAC)

Wire connection terminals for 24 VAC plug-in transformer and power connection point for (optional) wireless rain or rain/freeze sensor.

7 - Valve Common Terminal (VC)

Wire connection terminal for the valve (field) common wire.

8 - Rain Sensor Terminals (Sensor)

Wire connection terminals for (optional) Irritrol RainSensor™ model RS500, RS1000, or RFS1000.

9 - Sensor Terminal Jumper

Sensor terminal jumper wire (removed only when a rain or rain/freeze sensor is connected).

10 - Master Valve/Pump Terminal (MV/Pump)

Wire connection terminal for (optional) master valve or pump start relay.


11 - Valve Station Terminals

Valve connection terminals – one terminal for each valve. (Terminal layout varies by model – 12-station model shown.)

12 - Handheld Remote Control Plug-in Port

Modular connector port required for the Irritrol handheld remote control system models R-100-KIT or for CLIMATE LOGIC weather sensing system.

Figure 3



Installation Procedures

Installing the Controller Cabinet

Select a sheltered location for the indoor model Rain Dial-R such as a garage or service room, preferably within 5' (1.5m) of a grounded electrical outlet. For outdoor controllers, choose a location that protects against direct exposure to sun and contact with irrigation spray, and is at least 5' (1.5m) away from any motorized equipment.

1. Drive the provided stainless steel screw into a wall stud at approximately eye level, leaving 1/4" (6.4mm) of the screw shaft exposed.

Note: Use screw anchors when installing on drywall or masonry.

2. Hang the controller on the screw using the keyhole-shaped slot.
3. To secure the controller, drive one or two screws through the lower mounting holes.

Note: The lower mounting holes in the Outdoor cabinet have a thin veneer that is easily pierced when installing the mounting screw during installation.

Connecting the Valve Control Wiring

For best results, use connection wire cable specifically designed for automatic irrigation systems. Use 18-AWG wire for connections up to 800' from the controller, or heavier 14-AWG (2.0mm²) wire for connections up to 2000'. A separate wire for each valve (and relay) connection and at least one common (return) wire is required.

Note: If control wire conduit is required, install it at this time. For conduit installation, use the 3/4" (19mm) access hole in the indoor cabinet, or the threaded 1.25" NPT opening in the outdoor cabinet.

1. Route the control wire from the controller location to the valve(s).
2. Attach a separate control wire to either lead of each valve solenoid.
3. To provide a common (return) wire, attach the remaining lead of each valve solenoid to a single wire.

Note: To prevent corrosion and a possible short circuit, use waterproof wire connectors on all external wire splices.


For reference at the controller, note the wire color used for each valve connection and its corresponding watering zone.

4. Route the cable through the largest opening in the base of the controller cabinet or through conduit if installed. Remove the cable jacket to expose about 8" of wires. Carefully remove 3/8" of insulation from the end of each wire to be connected.
5. Secure each valve wire to numbered terminal in the preferred

operating sequence order.

6. Connect the common wire to the terminal labeled "VC."
7. If applicable, connect one leg of the master valve or pump start relay control wire to the terminal labeled "MV/PUMP", and the remaining leg to the valve common wire.

Note: The controller does not supply power to operate a pump. The pump start relay must have a nominal coil voltage of 24 VAC, rated at 0.375A maximum.



Connecting a Rain Sensor (optional)

The Rain Dial-R is designed to work in conjunction with Irritrol Rain Sensor models RS500, RS1000 or Rain/Freeze sensor RFS1000 to restrict watering when moisture and/or temperature limits are met.


Note: If connecting an alternate make of rain sensor, ensure it provides normally-closed switch circuit operation.

⚠ IMPORTANT: If a rain sensor is not installed, the sensor terminal jumper wire must remain in place, and the sensor switch must remain in the Bypass position. If either of these conditions are not met, automatic and manual operation will be disabled.

1. Insert the sensor cable through the bottom of the cabinet.
2. Loosen the Sensor terminals and remove the jumper wire.
3. Refer to the installation instructions provided with the Rain Sensor and connect wires accordingly.
4. Place the Sensor switch in the **Active** position.

Note: When the Rain Sensor is active, all watering operations will be terminated and SE_n (Sensor) will be displayed (in the current time dial position).

SE_n




Connecting a Remote Control Unit (optional)

The Rain Dial-R controller is remote-ready and is compatible with the Irritrol Handheld Remote Control model: R-100-KIT. Refer to the user guide provided with the remote kit for complete information.

As shown in the illustration below, the R-100-KIT receiver assembly simply plugs into the receptacle provided in the back of the Rain Dial-R control module.


Note: Irritrol's CLIMATE LOGIC weather sensing system's receiver module plugs in the same way.



Connecting an Earth Ground Device

Note: In order for the electrical surge components built into your Rain Dial-R to function properly, the controller must be connected to an earth ground device, such as a copper-clad ground rod or metal water pipe, using solid copper wire. This connection is especially important when the controller is installed in a lightning-prone area.

1. Connect a 12–16 AWG (2mm²– 1.3mm²) solid-copper wire to the ground device and route into the controller through an access opening in the base of the cabinet.
2. Secure the ground wire to the terminal labeled "Earth Ground."




Connecting the Power Source

Connecting the Power Supply - Indoor Models

Indoor models ship prewired with a power cord ready to be plugged into a standard wall power socket.

Note: To immediately test-run the Rain Dial-R irrigation control system, refer to the "Controller Station Test Feature" on page 8.




Connecting the Power Source - Outdoor Models

⚠ Warning: All electrical components and connection methods must comply with all applicable national and local electrical codes including installation by qualified personnel. These codes may require a junction box installed on controller's 1/2" (13mm) NPT nipple and a means in the fixed wiring of disconnecting AC power having a contact separation of at least 0.120" (3mm) in the line and neutral poles. The connection wire must have insulation rated @ 105° C min.

The controller must be connected to a grounded power source. Do not connect to one phase of a 3-phase power supply used by a pump or other electrical equipment.

Prior to connecting controller wiring, verify that power has been turned off at the source by using an AC volt meter.




Steps

1. Install a 1/2" (13mm) NPT conduit body to the transformer threaded fitting. From the conduit body, install electrical conduit routing to the AC power source (per electrical code).
2. Pull 14 AWG through the conduit into the conduit body.
3. Using twist-on wire connectors, attach the mating wires as shown in **Figure 9**.
4. Close and secure the conduit body cover.

5. Apply power to the controller and check controller operation. If the controller is not operating, disconnect the power at the source and have a qualified electrician check for possible short circuit.


▲ Caution: For maximum protection of the controller electronic components when installed outdoors, always keep the cabinet cover closed and locked whenever possible. Store the cabinet keys in a safe, convenient location.



Controller Station Test Feature

The controller **Station Test** feature enables you to quickly check for proper valve station operation after initial installation or service. The test cycle enables all valve stations to operate in sequence for a temporary run time, adjustable from 1–10 minutes.

1. Place the **Function** switch in the **Set Programs** or **Run** position.
2. Turn the **Dial** to the **Skip Days - Special Functions** position.
3. Press the **Manual** button (one time) to select the Test Run display as shown at right.



4. A 2-minute test run time is set by default. To adjust the run time from 1–10 minutes, press the **+** or **-** button.
5. Press the **Semi-Auto** button to start the watering cycle (station 1 will turn on).
6. Turn the **Dial** to the **Current Time** position. The display will indicate the current clock time (initially **12:00 PM**) and station **1**.
7. To manually advance through the station operating sequence, press the **Manual** button.


Getting the Most From Your Controller

What is an Automatic Program Watering Cycle?

An automatic watering Program begins at its earliest assigned start time on a scheduled watering day. The lowest valve station number assigned to the Program, turns on and operates the sprinklers for the specified run time duration. When finished, the next valve station in numeric order (with an assigned run time in the Program) begins operation. The Program Watering Cycle continues until all valve stations with an assigned run time in the Program have operated.

Why three programs?

A typical residential landscape includes various sections of lawn, shrubs, trees and ground cover, all of which require watering on different schedules for optimum plant health and conservation. To accommodate this, the Rain Dial-R provides three independent watering Programs: A, B and C.



Valve locations

The example below shows how multiple Programs can be used to easily accomplish this:

Program	Start Time	Valve #	Location	Run Time	Schedule
A	(#1) 5:00 AM	1	Front Lawn	15 min.	Odd
		2	Back yard	15 min.	Odd
		3	Side Yard	10 min.	Odd
B	(#1) 3:00 PM	4	Trees (drip)	2 hrs.	Mon
C	(#1) 4:00 PM	5	Garden	5 min.	Skip Days (1)
	(#1) 7:30 PM	5	Garden	5 min.	Skip Days (1)

Avoid unexpected start times

It is possible to set a second start time that begins before the watering cycle from the first start time has finished. When this happens, the start of the second cycle is delayed until the first is complete; so the start time may not occur when you expect it. In addition, increasing run time with the water budget feature may cause an overlap that delays the next scheduled start time.

Avoid watering on a non-watering day

A watering cycle that continues beyond Midnight will run to completion regardless if the next day is scheduled for watering.

Avoid excessive watering

By default, Programs A, B and C can be scheduled to run concurrently (overlap). This feature can be restricted by selecting the Program Stacking option (see page 13). Start times entered for any program will begin automatically when that time occurs. Using multiple programs enables valve stations to water on different schedules or to provide additional watering if one program is not enough. If you need extra water, use more than one start time and/or use the Water Budget feature to increase the valve station run time.

Avoid Creating a low water pressure condition

Start times assigned to different programs are independent. If you set identical or overlapping start times, more than one valve station can run at the same time. The total flow may exceed the available water supply. To avoid this situation, allow more time between start times to reduce the number of valves running at one time, and make sure that multiple Programs do not have the same start times.

Establishing new lawns

Having short, multiple watering cycles each day is especially useful when establishing a new lawn.




Help with electrical problems


The Rain Dial-R will display the station number and the word "FUS" if a short-circuit on a valve station is detected. The detected station will be bypassed, allowing the remaining operable stations to run in the Program watering cycle.




What the Display Indicates

The following examples represent the display information provided to assist you within the various programming, setup and operating modes.

Programming Mode (Function – Set Programs)

- **Current Time** - Displays the current time of day. 
- **Valve Run Times** - Displays the run time set for a selected valve number. Will indicate 01–59 minutes, 1.0–5.9 hours or Off.
- **Start Times** - Displays start time(s) assigned to the selected Program. 
- **Today** - Displays the current day within a Weekday schedule, e.g. Su, Mo, etc., or Skip Days schedule day (1–31). 
- **Schedule** - Displays ON or OFF for each day in a Weekday schedule. When using an Odd/Even schedule, Odd, Even or OFF will be displayed for each station. When using a Skip Days schedule, Once Every (01–31) will be displayed.



- **Special Functions (Dial – Special Functions)**
 - **Station Test Cycle** - All active station numbers will be shown at the top of the display. T:01–10 indicates minutes of run time selected for test cycle. 
 - **Water Budget (Per Program)** - Displays the current Water Budget % or OFF. If a Monthly Water Budget is in use, (– –) will be shown. 
 - **Clear Program Memory** - CLR indicates the Clear Program Memory function is selected. 

- **Well Recovery Time** - Indicates the delay time (00–59 seconds, 1–59 minutes or 1– 2 hours) set to occur between stations in a watering cycle.

W:02
- **Pump Operation during Station Delay** - Indicates pump operation is set to On or Off during a station delay period.

P:OF
- **Program Stacking/Overlap** - Indicates Program Stacking (1:On) or Overlap (3:On)

1.2^H_R
10_{MIN}

option selected.

1:On
- **Odd/Even Schedule** - Indicates Odd or Evn schedule selected.

Odd
- **Calender month** - Displays the current month.

JA
- **Calender month/day** - Displays the current month and day.

J:30
- **Year** - Displays the current year.

08
- **Rain Delay** - Indicates number of days (0–9) set to delay automatic operation.

rd3
- **Monthly Water Budget** - Indicates Water Budget status (On/Off) per month (1–12) and % factor (01–200 or Off) assigned to each month. (Month, day and year may also be set at this time.)

1 2 3 4 5 6 7 8 9 10 11 12
ON

1 2 3 4 5 6 7 8 9 10 11 12
85

Run Mode (Function – Run)

- **Automatic Mode** (Dial – Current Time) - Active valve number and current time are shown.
(Dial – Active valve number)- active valve number, current Program and remaining run time.

Note: *If Water Budget is active, the adjusted run time will be shown.*

³
3:58^{AM}

³
A:34_{MIN}

- **Manual Mode** - (Dial – Active valve number)- Valve number, M: and remaining run time are shown.
- **Rain Delay - OF** (Off) and the number of days until watering resumes alternates with the current time.
- **Diagnostic Circuit Breaker** - "FUS" (Fuse) and the bypassed valve number(s) will alternate with the current time.







⁷
M:06_{MIN}

OF 3

⁶
FUS



Basic Programming Procedures

Setting the Current Time and Day

1. Place the **Function** switch in the **Set Programs** (center) position.
2. Turn the **Dial** to the **Current Time** position.
3. Press the  or  button to set the current time (note AM/PM).
Note: When using the  or  button, press and release to adjust in steps, or press and hold to scroll.
4. Turn the **Dial** to the **Today** position.
5. Press the  or  button to select the current day (abbreviation).
Note: If Odd/Even schedule or Monthly Water Budget is used, the current day of the week is preset and cannot be changed.
6. Return the **Dial** to the **Current Time** position.
7. Return the **Function** switch to the **Run** position.
Note: The flashing colon (:) indicates AC power is present. If the colon is not flashing, the controller is operating on battery power only.



Setting the Valve Run Time Duration

Each valve station can have an individual run time assignment in each Program. Run time can be set for 1–59 minutes (in 1-minute increments) or 1–5.9 hours (in 1/10-hour increments).

1. Place the **Function** switch in the **Set Programs** (center) position.
2. Select Program **A**, **B** or **C**.
3. Turn the **Dial** to select the valve number .
4. Press the  or  button to set the valve run time duration.
5. Repeat steps 3 and 4 for all valves to be assigned to the selected Program.
6. Repeat steps 2–5 for each Program as needed.
7. When finished, return the **Dial** to the **Current Time** position.
8. Place the **Function** switch in the **Run** position.

Setting the Program Cycle Start Time(s)

Each Program can have three separate start times. For mature landscapes, one start time per Program is generally sufficient. When establishing a new lawn, using two or three start times with short valve run times can provide the additional irrigation required for grow-in, at a reduced rate to help prevent runoff and erosion.



1. Place the **Function** switch in the **Set Programs** position.
2. Select Program **A, B** or **C**.
3. Turn the **Dial** to select **Start Time 1 (2 or 3)**.
4. Press the  or  button to set the start time (note AM/PM).
Note: To remove a start time, select **Off**, displayed between 11:59–12:00 and 5:59–6:00 (AM and PM).
5. Repeat steps 3 and 4 to set additional start times for this Program.
6. Repeat steps 2–5 for each Program as needed.
7. When finished, return the **Dial** to the **Current Time** position.
8. Return the **Function** switch to the **Run** position.

Setting the Program Watering Day Schedule

Watering days can be scheduled for each Program using one of the following methods:

- **Weekdays** - Schedules watering for specific days of the week.
- **Skip Day** - Schedules watering days by interval frequency; e.g., every day (01), every-other-day (02) etc.
- **Odd/Even Date** - Schedules watering days based on Odd- or Even-numbered calendar days.



To set a Weekdays Schedule:



1. Place the **Function** switch in the **Set Programs** position.
2. Select Program **A, B** or **C**.
3. Turn the **Dial** to the desired weekday position.
4. Press the  button to select the day (On), or the  button remove the day (Off) from the watering day schedule.
5. Repeat steps 3 and 4 to schedule additional weekdays as needed.
6. Repeat steps 2–5 for each Program as needed.
7. When finished, return the **Dial** to the **Current Time** position.



8. Return the **Function** switch to the **Run** position.

Note: Each Program can have a Skip Days or an Odd/Even Date watering schedule, but not both. One schedule must be turned off to enable the alternate schedule to be selected.

To Set a Skip Day Schedule:

1. Place the **Function** switch in the **Set Programs** position.
2. Select Program **A, B** or **C**.
3. Turn the **Dial** to the **Skip Days/Special Functions** position.
4. Press the  /  buttons to select the **Skip Day** interval (**01–31**) days.



Note: To turn Off a Skip Day schedule, press the  or  button to display OFF.



5. Turn the **Dial** to the **Today** position.
6. Press the  /  buttons to select the current day within the **Skip Day** interval schedule.

Note: For example, if you have selected a 3-day schedule, and prefer to have watering start today, select 03. To water tomorrow, select 02. To watering in three days, select 01.



7. Repeat steps 2–6 for each Program as needed.
8. When finished, return the **Dial** to the **Current Time** position.
9. Return the **Function** switch to the **Run** position.





To Set an Odd/Even Date Schedule:

1. Place the **Function** switch in the **Set Programs** position.
2. Select Program **A, B** or **C**.
3. Turn the **Dial** to the **Skip Days/Special Functions** position.
4. Press the **Manual** button (seven times) to display dashes (– – –).
5. Press the  button to select **Odd**, or the  button to select **Even** (EVn).

Note: To turn Off an Odd/Even Date schedule, press the  or  button to display dashes (– – –).

6. Press the **Manual** button (one time) to select the calendar **Month** – January (**JA**) will be displayed.


7. Press the  /  buttons to adjust the month setting.

JA - January	Fe - February	MR - March
AP - April	My - May,	JN - June,
JL - July	AU - August	SE - September,
OC - October	nO - November	DE - December.
8. Press the **Manual** button (one time) to select the **Day** setting.
9. Press the  /  buttons to select the current calendar day.
Example: September 17th would be displayed as **S:17**.
10. Press the **Manual** button (one time) to select the **Year** setting.
11. Press the  /  buttons to select the year (09 = 2009).
12. When finished, return the **Dial** to the **Current Time** position.
13. Repeat steps 2–10 for each Program as needed.
14. Return the **Function** switch to the **Run** position.

***Note:** When an Odd/Even schedule is used, confirm that the current day of the week is correctly set by turning the Dial to the Today position. If the day of the week is incorrect, adjust the month, day and year settings to properly synchronize the controller. Also note that when using an Odd/Even schedule, watering never occurs on the 31st of any month or February 29th of a leap year.*

Day Exclusion Feature

When using a Skip Days and Odd/Even date watering schedule, watering will not occur on the same days from week to week. To restrict watering on specific weekdays; e.g., for scheduled mowing or maintenance, use the Day Exclusion feature as follows:

1. Place the **Function** switch in the **Set Programs** position.
2. Select Program **A**, **B** or **C**.
3. Turn the **Dial** to the **Day** to be excluded.
4. Press the  button display **OFF**.
5. Repeat steps 3 and 4 to exclude additional days.
6. When finished, return the **Dial** to the **Current Time** position.
7. Return the **Function** switch to the **Run** position.

This completes the basic programming requirements for automatic operation.

Special Functions

Rain Delay

The **Rain Delay** feature (for use when a weather sensor is not installed) enables automatic watering operation to be suspended for a period of 1 to 9 days; then resume watering automatically as scheduled.

1. Place the **Function** switch in the **Set Programs** position.
2. Turn the Dial to the **Skip Days - Special Functions** position.
3. Press the **Manual** button (repeatedly) to display **rd0** (Rain Delay = 0 days).
4. Press the **+** / **-** buttons to select a Rain Delay period of 1 to 9 days.
5. Return the **Dial** to the **Current Time** position.
6. Return the **Function** switch to the **Run** position.

Note: When the Rain Delay function is active, the display will alternately indicate the current time of day and the number of days remaining until automatic operation resumes. To cancel Rain Delay at any time, decrease Rain Delay setting to 0 days.

Water Budget

The **Water Budget** feature enables the run time of all stations, assigned to a specific Program, to be simultaneously adjusted up or down by percentage. From the baseline of 100%, run times can be reduced to 0% (Off) or increased up to 200%.

To help prevent runoff when selecting a Water Budget value above 100%, the adjusted run time is automatically cut in half, and the watering cycle is run twice. For example, increasing the Water Budget to 160% would first increase a 10-minute station run time to 16 minutes. However, the station will run for 8 minutes in two consecutive watering cycles.

All zone run times are retained in the timer memory and returned to their set value when the season adjust is reset to 100%. The only time a station run time will appear changed is during operation.

For additional control, a Water Budget factor can be assigned universally to a Program, or applied to a Program by specific months of the year – when Water Budgeting by seasonal demand is preferred.

Note: Each Program is limited to one Water Budget method at a time. Applying a Water Budget by monthly demand will override a basic Water

Budget adjustment value. Conversely, to apply a basic Water Budget, all months must be set at 100%.

To Apply a Basic Water Budget:

1. Turn the **Dial** to the **Skip Days - Special Functions** position.
2. Select Program **A, B** or **C**.
3. Place the **Function** switch in the **Set Programs** position.
4. Press the **Manual** button (twice) to display **100** (%).
5. Press the **+** or **-** button to adjust the % factor (10% increments).
Note: Decreasing the Water Budget value beyond **10%** to "OFF" prevents the Program from running automatically.
6. Return the **Dial** to the **Current Time** position.
7. Return the **Function** switch to the **Run** position.



To Apply a Monthly Water Budget:

Note: Applying a monthly Water Budget requires the current date to be set. If an Odd/Even watering schedule has been assigned, the current date was established during the procedure. Steps 1–11 in the following procedure establishes the current date. To bypass this portion of the procedure, begin at step 12.

1. Turn the **Dial** to the **Skip Days - Special Functions** position.
2. Select Program **A, B** or **C**.
3. Place the **Function** switch in the **Set Programs** position.
4. Press the **Manual** button repeatedly to select the Monthly Water Budget display as shown at right.
5. Press the **+** button to select ON.
6. Press the **Manual** button one time to select the calendar Month setting. January (JA) will be displayed.
7. Press the **+** or **-** button to select the current month abbreviation:
JA - January **Fe** - February **MR** - March
AP - April **My** - May, **JN** - June,
JL - July **AU** - August **SE** - September,
OC - October **nO** - November **DE** - December.
8. With the month selected, press the **Manual** button one time to select the **Day** setting.
9. Use the **+** / **-** buttons to select the current calendar day.



For example, April 4 would be displayed as **A:04**.

10. Press the **Manual** button one time to select the **Year** setting.
11. Press the **+** / **-** buttons to select the current year (09 = 2009).
12. Press the **Manual** button (as needed) to select the Monthly Water Budget display. 1 (January) is selected with its current Water Budget value (100% by default). 
13. To change the month selection, press the **Manual** button.
14. Press the **+** / **-** buttons to adjust the % factor in 1% increments down or up (Off or 10%–200%). 
15. Repeat steps 13 and 14 to set additional months.
16. When finished, return the **Dial** to the **Current Time** position.
17. Return the **Function** switch to the **Run** position.

Stack/Overlap

The **Stack/Overlap** option determines how the controller will manage concurrently scheduled programs or manually started valve stations. By default, the **Overlap** option is selected, enabling simultaneous operation of up to three Programs or manual valve stations. Selecting the **Stack** option limits operation to either one automatic Program or manual valve station.

⚠ Important:

- The **Stack** option prevents a scheduled Program or manually operated valve station from operating until any current operation has been completed or canceled. At midnight, any remaining scheduled Programs stacked in queue will be canceled.
 - Selecting the **Overlap** option can cause the electrical and/or hydraulic capacity of your irrigation system to be exceeded. Always plan your watering schedule carefully!
1. Turn the Dial to the **Skip Days - Special Functions** position.
 2. Place the **Function** switch in the **Set Programs** position.
 3. Press the **Manual** button repeatedly to display **3:On** (three programs or stations can run concurrently).
 4. To select the **Stack** option, press the **+** / **-** button to choose **1:On**.
 5. Return the **Dial** to the **Current Time** position.
 6. Return the **Function** switch to the **Run** position.

Station Delay

Irrigation systems that utilize a well-water source or have slow-closing valves, may require a delay period to occur between consecutive stations during a watering cycle. The Station Delay feature enables a delay period to be set from 1 second to 2 hours.

1. Place the **Function** switch in the **Set Programs** position.
2. Select Program **A**, **B** or **C**.
3. Turn the **Dial** to the **Skip Days - Special Functions** position.
4. Press the **Manual** button repeatedly to display **W:00** (no delay).
5. Press the **+**/**-** buttons to set the delay time: 00–59 seconds, 01–59 minutes (MIN) or 1.0–2.0 hours (HR.).

Note: *Hold the button down to scroll. The display will continuously scroll from seconds to minutes to hours (:00 = no delay time).*

6. Return the **Dial** to the **Current Time** position.
7. Return the **Function** switch to the **Run** position.

Pump Control During Station Delay


The Pump Control feature is generally used in conjunction with the Station Delay feature, enabling the pump/master valve to be turned on or off during the delay between consecutive stations in a watering cycle. For example, a system with slow-closing valves may require the pump to remain on throughout the watering cycle to assist valve closure. Alternately, a system utilizing a well-water supply source may require the pump to be off when an extended delay period between stations is required for adequate well-recovery time.

1. Place the **Function** switch in the **Set Programs** position.
2. Select Program **A**, **B** or **C**.
3. Turn the **Dial** to the **Skip Days - Special Functions** position.
4. Press the **Manual** button (repeatedly) to display **P:OF** (Pump Off).
5. Press the **+**/**-** button to toggle between **P:OF** and **P:On**.
6. Return the **Dial** to the **Current Time** position.
7. Return the **Function** switch to the **Run** position.

Pump Control Option

By default, the pump control circuit is activated simultaneously with any automatic or manual valve station operation. When pump operation is not required for specific valve stations; e.g., drip irrigation, the pump control circuit can be easily disabled as needed.


Note: *The Pump control option applies to the selected valve station regardless of its Program assignment.*

1. Place the **Function** switch in the **Set Programs** position.
2. Turn the **Dial** to select the appropriate valve station number.
3. Press the **Manual** button: **P:On** (Pump On) will be displayed.
4. To disable the pump control circuit from the valve station, press the  button to display **P:OF** (Pump Off).
5. Repeat steps 2–4 for additional valve stations as required.
6. Return the **Dial** to the **Current Time** position.
7. Return the **Function** switch to the **Run** position.

Diagnostic Circuit Breaker

The prompt “**FUS**” and the malfunctioning valve station number will be alternately displayed with the current time. The valve station will be bypassed during the watering cycle, enabling all remaining valve stations to run as scheduled.

With the **Dial** set in the **Current Time** position, press any button to clear the “**FUS**” display.

 **Important: Determine the cause of the malfunction and take corrective action as necessary. Clearing the display will not resolve the problem.**

Fuse Replacement

 **Caution: The 2.0A safety fuse protects the transformer from damage due an excessive current load (short circuit) condition.**

Locate and eliminate the cause of the problem before replacing the fuse. For continued protection against risk of fire, replace only with the same fuse type and rating.

1. Disconnect power to the controller.
2. Carefully remove the safety fuse from the terminal board (see **Figure 3**, page 4 for fuse location).
3. Install a new 2.0A slow-blow fuse, ensuring that it is properly seated

in the retaining clip.

4. Reconnect power to the controller.

Manual Operations

Semi-Automatic Program Operation

Semi-Automatic Program operation enables an automatic Program watering cycle to be started manually at any time. Once running, the manual advance feature enables you to step through the programmed station sequence.

1. Place the **Function** switch in the **Run** position.
2. Turn the **Dial** to the **Current Time** position.
3. Place the **Program** switch to select **A, B or C**.
4. Press the **Semi-Auto** button to start the watering cycle.

***Note:** Once started, the station sequence can be manually advanced by placing the Dial to **Current Time** and pressing the Manual button.*



***Note:** The Manual Advance feature applies to all Automatic, Semi-automatic and Station Test watering operations for the selected Program.*

***Note:** To terminate watering operations, place the **Function** switch momentarily in the **OFF or Stop** position.*

Manual Station Operation

Manual station operation provides manual control at the individual station level and provides the following four control options:

- Station(s) can be operated for a one-time run duration without altering the station's set run time in an automatic Program.
 - Operation can be limited to only one station running manually or set to allow three stations to run at the same time.
- Note:** Refer to "Stack/Overlap Option" on page 26 for additional information regarding manual operations.*
- Works with the Manual Advance feature to move up through the station sequence.
1. Place the **Function** switch in the **Run** position.
 2. Turn the **Dial** to the **Station Number** to be manually operated.

3. Use the / buttons to set a manual operation run time ranging from 1 minute to 5.9 hours.
4. Press the **Manual** button to start the operation.
5. If this is the only station to be run manually, skip step 6 and continue at step 7 below.
6. To add additional stations to the manual run operation, repeat steps 2 through 4 as needed, then continue at step 7.

Note: Depending upon the Stack/Overlap setting, additional stations selected (beyond the one or three option setting) will register as OFF when entered with the Manual button. However, they will be placed (stacked) in the manual sequence to run.


7. Turn the **Dial** to the **Current Time** position.

Note: Once started, the station sequence can be manually advanced by pressing the **Manual** button.


Note: To terminate manual watering operations, place the **Function** switch momentarily in the **OFF or Stop** position.


Clear Program Memory

The **Clear Program Memory** feature enables you to safely clear the automatic watering program settings defined for a specific Program without affecting any remaining Program information. The memory erase function applies only to the specified Program, leaving the remaining Programs intact.

 **Important: The "Clear Program" function completely erases all user-defined programming information from the selected Program including: start times, run times, and watering day schedule.**

Note: To reset the controller (all Programs) to factory default settings, refer to "Restore Rain Dial-R to Factory Default Settings" on page 35.

1. Place the **Function** switch in the **Set Programs** position.
2. Place the **Program** switch to select **A, B or C**.
3. Turn the **Dial** to the **Skip Days - Special Functions** position.
4. Press the **Manual** button repeatedly to display **CLr** (Clear).
5. Press the  button one time. The display will show the prompt: **CL?** (Clear?).

6. To complete the process, press the  button again to display the prompt "**End**".
7. Return the **Dial** to the **Current Time** position.
8. Return the **Function** switch to the **Run** position.

Restore Factory Default Settings

The Rain Dial-R factory default settings for automatic program operation are as follows:

Current Time: 12:00 AM.

Current Day: Sunday.

Current Date: January 1, 2008.

Program **A**: Weekday watering schedule with all days active.
One start time at 7:00 AM.
10-minute run time on all valve stations.

Program **B** and **C**: No watering days, station run times or start times.

Skip Days and Odd/Even day schedule: OFF - all Programs.

Excluded days in Skip Days or Odd/Even schedule: None.

MV/Pump operation: ON - all stations.

Well Recovery period: 00 (OFF) - all Programs.

MV/Pump operation during Well Recovery: OFF - all Programs.

Water Budget: 100% - all Programs and months.

Rain Delay: 0 days.

Stack/Overlap: Overlap - 3 Programs or 3 manual stations.

To restore factory default settings:

1. Turn the dial to **Start Time** number 3.
2. Repeatedly press the **Manual** button.*
3. After the first 7 depressions, the firmware version appears in the display.
4. On the 14th depression, "CLR" appears.
5. On the 15th depression, "ALL" appears.
6. On the 16th depression, "OFF" begins flashing indicating erasure of all user-entered information.
7. Turn the dial back to CURRENT TIME. "12:00AM" appears in the

display.

* The numerous button depressions required are to avoid inadvertent or accidental erasure.

Troubleshooting Guide

Problem	Possible Cause	Correction
Display blank.	No power.	Check transformer/power connections, 2A fuse, and AC power.
Some valves do not operate.	Faulty or improper valve wire connections. Debris in valve.	Check and correct all valve wire connections. Inspect, clean/replace valve solenoid/plunger and diaphragm.
No valves operate.	Function switch OFF. Faulty valve common wire connection. Sensor switch in Active position—no sensor or jumper connected. No start time set.	Set switch to Run. Check/correct valve common connection. Set switch to Bypass or install terminal jumper. Set Program start time.
Watering on wrong day.	Watering day schedule set incorrectly.	Correct watering day schedule as needed.
Current time is wrong and flashing.	Power interruption without battery backup.	Install/replace battery, reset current time.
"FUS" and a station number alternates with current time.	Short or over-current on valve station.	Check/replace valve solenoid and splices.
Valve will not turn off (with Function Switch in the OFF position).	Valve malfunction.	Inspect, clean/replace valve solenoid/plunger and diaphragm.
"SEN" alternates with time of day.	Watering on hold due to sensor operation.	Normal operation for sensor. Set Sensor switch to Bypass.

Contact Information

The troubleshooting solutions are provided to help resolve problems that may arise during setup and/or operation of the Rain Dial-R controller.

If the problem is not listed or cannot be resolved with the provided solutions, contact an authorized Irritrol product expert for assistance via phone or email.

U.S./Canada: Phone: 1-800-634-8873 (7:30 am–4 pm, M–F, PT)
E-mail: irrigationsupport@irritrol.com

Europe: Phone: +39-076540191
E-mail: intlirrigationsupport@irritrol.com

Australia: Phone: +61 8 8300 3633
E-mail: intlirrigationsupport@irritrol.com

Specifications

Input Power

- **Outdoor Model:** 120 VAC 60 Hz, 30 VA (Domestic)
230/240 VAC, 50 Hz, 30VA
(International)
- **Indoor Model:** 24 VAC, 60 Hz, 30 VA (Domestic)
(from plug-in transformer) 24 VAC, 50 Hz, 30 VA
(International and Australian)

All Models:

- Station Output: 24 VAC at 0.5A, 1.0A (maximum total)
- Master Valve/Pump Start Relay Output: 24 VAC at 0.375A
- 2.0A Slow-blow Fuse
- Battery Back-up (time, day and date)
- Operating temperature range: 32°F to 140°F (0°C to 60°C)

⚠ Caution: The Rain Dial is designed to operate 24 VAC valve solenoids rated at 0.25A (6 VA). Total current load during operation must not exceed 1.0A. A maximum of two solenoids per station terminal may be used if the total station load does not exceed 0.5A. No more than three solenoids (plus MV/Pump circuit) should operate concurrently. In irrigation systems where multiple controllers are used, each controller must utilize a separate valve common circuit.

FCC Rules

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Subpart J of Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

1. Reorient or relocate the receiving antenna.
2. Increase the separation between the equipment and receiver.
3. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
4. Consult the dealer or an experienced radio/TV technician for help.

The user may find the following booklet prepared by the Federal Communications Commission helpful:

"How To Identify and Resolve Radio-TV Interference Problems." This booklet is available from the U.S. Government Printing Office, Washington, DC 20402, stock # 004-000-00345-4.

International: This is a CISPR 22 Class B product.



WARNING: Cancer and Reproductive harm – www.P65Warning.ca.go.
For more information, please visit www.toro.com/CAProp65.

Patents: www.ttcopats.com

Notes

