SAFETY DATA SHEET



Texrite Ac-cent Sanded Grout

		As of date: August 7, 2015
Section 1	Product Description	
Product Name: Recommended Use: Synonyms:	Ac-cent Sanded Grout Sanded Grout Latex –Polymer Grout, Polymer modified grout, Tile joint filler mortar	
Manufacturer:	Texas Cement Products, dba Texrite 4000 Pinemont, Houston, Texas 77018, USA 713-682-8411 www.texrite.com	
General Phone Number General Fax Number:	: 713-682-8411 (8am-3pm, CST, M-F) 713-688-2488	

Section 2 Hazards Identification

Classification of the chemical in accordance with paragraph (d) of 1910.1200;

Signal Word:	Danger
GHS Class:	Serious Eye Damage/Eye Irritation, Category 1, Skin Corrosion/Irritation, Category 2 Skin Sensitizer/Allergic skin reaction, Category 1 Carcinogen/May cause cancer if inhaled, Category 1A, May cause respiratory irritation, STOT SE3 Damage to organs through prolonged or repeated exposure if inhaled, STOT RE1
Hazard Statements:	H100s = General, H200s = Physical, H300s = Health, H400s = Environmental
	 H315 -Causes skin irritation. H317 -May cause an allergic skin reaction. H318 -Causes serious eye damage. H335 -May cause cancer if inhaled. H350A -May muse respiratory irritation. H372A - Causes damage to organs through prolonged or repealed exposure if inhaled.
Precautionary Statements	 S: P201 -Obtain special instructions before use. P202 -Do not handle until all safety precautions have been read and understood. P260B -Do not breathe dust. P264.3 -Wash skin thoroughly after handling. P270 -Do not eat, drink or smoke when using this product. P271 -Use only outdoors or in a well-ventilated area. P272 -Contaminated work clothing should not be allowed out of the workplace P280B -Wear protective gloves and eye, face protection. P302+P3529, -IF ON SKIN. Wash with plenty of water P304+P340 -IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 -IF exposed or concerned: Gel medical advice / attention. P310A -Immediately call a POISON CENTER. P314 -Get medical advice/attention if you feel unwell.

P321 .A -Specific treatment (see supplementary instructions on this label) P333+P313 -If skin irritation or rash occurs: Get medical advice/attention. P362+P364 -Take &contaminated clothing and wash it before reuse.

P403+P233 -Store in a well-ventilated place. Keep container lightly dosed.

- P405 -Store locked up.
- P501A -Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Ingredients(s) with unknown acute toxicity: None

Hazards not otherwise classified identified during the classification process: None

Section 3 Composition Information and Ingredients

Mixture:

Component Name	CAS #	WT %	<u>Classification</u>
Silica Sand	14808-60-7	50-80%,	Carc. 1A, H350A, STOT RE 1, H372A
Portland Cement	65997-15-1	20-45%	STOT SE 3, H335: Eye Dam 1,H318 Skin Sens. 1, H317; Skin Irrit. 2, H315
Titanium dioxide	13463-67-7	0.1-5%,	Carc. 2, H351
Calcium sulfate	7778-18 -9	0.1-5%	STOT SE 3, H335:

Section 4 First-Aid Measures

Emergency and First Aid Procedures

Inhalation:	Remove casualty to fresh air and keep at rest. If breathing is irregular or stopped, administer artificial respiration. In case of inhalation, consult a doctor immediately and show him packing or label.			
Eyes:	IF IN EYES: Rinse cautiously with water with the eyelids open for a sufficient length of time. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation continues, then get medical advice/attention immediately. Protect uninjured eye.			
Skin Contact:		IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.		
Ingestion:	If swallowed, do label.	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.		
	Most Important symptoms/effects, acute and delayed: Eye Irritation Eye damages Skin Irritation Erythema Indication of any immediate medical attention and special treatment needed: In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).			
Section 5	Fire Fighting M	leasures		
Extinguishing Media: Fire Fighting Methods and Protection: Fire and/or Explosion Hazards:		Use carbon dioxide, or water spray when fighting fires involving this material. Firefighters should wear full protective equipment and NIOSH approved self- contained breathing apparatus. Do not inhale explosion and combustion gases. Burning produces heavy smoke.		
Hazardous Combustion Products: Explosive properties: Oxidizing properties: Special protective equipment and precau		N.A. N.A. N.A.		

Collected contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

Section 6 Accidental	Release Measures
Steps to Take in Case Material Is	Wear personal protection equipment.Wear breathing apparatus if exposed to vapors/dusts/aerosols. Provide adequate ventilation. Use appropriate respiratory protection. See protective measures under section 7 and 8. Ventilate
Released or Spilled:	the contaminated area. Suitable material for taking up: absorbing material, organic, sand. Wash with plenty of water.
Section 7 Handling ar	nd Storage
Handling:	Avoid contact with skin and eyes, Inhalation of vapors and mists. Exercise the greatest care when handling or opening the container. Use localized ventilation system. Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. Contaminated clothing should be changed before entering eating areas. Do not eat or drink while working. See also section 8 for recommended protective equipment. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Storage:	Keep dry. Keep container tightly closed & upright when not in use to prevent leakage.

Storage Code:

N.A.

Section 8	Evno		trals / Dorsa	nal Dratasti	0.0			
Section 8			trois / Perso	nal Protecti	on			
List of compon	ents with OEL valu	le						
<u>Component</u>	OEL Type Country	Ceiling	Long Term <u>mg/m3</u>	Long Term ppm	Short Term mg/m3	Short Term ppm	<u>Behavior</u>	Note
Silica Sand	ACGIH		0.025					A2-SupsectedHuman Carcinogen; lung cancer; pulmonary fibrosis
Portland cement	OSHA OSHA ACGIH		15 5.0 1					A4- Not classifiable as a Human Carcinogen; pulmonary function: respiratory symptoms;
Titanium dioxide	OSHA		15					asthma A4- Not classifiable as a Human Carcinogen;
	ACGIH		10					lower tract irritation
Calcium sulfate	OSHA OSHA ACGIH		15 5 10					nasal symptoms
Control Param	eters							
Engineering Measures: General room ventilation might be required to maintain operator comfort under normal conditions of use. Avoid generating airborne dust								
Personal Protective Equipment (PPE): Respiratory Protection:		No respiratory protection required under normal conditions of use.						

No respiratory protection required under normal conditions of use. Use NIOSH approved air purifying respirator with dust filter. Wear close fitting safety glasses or goggles when handling this product. Avoid skin contact by wearing clothing that provides comprehensive protection. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Respirator Type(s):

Eye Protection:

Skin Protection:

Section 9 Physical and C	hemical Properties
A	Develop verieve polidoplan
Appearance:	Powder, various- solid color
Odor:	Cement likes
Odor Threshold:	None
pH (Neutrality):	N.A.
Melting Point/Freezing Point:	N.A.
Boiling Range (Ibp,50%,Dry Point):	N.A.
Flash Point (Test Method):	N.A.
Evaporation Rate	
(n-Butyl Acetate=1):	N.A.
Flammability Classification:	N.A.
Lower Flammable	
Limit in Air (% by vol):	N.A.
Upper Flammable	
Limit in Air (% by vol):	N.A.
Vapor Pressure (mm of Hg)@20 C:	N.A.
VAPOR DENSITY (Air=1):	N.A.
GRAVITY @ 68/68F / 20/20C:	
Specific Gravity (Water=1):	N.A.
Pounds/Gallon:	N.A.
Water Solubility:	Soluble
Partition Coefficient (n-Octane/Water):	N.A.
Auto Ignition Temperature:	N.A.
Decomposition Temperature:	N.A.
Becomposition remperature.	N.7 (.
Other Information	
Substance Groups relevant properties	N.A.
Miscibility:	N.A.
Fat Solubility:	N.A.

Section 10

Conductivity:

Stability and Reactivity

N.A.

Reactivity:
Chemical Stability:
Possibility of Hazardous Reaction:
Conditions to Avoid:
Incompatible Materials:
Hazardous Decomposition Products:

Stable under normal conditions. No data available None Stable under normal conditions. None in particular None

Section 11	Toxicological Information
Toxicological Information of	of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentrations of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological Information on the main components of the mixture:

Silica Sand	a) acute toxicity	LD50 (Oral): =500 mg/kg (Rat)
Titanium dioxide	a) acute toxicity	LD50 (Oral):>10000 mg/kg (Rat)
Calcium sulfate	 a) acute toxicity 	LD50 (Oral): >3000 mg/kg (Rat)

If not differently specified, the information required in the regulation and listed below must be considered NA.

a) acute toxicity

- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitization
- e) germ cell mutagenicity

	 g),reproductive toxicity h) STOT - single exposure I) STOT -repeated exposu J) aspiration hazard 	
Substance(s) listed on the	IARC Monographs:	
	Silica Sand	Group 1
	Titanium Dioxide	Group 2B
Substance(s) listed as OSI	HA Carcinogen(s):	·
	Silica Sand	
	Titanium Dioxide	
Substance(s) listed as NIC	SH Carcinogen(s):	
	Silica Sand	
	Titanium Dioxide	
Substance(s) listed on the	NTP report on Carcinogen	s:
	Silica Sand	

f) carcinogenicity

Section 12 Ecological Information

Overview:

Adopt good working practices, so that the product is not released Into the environment.

Ecotoxicity:

<u>QTY , Chemical Na</u> me 50-80%, Silica Sand	CAS Number 14808-60-7	Eco Toxicity LC 50 a) Aquatic acute toxicity carp >10000.00000 mg/L 72h
0.1-5 %, Calcium sulfate	7778-18 -9	LC 50 a) Aquatic acute toxicity Fish Lepomis macrochirus =2980mg/L 96h EPA LC 50 a) Aquatic acute toxicity Fish Pimephales promelas > 1970mg/L 96h EPA
Persistence and degradability:The polyBioaccumulative potential:No dataMobility in soil:No dataOther Adverse Effects:No data		a

Section 13 Disposal Considerations

Disposal Methods:

Waste Disposal Code(s):

Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance. Not Determined

Section 14	Transport Information			
UN number				
ADR-UN number	: N/A			
DOT-UN number	: N/A			
IATA-UN number	r: N/A			
IMDG-UN numbe	er: N/A			
UN proper shipping name				
ADR-Shipping N	ame: N/A			
DOT Proper Shipping Name: N/A				
IATA-Technical r	name: N/A			
IMDG-Technical	name: N/A			
Transport hazard class(es)				
ADR- Class:	, N/A			
DOT Hazard Cla	ss: N/A			
IATA- Class:	N/A			
IMDG-Class:	N/A			
Packing group				
ADR Packing Gr	oup: N/A			

DOT-PackInq group:	N/A
IATA-Packing group:	N/A
IMDG-Packing group:	N/A
Environmental hazards	
Marine pollutant:	No
Environmental Pollutant:	N.A.
Transport in bulk according to Annex II of MA	ARPOL73/78 and the IBC code:
	N.A.
Special Precautions	
Department of Transportation (DOT):	
DOT-Special Provision(s):	N/A
DOT Label(s):	N/A
DOT Symbol:	N/A
DOT Cargo Aircraft:	N/A
DOT Passenger Aircraft:	N/A
DOT Bulk:	N/A
DOT Non-Bulk:	N/A
Road and Rail (ADR-RID):	
ADR-Label:	N/A
ADR Hazard identification number:	N/A
ADR Tunnel Restriction Code:	N/A
Air (IATA) :	
ÍATA- Passenger Aircraft:	N/A
IATA- Cargo Aircraft :	N/A
IATA- Label:	N/A
IATA- Subrisk:	N/A
IATA- Erg:	N/A
IATA- Special Provisions:	N/A
Sea (IMDG):	
IMDG -Stowage Code:	N/A
IMDG -Stowage Note:	N/A
IMDG -Subrisk:	N/A
IMDG -Special Provisions:	N/A
IMDG -Page:	N/A
IMDG -Label:	N/A
IMDG -EMIS:	N/A
IMDG -MFAG:	N/A

Section 15

Regulatory Information

USA - Federal regulations

TSCA • Toxic Substances Control Act TSCA Inventory: All the components are fisted on the TSCA inventory

TSCA listed substances:

is listed in TSCA	Section 8b
is listed in TSCA	Section 8b
is listed in TSCA	Section 8b
is listed in TSCA	Section 8b
	is listed in TSCA is listed in TSCA

SARA - Superfund Amendments and Reauthorization Act Section 302 – Extremely Hazardous Substances: no substance listed

Section 304 –Hazardous substances:	no substance listed
Section 313 – Toxic chemical list:	no substance listed


CERCLA – Comprehensive Environmental Response, Compensations, and Liability Act Substance(s) listed under CERCLA: no substance listed

CAA – Clean Air Act

Texrite Ac-cent Sanded Grout -SDS

CAA Substances listed:	no substance listed		
CWA – Clean Water Act CWA Substances listed:	no substance listed		
USA - state specific regu	lations		
California Proposition 65 Substance(s) listed under Silica Sand Titanium Dioxide	California Proposition 65 listed as carcinogen listed as carcinogen		
Massachusetts right to kno Substance(s) listed under Silica Sand Portland cement Titanium dioxide Calcium sulfate	w Massachusetts Right to Know;		
Pennsylvania Right to kno Substance(s) listed under Silica Sand Portland cement Titanium dioxide Calcium sulfate	<i>w</i> Pennsylvania Right to Know;		
New Jersey Right to know Substance(s) listed under New Jersey Right to Know; Silica Sand Portland cement Titanium dioxide Calcium sulfate			
Section 16	Other Information		

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems. NFPA: HMIS III:



Code Description

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Cause serious eye damage.
H335	May cause respiratory irritation.
H350A	May cause cancer if inhaled
H372A	Causes damage to organs through prolonged or repeated exposure if inhaled

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Texrite makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

ACGIH	-American Conference of Governmental Industrial Hygienists	OSHA	-Occupational Safety and Health Administration
CAS	-Chemical Abstract Service Number	PEL	-Permissible Exposure Limit
CERCL	A -Comprehensive Environmental Response,	ppm	-Parts per million
	Compensation, and Liability Act	RCRA	-Resource Conservation and Recovery Act
DOT	-U.S. Department of Transportation	SARA	-Superfund Amendments and
IARC	-International Agency for Research on		Reauthorization
	Cancer	TLV	-Threshold Limit Value
N/A	-Not Available	TSCA	-Toxic Substances Control Act
NTP	-National Toxicology Program	IDLH	-Immediately dangerous to life and

health

SAFETY DATA SHEET



Texrite Ac-cent Nonsanded Grout

As of date: August 7, 2015

Section 1	Product Description
Product Name: Recommended Use: Synonyms:	Ac-cent Nonsanded Grout Nonsanded Grout Unsanded Grout, Latex-polymer tile grout, Latex-polymer joint filler mortar
Manufacturer:	Texas Cement Products, dba Texrite 4000 Pinemont, Houston, Texas 77018, USA 713-682-8411 www.texrite.com
	713-682-8411 (8am-3pm, CST, M-F) 713-688-2488

Classification of the chemical in accordance with paragraph (d) of 1910.1200;

Signal Word:	Danger
GHS Class:	Serious Eye Damage/Eye Irritation, Category 1, Skin Corrosion/Irritation, Category 2 Skin Sensitizer/Allergic skin reaction, Category 1 Carcinogen/May cause cancer if inhaled, Category 1A, May cause respiratory irritation, STOT SE3 Damage to organs through prolonged or repeated exposure if inhaled, STOT RE1
Hazard Statements:	H100s = General, H200s = Physical, H300s = Health, H400s = Environmental
	 H315 -Causes skin irritation. H317 -May cause an allergic skin reaction. H318 -Causes serious eye damage. H335 -May cause cancer if inhaled. H350A -May muse respiratory irritation. H372A - Causes damage to organs through prolonged or repealed exposure if inhaled.
Precautionary Statements:	 P201 -Obtain special instructions before use. P202 -Do not handle until all safety precautions have been read and understood. P260B -Do not breathe dust. P264.3 -Wash skin thoroughly after handling. P270 -Do not eat, drink or smoke when using this product. P271 -Use only outdoors or in a well-ventilated area. P272 -Contaminated work clothing should not be allowed out of the workplace P280B -Wear protective gloves and eye, face protection. P302+P3529, -IF ON SKIN. Wash with plenty of water P304+P340 -IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 -IF exposed or concerned: Gel medical advice / attention. P312A - Call a POISON CENTER if you feel unwell. P314 -Get medical advice/attention if you feel unwell.

P321A -Specific treatment (see supplementary instructions on this label) P333+P313 -If skin irritation or rash occurs: Get medical advice/attention. P363 - Wash contaminated clothing before reuse.

- P403+P233 -Store in a well-ventilated place. Keep container lightly dosed.
- P405 -Store locked up.
- P501A -Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Ingredients(s) with unknown acute toxicity: None

Hazards not otherwise classified identified during the classification process: None

Section 3 Composition Information and Ingredients

Mixture:

Component Name	CAS #	WT %	<u>Classification</u>
Portland Cement	65997-15-1	40-60%	STOT SE 3, H335: Eye Dam 1,H318 Skin Sens. 1, H317; Skin Irrit. 2, H315
Titanium dioxide	13463-67-7	0.1-5%,	Carc. 2, H351
Calcium sulfate	7778-18 -9	0.1-5%	STOT SE 3, H335:
Silica Sand	14808-60-7	0.1-5%	Carc. 1A, H350A, STOT RE 1, H372A

Section 4 First-Aid Measures

Emergency and First Aid Procedures

Inhalation:	Remove casualty to fresh air and keep at rest. If breathing is irregular or stopped, administer artificial respiration. In case of inhalation, consult a doctor immediately and show him packing or label.			
Eyes:	IF IN EYES: Rinse cautiously with water with the eyelids open for a sufficient length of time. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation continues, then get medical advice/attention immediately. Protect uninjured eye.			
Skin Contact:		IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.		
Ingestion:	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.			
Most Important sympton	Eye Irritation Eye damages Skin Irritation Erythema liate medical atte	ntion and special treatment needed: ent or unwellness, seek medical advice immediately (show directions for use or		
Section 5	Fire Fighting N	leasures		
Extinguishing Media: Fire Fighting Methods a	nd Protection:	Use carbon dioxide, or water spray when fighting fires involving this material. Firefighters should wear full protective equipment and NIOSH approved self- contained breathing apparatus.		
Fire and/or Explosion Hazards:		Do not inhale explosion and combustion gases. Burning produces heavy smoke.		
Hazardous Combustion Products:		N.A.		
Explosive properties:		N.A.		
Oxidizing properties:		N.A.		
Special protective equir	ment and preca	itions for fire-fighters		

Special protective equipment and precautions for fire-fighters:

Texrite Ac-cent Nonsanded Grout -SDS

Use suitable breathing apparatus. Collected contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

Section 6	Accidental	Release Measu	ires				
Steps to Take in Case Material Is Released or Spilled:		vapors/dus respiratory the contam Suitable ma	Wear personal protection equipment.Wear breathing apparatus if exposed to vapors/dusts/aerosols. Provide adequate ventilation. Use appropriate respiratory protection. See protective measures under section 7 and 8. Ventilate the contaminated area. Suitable material for taking up: absorbing material, organic, sand. Wash with plenty of water.				
Section 7	Handling a	nd Storage					
Handling: Storage:		Exercise th localized ve cleaned. Be incompatibl be changed also section handling. W protection.	entilation syste efore making t le material res d before enteri n 8 for recomn /ear protective Keep containe	e when hand em. Don't use ransfer oper iduals in the ng eating are hended prote gloves/prot	Iling or oper e empty con ations, assu containers. eas. Do not ective equip ective clothi	ning the c tainer be re that th Contami eat or dri ment. Wa ng/eye p	ontainer. Use fore they have been ere aren't any nated clothing should nk while working. See ish thoroughly after rotection/face
Storage Code	:	N.A.					
Section 8 List of compon	Exposure C ents with OEL value	ontrols / Perso	onal Protecti	on			
<u>Component</u>	OEL Type Country Ceiling	Long Term <u>mg/m3</u>	Long Term ppm	Short Term <u>mg/m3</u>	Short Term ppm	<u>Behavior</u>	Note
Portland cement	OSHA OSHA ACGIH	15 5.0 1					A4- Not classifiable as a Human Carcinogen; pulmonary function: respiratory symptoms;
Titanium dioxide	OSHA	15					asthma A4- Not classifiable as a Human Carcinogen;
	ACGIH	10					lower tract irritation
Calcium sulfate	OSHA OSHA ACGIH	15 5 10					nasal symptoms
Silica Sand	ACGIH	0.025					A2-SupsectedHuman Carcinogen; lung cancer; pulmonary fibrosis
Control Param Engineering M Personal Prote			al conditions		generating	airborne	erator comfort dust

No respiratory protection required under normal conditions of use. Use NIOSH approved air purifying respirator with dust filter. Wear close fitting safety glasses or goggles when handling this product.

Respiratory Protection: Respirator Type(s):

Eye Protection:

Skin Protection:

Gloves:

Avoid skin contact by wearing clothing that provides comprehensive protection. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. PVC, neoprene, rubber, nitrile

Section 9 **Physical and Chemical Properties**

Appearance:	Powder, various- solid color
Odor:	Cement likes
Odor Threshold:	None
pH (Neutrality):	N.A.
Melting Point/Freezing Point:	N.A.
Boiling Range (Ibp,50%,Dry Point):	N.A.
Flash Point (Test Method):	N.A.
Evaporation Rate	
(n-Butyl Acetate=1):	N.A.
Flammability Classification:	N.A.
Lower Flammable	
Limit in Air (% by vol):	N.A.
Upper Flammable	
Limit in Air (% by vol):	N.A.
Vapor Pressure (mm of Hg)@20 C:	N.A.
VAPOR DENSITY (Air=1):	N.A.
GRAVITY @ 68/68F / 20/20C:	
Specific Gravity (Water=1):	N.A.
Pounds/Gallon:	N.A.
Water Solubility:	Dispersible
Partition Coefficient (n-Octane/Water):	N.A.
Auto Ignition Temperature:	N.A.
Decomposition Temperature:	N.A.
Other Information	
Substance Groups relevant properties	N.A.
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
-	

Section 10

Stability and Reactivity

Reactivity: Chemical Stability: Possibility of Hazardous Reaction: Conditions to Avoid: Incompatible Materials: Hazardous Decomposition Products: Stable under normal conditions. No data available None Stable under normal conditions. None in particular None

Section 11

Toxicological Information Toxicological Information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentrations of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological Information on the main components of the mixture:

Silica Sand	a) acute toxicity	LD50 (Oral): =500 mg/kg (Rat)
Titanium dioxide	a) acute toxicity	LD50 (Oral):>10000 mg/kg (Rat)
Calcium sulfate	 a) acute toxicity 	LD50 (Oral): >3000 mg/kg (Rat)

If not differently specified, the information required in the regulation and listed below must be considered NA. a) acute toxicity

b) skin corrosion/irritation

	 c) serious eye damage/irri d) respiratory or skin sensi e) germ cell mutagenicity f) carcinogenicity g),reproductive toxicity h) STOT - single exposure I) STOT -repeated exposure J) aspiration hazard 	itization
Substance(s) listed on the	IARC Monographs: Silica Sand Titanium Dioxide	Group 1 Group 2B
Substance(s) listed as OS		
Substance(s) listed as NIC	OSH Carcinogen(s): Silica Sand Titanium Dioxide	
Substance(s) listed on the	NTP report on Carcinogen Silica Sand	S:

Section 12 Ecol

Ecological Information

Overview: Adopt good working practices, so that the product is not released Into the environment.

Ecotoxicity:

QTY , Chemical Name	CAS Numb	r Eco Toxicity
0.1-5 %, Calcium sulfate	7778-18 -9	LC 50 a) Aquatic acute toxicity Fish Lepomis macrochirus =2980mg/L 96h EPA LC 50 a) Aquatic acute toxicity Fish Pimephales promelas > 1970mg/L 96h EPA
0.1-5 %, Silica Sand	14808-60-7	LC 50 a) Aquatic acute toxicity carp >10000.00000 mg/L 72h
Persistence and degrad Bioaccumulative potent Mobility in soil: Other Adverse Effects:	ial: No No	polymeric component is not expected to biodegrade. data data data

Section 13 Disposal Considerations

Disposal Methods:

Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance. Not Determined

Waste Disposal Code(s):

Section 14 Transport Information

UN number ADR-UN number: N/A DOT-UN number: N/A IATA-UN number: N/A IMDG-UN number: N/A UN proper shipping name ADR-Shipping Name: N/A DOT Proper Shipping Name: N/A IATA-Technical name: N/A IMDG-Technical name: N/A Transport hazard class(es) ADR- Class: N/A DOT Hazard Class: N/A

Texrite Ac-cent Nonsanded Grout -SDS

IATA- Class:	N/A
IMDG-Class:	N/A
Packing qroup	
ADR Packing Group:	N/A
DOT-PackIng group:	N/A
IATA-Packing group:	N/A
IMDG-Packing group:	N/A
Environmental hazards	
Marine pollutant:	No
Environmental Pollutant:	N.A.
Transport in bulk according to Annex II of M/	ARPOL73/78 and the IBC code:
	N.A.
Special Precautions	
Department of Transportation (DOT):	
DOT-Special Provision(s):	N/A
DOT Label(s):	N/A
DOT Symbol:	N/A
DOT Cargo Aircraft:	N/A
DOT Passenger Aircraft:	N/A
DOT Bulk:	N/A
DOT Non-Bulk:	N/A
Road and Rail (ADR-RID):	
ADR-Label:	N/A
ADR Hazard identification number:	
ADR Tunnel Restriction Code:	N/A
Air (IATA) :	
IATA- Passenger Aircraft:	N/A
IATA- Cargo Aircraft :	N/A
IATA- Label:	N/A
IATA- Subrisk:	N/A
IATA- Erg:	N/A
IATA- Special Provisions:	N/A
Sea (IMDG):	
IMDG -Stowage Code:	N/A
IMDG -Stowage Note:	N/A
IMDG -Subrisk:	N/A
IMDG -Special Provisions:	N/A
IMDG -Page:	N/A
IMDG -Label:	N/A
IMDG -EMIS:	N/A
IMDG -MFAG:	N/A

Section 15

Regulatory Information

USA - Federal regulations

TSCA • Toxic Substances Control Act TSCA Inventory:

All the components are fisted on the TSCA inventory


TSCA listed substances:

SARA - Superfund Amendments and Reauthorization Act Section 302 – Extremely Hazardous Substances: no substance listed

Section 304 – Hazardous substances:	no substance listed
Section 313 – Toxic chemical list:	no substance listed

CERCLA – Comprehensive Environme Substance(s) listed under CERCLA:	ntal Response, Compensations, and Liability Act no substance listed
CAA – Clean Air Act CAA Substances listed:	no substance listed
CWA – Clean Water Act CWA Substances listed:	no substance listed
USA - state specific regulations	
California Proposition 65 Substance(s) listed under California Pro Titanium Dioxide Silica Sand	oposition 65 listed as carcinogen listed as carcinogen
Massachusetts right to know Substance(s) listed under Massachuse Portland cement Titanium dioxide Calcium sulfate Silica Sand	tts Right to Know;
Pennsylvania Right to know Substance(s) listed under Pennsylvania Portland cement Titanium dioxide Calcium sulfate Silica Sand	a Right to Know;
New Jersey Right to know Substance(s) listed under New Jersey Portland cement Titanium dioxide Calcium sulfate Silica Sand	Right to Know;
Section 16 Other Info	rmation

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.



Texrite Ac-cent Nonsanded Grout -SDS

NFPA Special Risk: NONE

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Cause serious eye damage.
H335	May cause respiratory irritation.
H350A	May cause cancer if inhaled
H372A	Causes damage to organs through prolonged or repeated exposure if inhaled

The information provided in this (Material) Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Texrite makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the (Material) Safety Data Sheet.

Glossary

0.0000	.,
ACGIH	-American Conference of Governmental
	Industrial Hygienists
CAS	-Chemical Abstract Service Number
CERCL	A -Comprehensive Environmental Response,
	Compensation, and Liability Act
DOT	-U.S. Department of Transportation
IARC	-International Agency for Research on
	Cancer

- N/A -Not Available
- NTP -National Toxicology Program

- OSHA -Occupational Safety and Health Administration
- PEL -Permissible Exposure Limit
- ppm -Parts per million
- RCRA -Resource Conservation and Recovery Act
- SARA -Superfund Amendments and Reauthorization
- TLV -Threshold Limit Value
- TSCA -Toxic Substances Control Act
- IDLH -Immediately dangerous to life and health