

PRODUCT SPECIFICATIONS

PROJECT:	
MODEL #: LAMP(S):	
NOTES:	

Available Models


300DB (300W, direct burial) 360DB (360W, direct burial) 500DB (500W, direct burial) 600DB (600W, direct burial) 840DB (840W, direct burial) 1120DB (1120W, direct burial)


MODEL WATTAGE

310 = 12V-13V Output Leads 360 = 12V-15V Output Leads 500 = 12V-17V Output Leads 600 = 12V-17V Output Leads 840 = 12V-20V Output Leads 1120 = 12V-22V Output Leads 1500 = 12V-22V Output Leads 1838 = 12V-22V Output Leads

	120v		
Output Output	Max Fuse		
Wattage Leads	Amps Size		
310 (12-13v)	2.58 3.00		
360 (12-15v)	3.00 4.00		
500 (12-17v)	4.16 5.00		
600 (12-17v)	5.00 6.00		
840 (12-20v)	7.00 8.00		
1120 (12-22v)	9.33 10.00		
1500 (12-22v)	12.50 13.00		
1838 (12-22v)	15.31 16.00		

1/2-14 NPSM threaded hole for mounting fixture





Name plate molded into lid of unit.

TRANSFORMER #	PANEL#	CURCUIT#
1	1	13

Specifications:

Core

Engineered single core design with precision grain-oriented steel laminations. High temperature glass impregnated nylon bobbin and solid copper mag wire. To ensure robust construction each output tap is welded to the mag wire for optimum connectivity.

Construction

Durable UV resistant composite box. Suitable for directburial. Agency approval as "SUITABLE FOR GROUNDMOUNTED RECESSED."

Primary Protection

Replacable 3AG Time Delay (glass slow-blow fuse).

Power

Unit must be hardwired

Electrical Requirements

Available power ratings 310, 360, 500, 600, 840, 1120,1500 and 1838 Watts. Primary voltage is 120 volts, secondary voltage varies from 12V-22V output. Seeindividual models for exact output leads.

Output Terminal

Each DB includes ready to wire color coded 10 gauge output wire lead.

Finish

Black UV resistant composite box standard.

Warranty

Limited lifetime warranty against manufacturer's defects.



UL 2108: 2004 R4.11 CAN/CSA-C22.2 No. 250.0-08

Unique Lighting Systems® reserves the right to modify the design and/or construction of the fixture shown without further notification