## Section 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:

BLUE JAY PIGMENT BLEND

VERSION DATE:

May 1, 2015

CAS NUMBER:

N/A-PROPRIETARY MIXTURE

### Section 2. COMPOSITION

## NON-HAZARDOUS PIGMENT PREPARATION

### Section 3. HAZARDS IDENTIFICATION

### Potential Health Effects

Inhalation: May cause irritation.

Ingestion: May cause gastrointestinal irritation.

Skin Contact: May causes skin irritation if in contact for extended periods of time.

Eye Contact: May cause corneal injury or blindness. Absorption can occur through eye tissues but the more

common hazards are local irritation or abrasion.

Chronic Exposure: Prolonged exposure may cause dermatitis and/or bronchitis

Aggravation of Pre-existing Conditions: None known

## Section 4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact: Immediately flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyè Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

### Section 5. FIRE FIGHTING MEASURES

Fire: Not considered to be a fire hazard.

Explosion: Not considered to be an explosion hazard. Sealed containers may rupture when heated.

### Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire. Do not allow water runoff to enter sewers or waterways. Carbon dioxide, water spray or foam are all suitable.

### **Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

## Section 6. ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

### Section 7. HANDLING AND STORAGE

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Wear special protective equipment (Sec. 8) for maintenance break-in or where exposures may exceed established exposure levels. Wash hands, face, forearms and neck when exiting restricted areas. Shower and change clothing. Clean garments at the end of the day. Avoid cross-contamination of street clothes. Wash hands before eating and do not eat, drink, or smoke in workplace. Observe all warnings and precautions listed for the product.

### Section 8. EXPOSURE CONTROLS

### For Nuisance dust:

- ACGIH Threshold Limit Value (TLV):
- 0.5 mg/m3 TWA
- OSHA Permissable Exposure Limit (PEL):

As Nuisance dust: 0.5 mg/m3 TWA

**Ventilation System:** A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

## Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, a half-face high efficiency dust/mist respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece high efficiency dust/mist respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres. For further information regarding respirators, see OSHA 20 CFR 1910.134

#### Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. For further information, see OSHA 29 CFR 1910.1025.

### **Eye Protection:**

Use chemical safety goggles and/or full-face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

## **Other Control Measures:**

Eating, drinking, and smoking should not be permitted in areas where solids or liquids containing lead compounds are handled, processed, or stored. See OSHA substance-specific standard for more information on personal protective equipment, engineering and work practice controls, medical surveillance, record keeping, and reporting requirements. (29 CFR 1910.1025).

| Se                              | ction 9. PHYSICAL AN   | D CHEMICAL PROPERTIES   |                |  |
|---------------------------------|--|---|----------------|--|
| Appearance:                     | Blue, Black, Brownish, or Bluish-Black Powder  |   |                |  |
| Odor:                           | Odorless   | Odorless  |                |  |
| Solubility:                     | Insoluble  |   |                |  |
| Specific Gravity:               |  | 2.35-2.60   |                |  |
| pH:                             |  | NA  |                |  |
| % Volatiles by volume @ 21C (70 |  | NA  |                |  |
| Boiling Point:                  | A CONTRACTOR OF THE PARTY OF TH | NA  |                |  |
| Melting Point:                  |  | NA  |                |  |
| Vapor Density (Air=1):          |  | No information found.   |                |  |
| Vapor Pressure (mm Hg):         |  | No information found.   |                |  |
| Evaporation Rate (BuAc=1):      |  | No information found.   |                |  |
|                                 |  | TY AND REACTIVITY   |                |  |
| Stability:                      | Stable und   | Stable under ordinary conditions of use and storage.            |                |  |
| Hazardous Decomposition Produc  | ts: Thermal d  | Thermal decomposition may produce oxides of carbon and nitrogen |                |  |
| Hazardous Polymerization:       | Will not o   |   | *              |  |
| Incompatibilities:              |  | Strong oxidizing agents and strong acids.                       |                |  |
| Conditions to Avoid:            | Incompatil   | Incompatibles.  |                |  |
|                                 |  | GICAL INFORMATION   |                |  |
| Toxicological Data:             |  |   |                |  |
| Reproductive Toxicity:          |  |   |                |  |
| Cancer Lists                    |  |   |                |  |
| Ingredient                      | NTP Carcinogen   |   |                |  |
|                                 | Known  | Anticipated   | IARC Category  |  |
| None                            |  |   | IAINC Calegory |  |

None

### Section 12. ECOLOGICAL INFORMATION

#### **Environmental Fate:**

When released into the soil, this material may leach into groundwater. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

**Environmental Toxicity:** No information found.

### Section 13. DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. (See 40 CFR Part 262). Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

### Section 14. TRANSPORTATION INFORMATION

Domestic (Land, D.O.T.)

Proper Shipping Name:

Not regulated

Hazard Class:

UN/NA: Information reported for product/size:

Packing Group:

International (Water, I.M.O.)

Proper Shipping Name:

Not regulated

Hazard Class:

UN/NA:

Packing Group:

Information reported for product/size:

International (Air, I.C.A.O.)

Proper Shipping Name:

Hazard Class:

UN/NA:

Packing Group:

Information reported for product/size:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

#### Section 15. OTHER

**NFPA Ratings:** 

PIGMENT PAKS MSDS

Health: 1 Flammability: 0 Reactivity: 0

## **Label Hazard Warning:**

**Label Precautions:** Do not get in eyes, on skin, or on clothing. Do not breathe dust. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Label First Aid: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. In all cases get medical attention immediately.

## DISCLAIMER OF LIABILITY

Universal White Cement provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

UNIVERSAL WHITE CEMENT AND RELATED ENTITIES MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, UNIVERSAL WHITE CEMENT WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.