

## CERTI-VEX® NON-SLIP ADDITIVE

### DESCRIPTION

**CERTI-VEX NON-SLIP ADDITIVE** is a highly pure particle size controlled sand for addition to Vexcon epoxy and urethane coatings for increased slip resistance and fine texturing. Certi-Vex Non-Slip Additive has low oil absorption and high solvent resistance and will stir easily into the coatings with little effect on the coating viscosity.

### BENEFITS

- Good compatibility with minimal viscosity effects.
- Can be added to water or solvent based system.
- Recommended for PowerCoat High Performance Coatings.
- Slip resistance.
- Good chemical and abrasion resistance.

### APPLICATION

- **Method 1**  
Add contents of can to PowerCoat High Performance Coatings after mixing A & B. Keep suspended by mixing during application.
- **Method 2**  
Sprinkle over 1<sup>st</sup> coat of PowerCoat High Performance Coatings after it has tacked up. Leave on overnight. Vacuum or blow off excess. Apply a second coat Certi-Vex.

### WARNING

1. Certi-Vex Non-Slip Additive will increase the coefficient of friction on the surface of a paint. The coating that this is added to will have a texture and surface changes from a smooth coating.
2. Not for use with wood stains or wood sealers.
3. Do not add to penetrating water repellants.
4. For use by Professional Applicators only.
5. Keep out of reach of children.
6. Use **Certi-Vex® Grip for PowerCoat® Epoxy LD**

### THIS PRODUCT INCLUDES

- Certi-Vex Non-Slip Additive is packed 7 lb. by weight in a container.

### VITAL STATISTICS

- Controlled particle size slip resistant additive.

### HEALTH AND SAFETY

- Certi-Vex Non-Slip Additive contains silica, but should be treated as a nuisance dust while incorporating it into its intended coating – use dust mask.
- It is recommended that when mixing into unfamiliar coatings, a small test batch and application be made.
- Use only with adequate ventilation.
- Use of gloves, goggles and other protective clothing is advised when using this product.
- If swallowed, do not induce vomiting.  
Vexcon SDSOP130 is an integral part of the safety and application of our product. A short synopsis is provided in this product data sheet. Before using this Vexcon product, it is advisable to obtain a copy of the SDS from your distributor or by contacting Vexcon Chemicals directly.
- **FOR USE BY PROFESSIONAL APPLICATORS ONLY.**
- Proper application of Vexcon material is the responsibility of the installer or user. Telephone consultation and/or field visits by Vexcon personnel are for the sole purpose of making technical recommendations only, and not for providing quality control or supervision on location.

### THIS PRODUCT INCLUDES

MATERIAL OR COMPONENTS	CAS NO.	%	OSHA PEL:	ACGIH TLV
SILICA SAND*	14808-60-7	100	0.1 mg/m3	0.1 mg/m3

\*CONTINUED INHALATION OF DUST OVER A PERIOD OF YEARS WITHOUT PROPER RESPIRATOR AND VENTILATION CONTROLS WILL CAUSE SILICOSIS AND LUNG CANCER. CURRENT OSHA STANDARD FOR CRYSTALLINE SILICA (RESPIRABLE DUST) IS 10mg SILICA PER CUBIC METER OF AIR DIVIDED BY THE PERCENT SiO<sub>2</sub> AVERAGED OVER AN EIGHT HOUR WORK SHIFT AND FOR TOTAL DUST IS 30mg/m<sup>3</sup> DIVIDED BY THE PERCENT SiO<sub>2</sub> AVERAGED OVER AN EIGHT HOUR WORK SHIFT.

### CONTACT US @

Additional product information, technical assistance and customer service is available by contacting Vexcon Chemicals directly or our distributors.

- [vexcon.com](http://vexcon.com)
- [techservice@vexcon.com](mailto:techservice@vexcon.com)
- [customerservice@vexcon.com](mailto:customerservice@vexcon.com)
- [sales@vexcon.com](mailto:sales@vexcon.com)
- Voice: 888.839.2661
- Fax: 215.332.9997

#### WARRANTY

LIMITED WARRANTY: Vexcon warrants for a period of one (1) year from the date of manufacture that the goods supplied hereunder shall be of its standard quality and free of defects, and conforms to (a) Vexcon's published specifications in force on the date of acceptance by Vexcon of the order and (b) the sample which has been made available for testing by buyer prior to sale. Any claim under this warranty must be made in writing to Vexcon Chemicals within sixty (60) days after such non-conformity is first discovered. As the EXCLUSIVE REMEDY for any breach of this Limited Warranty, Vexcon at its option shall replace nonconforming goods or refund the purchase price. Since methods of use and application are beyond Vexcon's control, this Limited Warranty IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THOSE CONCERNING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY IS ALSO IN LIEU OF ANY OTHER POSSIBLE LIABILITIES OF VEXCON, WHETHER ALLEGED TO ARISE BY AGREEMENT OR BY OPERATION OF LAW, RESPECTING THE SALE, APPLICATION, USE OR FUNCTION OF VEXCON'S PRODUCTS, INCLUDING BUT NOT LIMITED TO CLAIMS OF NEGLIGENCE, GROSS NEGLIGENCE, MISUSE, STORAGE DAMAGE, MISAPPLICATION, ACCIDENT, STRICT LIABILITY OR ANY OTHER TORT. No person is authorized by Vexcon to assume for it any other liability of any kind in connection with the sale or use of products manufactured and sold by it, and there are no oral agreements or warranties collateral to or affecting any sale or use. All of the foregoing arises under the substantive law of Pennsylvania without regard to principles of conflicts of laws.

LIMITATION OF LIABILITY: IN ALL EVENTS VEXCONS LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF PURCHASED PRODUCTS. IN NO EVENT SHALL VEXCON BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE, REAL OR PERSONAL, ATTRIBUTED TO ITS PRODUCTS, NOR FOR ANY EXCAVATION, REMOVAL, REAPPLICATION, DOWN TIMES, CLEANUP, LOSS OF USE, LOSS OF OPPORTUNITY, LOSS OF MARKET VALUE, LOSS OF RENTAL VALUE OR FOR ANY LOSS OF PROFITS OR OTHER SPECIAL, INCIDENTAL, RESULTING, CONSEQUENTIAL OR EXEMPLARY DAMAGES.