



VEXCON
CHEMICALS, INC.

Concrete solutions for architects, engineers and builders since 1974
888-839-2661 | sales@vexcon.com | 7240 State Road | Philadelphia, PA 19135 **vexcon.com**

HAZARD RATING
4=EXTREME
3=HIGH
2=MODERATE
1=SLIGHT
0=INSIGNIFICANT

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

SAFETY DATA SHEET
VEXCON NO. CS132

CERTI-VEX AC 1315 SUPER SEAL HG

SECTION I - GENERAL INFORMATION

PRODUCT IDENTIFICATION:	
CERTI-VEX AC1315 SUPER SEAL HG	
VOC CONTENT: <350 GRAMS/LITER OR <2.91#/GAL	
CATEGORY: CONCRETE CURE	
COMMON NAME: STYRENE ACRYLATE COPOLYMER IN AROMATIC/ EXEMPT SOLVENT	
MANUFACTURER: VEXCON CHEMICALS, INC.	
ADDRESS: 7240 STATE RD., PHILA., PA 19135 USA	
EMERGENCY NO: 1-800-858-2828	
TELEPHONE NO: 1-215-332-7709	
CHEMTREC NO: 1-800-424-9300	
PREPARED: SEPTEMBER 2008	
UPDATED: NOVEMBER 2019	
PREPARED BY: DARRYL F. MANUEL, PRESIDENT	

SECTION II - HAZARD IDENTIFICATION

CLASSIFICATION OF MIXTURE

FLAMMABLE LIQUIDS - CATEGORY 2
ACUTE TOXICITY; INHALATION - CATEGORY 4
SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY - SINGLE EXPOSURE - CATEGORY 3
ACUTE AQUATIC TOXICITY - CATEGORY 3

SINGLE WORD: DANGER

HAZARD STATEMENT: HIGHLY FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. HARMFUL TO AQUATIC LIFE.



PRECAUTIONARY STATEMENT FLAMMABLE LIQUID: KEEP AWAY FOR HEAT/SPARKS/ OPEN FLAMES/HOT SURFACES- NO SMOKING. USE ONLY WITH ADEQUATE VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING; USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT: ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL: USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT IN CONFINED AREA.



SECTION III HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA
STYRENE ACRYLATE POLYMER	25036-16-2	20-35 %	ND
TERT BUTYL ACETATE	540-88-5	20-70 %	OSHA HAZARD: FLAMMABLE LIQUID OSHA PEL: 200 ppm ACGIH TLV: 200 ppm
ACETONE	67-64-1	20-35 %	OSHA PEL: 1000 ppm ACGIH TLV: 500 ppm NIOSH REL: 250 ppm

SOLVENT NAPHTHA (Petroleum), AROMATIC	64742-95-6	5-20 %	TLV 50 PPM OSHA HAZARD: COMBUSTIBLE
WHICH CONTAINS			
PETROLEUM HYDROCARBONS	8052-41-3	40-66%	OSHA PEL: 2900 mg/m3 ACGIH TLV: 525 mg/m3 OR 100 ppm
TRIMETHYL BENZENE	95-63-6	10%	OSHA PEL: NE ACGIH TLV: 25 ppm
THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:			
COMPONENT	CAS NO.	MAX %	
TRIMETHYL BENZENE	95-63-6	1.5%	OSHA PEL: NE ACGIH TLV: 25ppm

SECTION IV FIRST AID MEASURES

HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE

ROUTES OF EXPOSURE:

INHALATION:	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. ACETONE COMPONENT, TERTIARY BUUTYL ACETATE COMPONENT, AROMATIC NAPHTHA COMPONENT.
SKIN CONTACT:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. ACETONE COMPONENT, TERTIARY BUUTYL ACETATE COMPONENT, AROMATIC NAPHTHA COMPONENT.
SKIN ABSORPTION:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. ACETONE COMPONENT, TERTIARY BUUTYL ACETATE COMPONENT, AROMATIC NAPHTHA COMPONENT.
EYE CONTACT:	THIS PRODUCT MAY BE AN EYE IRRITANT.
INGESTION / INHALATION	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING SEEK IMMEDIATE MEDICAL ATTENTION.
EFFECTS OF OVEREXPOSURE:	TLV 50 ppm ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
ACUTE OVEREXPOSURE:	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEBAT THE SKIN POSSIBLY CAUSING DERMATITIS.

EMERGENCY AND FIRST AID PROCEDURES:

EYES:	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
SKIN:	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
INHALATION:	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
INGESTION:	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

SECTION V FIREFIGHTING MEASURES

EXTINGUISHING MEDIA:	FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY.
GENERAL HAZARD:	FLAMMABLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
ELECTRO-STATIC ACCUMULATION HAZARD:	USE PROPER GROUNDING
UNUSUAL FIRE AND EXPLOSION HAZARD:	THIS PRODUCT IS EXTREMELY FLAMMABLE AND EXPLOSIVE UNDER NORMAL CONDITIONS IN THE PRESENCE OF FLAME OR SPARK SOURCE. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT. VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.
SPECIAL FIRE FIGHTING PROCEDURES:	THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP.

SECTION VI ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

WATER SPILL: REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

SECTION VII HANDLING AND STORAGE

PRECAUTIONARY STATEMENTS: WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED/DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.

OTHER HANDLING AND STORAGE REQUIREMENTS: KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.

RESPIRATORY (SPECIFY IN DETAIL): THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE: FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.

EYE: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.

GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.

OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: (760mmHg) 133°F / 56.5°C	MELTING POINT: N/A
VAPOR PRESSURE: (acetone) 400 mmHg@104°F/39.5°C	VAPOR DENSITY (AIR=1): 2.0
SOLUBILITY IN H2O % BY WT: 0.5%	% VOLATILES BY VOL: 70-80%
EVAPORATION RATE (BuAc=1): 2.8	SPECIFIC GRAVITY (H2O=1) 0.885
pH (AS IS) N/A	pH (1% SOLN) N/A
APPEARANCE AND ODOR:	CLEAR LIQUID WITH SWEET SOLVENT ODOR
FLASH POINT: (TEST METHOD)	-20°C / -4°F (TCC) acetone
AUTOIGNITION TEMP:	465°C / 869°F
FLAMMABLE LIMITS IN AIR, % BY VOL:	LOWER: 2.5% UPPER: 12.8%

SECTION X STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY:	THIS PRODUCT IS STABLE.
INCOMPATIBILITY:	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
HAZARDOUS DECOMPOSITION PRODUCTS:	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:	N/A WILL NOT OCCUR

SECTION XI TOXICOLOGICAL INFORMATION

<u>ACUTE TOXICITY</u>	LC50 (VAPOR)	RAT	4211 ppm	6 HOURS
	LD50 (ORAL)	RAT	4500 MG/KG BWT	
	LD50	RABBIT	>2000 ,G/KG BWT	
<u>ACUTE EFFECTS</u>	INHALATION		VAPORS OR AEROSOL MAY CAUSE IRRITATION OF THE EYES, NOSE AND THROAT AS WELL AS CNS DEPRESSION (FATIGUE, DIZZINES, LOSS OF CONCENTRATION, WITH COLLAPSE, COMA AND DEATH POSSIBLE IN CASES OF SEVERE OVER EXPOSURE), INHALATION OF AIRBORNE DROPLETS MAY CAUSE IRRITATIONS OF THE RESPIRATORY TRACT.	
	INGESTION		MAY CAUSE CNS DEPRSSION, GASTRIC DSCOMFORT, AND VOMITING. THIS MATERIAL IS AN ASPIRATION HAZARD.	
	SKIN CONTACT		NO SYSTEMIC TOXICITY IS EXPECTED FROM ACUTE DERMAL EXPOSURE	
<u>IRRITATION</u>	SKIN		NOT A SKIN IRRITANT	
	EYES		NO EYE IRRITATION	
<u>SENSITIZATION</u>	DOES NOT INDUCE SKIN SENSITIZATION.			
<u>REPEATED DOES TOXICITY</u>	INHALATION REPEATED EXPOSURE STUDIES DEMONSTRATED TARGET ORGAN EFFECTS IN MALE RATS (KINDEY) BY MECHANISM OF ACTION THAT IS NOT RELEVANT TO HUMAS NAD IN MICE (NERVOUS SYTEM) TRANSIENT BEHAVIOR CHANGES THAT WERE OBSERVED IMMEDIATELY AFTER EXPOSURE.			
<u>REPRODUCTIVE EFFEXTE</u>	THIS SUBSTANCE IS NOT TOXIT TO REPRODUCTION. THE REPRODUCTIVE TOXICITY OF T-BUTYL ACETATE HAS BEEN INVESTAGATED IN RATS VIA A INHALATION ROUTE. THERE WERE NO ADVERSE EFFECTS ON REPRODUCTIVE PERFORMANCE OR SPERM NUMVER OR UALITY AT 1600 ppm, THE HIGHEST EXPOSURE LEVEL TESTED. IN ADDITION, NO GROSS OR HISTOPATHOLOGIC EFFECTS WERE OBSERVED IN THE REPRODUCTIVE ORGANS OF MALE AND FEMALE RATS OR MICE EXPOSED AT 1600 ppm FOR 90 DAYS IN A REPEATED EXPOSURE TOXICITY STUDY CONDUCTED VIA INHALATION AND THERE WAS NO ADVERSE EFFECTS ON ESTROUS CYCLE LENGTH IN MICE.			
<u>DEVELOPMENTAL TOXICITY</u>	THIS SUBSTANCE IS NOT A DEVELOPMENTAL TOXICANT. IT DID NOT CAUSE MATERNAL TOXICITY AND NO EMBRO/FETAL TOXICITY OR DEVELOPMENTA ABNORMALITIES WERE OBSERVED IN THE OFF SPRINF OF ANIMALS FOLLOWING INHALATION EXPOSURES OF 1600 ppm.			
<u>GENETIS TOXICITY</u>	NEGATIVE FOR GENOTOXICITY USING BOTH IN VITRO AND IN VIVO TEST.			
<u>GARCINOGENICITY</u>	SPECIFIC DATA NOT AVAILABLE. T-BUTANOL, THE PRIMARY METABOLITE OF T-BUTYL ACETATE IS AN ANAMAL CARCINOGEN. IN DRINKING WATER STUDY, T-BUTANOL INDUCED BEGINN KIDNEY TUMORS IN MALE RATS VIA AN a-2u-GLOBULIN MODE OF ACTION, A TUMOR MECHANISM NOT RELEVANT TO HUMANS. IN FEMAL MICE, THERE WAS AN INCREASE INCIDENCE OF BEGINN THYROID TUMORS, A TUMOR MECHANISM THAT MOST LIKELY IS NOT RELEVANT TO HUMAND. THIS SUBSTANCE IS NOT CLASSIFIED FOR CARCINOGENICITY BY IARC, OSHA, NTP OR THE EPA.			

SECTION XII ECOLOGICAL INFORMATION

<u>ECOTOXICITY</u>	ACUTE FISH TOXICITY	LC50/96 HOURS	ONCORH YNCHUS MYKISS 240 mg/l	ACUTE TOSICITY TO FISH IS LOW
	ACUTE TOXICITY TO AQUATIC INVERTEBRATES	EC50/48 HOURS	DAPHNIA MAGNE 350 mg/l	LOW ACUTE TOXICITY TO AQUATIC INVERTEBRATE S.
	TOXICITY TO AQUATIC PLANTS	EC/5096 HOURS	PSEUDO KIRCHNE RIELLA SUBCAPI TATA 60 mg/l	LOW TOXICITY TO ALGAE
	TOXICITY TO MICROORGA NISMS	EC3/16 HOURS	PSEUDO MONAS PUTIDA 78 mg/l	LOW TOXICITY TO BACTERIA
		EC3/72 HOURS	ENTOSPI HON SULCATU M 970 mg/l	
	CHRONIC TOXICITY TO FISH	NO DATA AVAILABLE		
	CHRONIC TOXICITY TO AQUATIC INVERTEBRATES	NON DATA AVAILABLE		
OTHER ADVRSE EFFECTS	EXPECTED TO SHOW LOW TOXICITY TO HIGHER PLANTS			
<u>ENVIRONMEN TAL FATE AND PATHWAYS</u>	EXPECTED TO BE EMMITTED AND PARTITION PREDOMINANTLY TO THE ATMOSPHERE. ACCIDENTIAL RELEASES TO WATER OR SOIL ARE EXPECTED TO EVAPORATED AND UNDERGO ATMOSPHERIC DECOMPOSITION PROCESSES.			
	MOBILITY	BEHAVIOR IN ENVIRONMENTAL COMPARTMENTS; RELEASED MATERIAL WOULD BE EXPECTED TO SHOW HIGH SOIL MOBILITY AND TO VOLATILIZE READILY FORM SOIL NAD SURFACE WATERS, FORMING ATMOSPHERIC VAPOR.		
	PERSISTENCE AND DEGRADABILITY	BIODEGRADATION: EXPECTED TO HYDROLYZE SLOWLY IN WATER (HALF-LIFE CA 0.5 YEARS OR LONGER). ATMOSPHERIC VAPORS EXPECTED TO BE PHOTOCHEMICALLY DEGRADED BY REACTION WITH HYDROXYL RADICALS (HALS LIKE 19.7 DAYS). INHERENTLY BIODEGRADABLE.		
		BIOACCUMULATION: BIOCONCENTRATION FACTOR (BCF) 5.61 (QSAR CALCULATED VALUE) THIS MATERIAL IS NOT EXPECTED TO BIOACCUMULATE.		
	OTHE ADVERSE EFFECTS	THIS MATERIAL IS NOT CONSIDERED PERSISTENT BY EPA, AND IS NOT EXPECED TO CONTRIBUTE TO THE GREENHOUSE GAS EFFECT, STRATOSPHERIC OZONE DEPLETION. TROPOSPHERIC OZONE FORMATION, OR PARTICULATE MATTER FORMATION.		

SECTION XIII DISPOSAL CONSIDERATIONS

AQUATIC TOXICITY (E.G. 96 HR. TLM): DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).

WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

SECTION XIV TRANSPORTATION INFORMATION

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group	Quantity Limitation
DOT	GROUND	1866	RESIN SOLUTION	3	II	ORMD – Max 30Kg gross wt (66lbs)
IATA	AIR	1866	RESIN SOLUTION	3	II	Passenger Aircraft - 5L Cargo Aircraft - 60L
IMDG	OCEAN	1866	RESIN SOLUTION	3	II	
MARINE POLLUTANT:		THIS PRODUCT DOES CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B) AROMATIC 100				

SECTION XV REGULATORY INFORMATION

<p>TSCA: THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6 (aromatic 100). 540-88-5 (tertiary butyl acetate).</p> <p>CERCLA: IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675.</p> <p>THE REPORTABLE SPILL QUANTITY (RQ) OF THIS PRODUCT IS 5,000 POUNDS (ACETONE, BUTYL ACETATE).</p> <p>SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: DELAYED HEALTH, FIRE</p> <p>ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER) FEDERAL / FDA / USDA:</p> <p>MARINE POLLUTANTS: THIS PRODUCT DOES CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B).SEE SECTION XIV</p> <p>CALIFORNIA PROP 65: WARNING: This product contains chemicals known to the state of California to cause cancer or birth defects or other reproductive harm. (Epichlorohydrin, Ethylbenzene, Crystalline Silica particles of respirable size)</p> <p>CERCLA / RQ: 5000 POUNDS (ACETONE, BUTYL ACETATE)</p> <p>THIS PRODUCT CONTAINS A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A): ACETONE, BUTYL ACETATE,</p> <p>TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES</p>
--

SECTION XVI OTHER INFORMATION

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
<p>THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETMENT OF THE INFORMATION CONTAINED HEREIN.</p>	

<p>HMIS HAZARD RATINGS: THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS</p>			<p>KEY 4 -- SEVERE</p>
CERTI-VEX AC 1315 SUPER SEAL HG	NPCA-HMIS	NFPA 704	3 -- SERIOUS
HEALTH	2	2	2 -- MODERATE
FLAMMABILITY	3	3	1 -- SLIGHT
REACTIVITY	0	0	0 -- MINIMAL