



MODEL 2238 | Specification Sheet
Residential Series • Specialty / Downlight

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES

Wattage	4.5 W or 5.5 W
Voltage	9 – 15 VAC
Lumens	295 or 389 Lumens
Lamp Type	MR-16 LED
Housing	Die-cast Aluminum
Dimensions	2 ¼" DIA x 4 ¾" H



ORDERING INFORMATION

EXAMPLE: HT-2238-B-4.5-W-36-FR

CATEGORY	MODEL	FINISH	LED
HT	2238		

CATEGORY	MODEL	FINISH	LED	ACCESSORIES
HT Hanging Downlight	2238	B Black	4.5-W-15 4.5 Watts Warm 15° Narrow Spot	FR Frosted Lens
		Z Architectural Bronze	4.5-W-25 4.5 Watts Warm 25° Spot	BL Flat Cool Blue Lens
		DZ Dark Bronze	4.5-W-36 4.5 Watts Warm 36° Flood	SL Flat Spread Lens
		GT Granite	4.5-W-60 4.5 Watts Warm 60° Wide Flood	DBL Flat Dark Blue Lens
		W White	5.5-W-15 5.5 Watts Warm 15° Narrow Spot	GL Flat Dark Green Lens
		BR Architectural Brick	5.5-W-25 5.5 Watts Warm 25° Spot	RL Flat Red Lens
		LZ Light Bronze	5.5-W-36 5.5 Watts Warm 36° Flood	YL Flat Amber Lens
		SB Special Bronze	5.5-W-60 5.5 Watts Warm 60° Wide Flood	HL Honeycomb louver
		GG Glossy Gray	NL No Lamp	
		R Rust		
		HG Hunter Green		
		WB Weathered Bronze		
		WI Weathered Iron		
		GM Graphite Metallic		
		G Verde		
		P Pewter		
M Mocha				
OF Olde Finish				



PROFESSIONAL
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



SPECIFICATIONS

HOUSING CONSTRUCTION:
Die-cast A360 aluminum.

FINISH:
Powder coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

LENS:
Clear, tempered glass lens.
Optical effect lenses are available.

MOUNTING:
Solid brass loop with a six-foot stainless steel cable-hanger included.

FASTENERS:
All fasteners are stainless steel.

LED:
MR-16 LED Lamp.
295 or 389 Lumens.
4.5 or 5.5 Watts.

ELECTRICAL:
Input voltage range 9 - 15 VAC.
Low voltage transformer required to operate (sold separately).

WIRING:
Prewired with a 36" pigtail of 18-2 SPT1 UV resistant cable and watertight connectors.

CERTIFICATION:
UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

LIGHT DISTRIBUTION:
Very Narrow Spot **15** (15°)
Narrow Spot **25** (25°)
Medium Flood **36** (36°)
Wide Flood **60** (60°)

DIMENSIONS

