



**MODEL 4260M** | Specification Sheet  
Residential Series • Step Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage	2.5 W
Voltage	9 – 15 VAC
Shroud	Brass, Copper or Stainless Steel
Dimensions	5 7/8" L x 1 1/4" H x 4" D

**ORDERING INFORMATION**

EXAMPLE: *SL-4260M-B-W-LB2ND*

CATEGORY	MODEL	FINISH	LED
SL	4260M		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4260M	<b>B</b> Black	<b>W-LB2ND</b> 2.5 Watts   Warm   Integrated LED <b>C-LB2ND</b> 2.5 Watts   Cool   Integrated LED
		<b>Z</b> Architectural Bronze	
		<b>DZ</b> Dark Bronze	
		<b>GT</b> Granite	
		<b>W</b> White	
		<b>BR</b> Architectural Brick	
		<b>LZ</b> Light Bronze	
		<b>SB</b> Special Bronze	
		<b>GG</b> Glossy Gray	
		<b>R</b> Rust	
		<b>HG</b> Hunter Green	
		<b>WB</b> Weathered Bronze	
		<b>WI</b> Weathered Iron	
		<b>GM</b> Graphite Metallic	
<b>G</b> Verde			
<b>P</b> Pewter			
<b>M</b> Mocha			
<b>OF</b> Olde Finish			
<b>BSN</b> Natural Brass	<b>CSN</b> Natural Copper		
<b>BSO</b> Olde Brass	<b>SS</b> Stainless Steel		



PROFESSIONAL  
OUTDOOR LIGHTING

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



**SPECIFICATIONS**

**SHROUD CONSTRUCTION:**  
Brass, Copper or Stainless Steel.

**HOUSING CONSTRUCTION:**  
Die-cast A360 aluminum.

**FINISH:**  
Stainless Steel shroud available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**  
Textured, high-impact polycarbonate lens.

**FASTENERS:**  
All fasteners are stainless steel.

**WIRING:**  
Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

**CERTIFICATION:**  
UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**  
Integrated LED Module. 2.5 Watts.

**ELECTRICAL:**  
Input voltage range 9 - 15 VAC.  
Low voltage transformer required to operate (sold separately).

**DIMENSIONS**

