



MODEL 2119 | Specification Sheet
Residential Series • Brass & Copper • Underwater

TYPE: MODEL:

PROJECT:

PRODUCT FEATURES



Wattage	5 W
Voltage	9 – 15 VAC
Housing	Brass or Stainless Steel
Dimensions	2 7/8" DIA x 3 1/2" D

ORDERING INFORMATION

EXAMPLE: **UW-2119-BSN-W-LC5ND**

CATEGORY	MODEL	FINISH	LED
UW	2119		

CATEGORY	MODEL	FINISH	LED	ORDERING NOTES
UW Underwater	2119	BSN Natural Brass SS Stainless Steel	W-LC5ND 5 Watts Warm Integrated LED N-LC5ND 5 Watts Neutral Integrated LED C-LC5ND 5 Watts Cool Integrated LED	2119 NOT for use in swimming pools or spas.





SPECIFICATIONS

HOUSING CONSTRUCTION:

Machined brass or stainless steel.

LENS:

Clear, tempered soda-lime glass lens.

MOUNTING:

Solid brass or stainless steel mounting bracket allows $\pm 20^\circ$ of adjustment.

FASTENERS:

All fasteners are stainless steel.

WIRING:

Pre-wired with a fifteen-foot pigtail of 18-3 submersible cable.

Connectors for a required above-water connection are also included.

LED:

Integrated LED Module.

5 Watts.

ELECTRICAL:

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

CAUTION:

Follow installation instructions as well as local electrical codes when installing.

NOT for use in swimming pools or spas.

DIMENSIONS

