



**MODEL 4261** | Specification Sheet  
Residential Series • Step Light

TYPE:  MODEL:

PROJECT:

**PRODUCT FEATURES**



Wattage 5 W

Voltage 9 – 15 VAC

Faceplate Aluminum, Brass, Copper or Stainless Steel

Dimensions 12" L x 1" H x 3 ¼" D

**ORDERING INFORMATION**

EXAMPLE: *SL-4261-BSN-W-LB2ND*

CATEGORY	MODEL	FINISH	LED
SL	4261		

CATEGORY	MODEL	FINISH	LED
SL Step Light	4261	<b>B</b> Black	<b>W-LB2ND</b> 2.5 Watts (x2)   Warm   Integrated LED <b>C-LB2ND</b> 2.5 Watts (x2)   Cool   Integrated LED
		<b>Z</b> Architectural Bronze	
		<b>DZ</b> Dark Bronze	
		<b>GT</b> Granite	
		<b>W</b> White	
		<b>BR</b> Architectural Brick	
		<b>LZ</b> Light Bronze	
		<b>SB</b> Special Bronze	
		<b>GG</b> Glossy Gray	
		<b>BSN</b> Natural Brass	
<b>BZO</b> Olde Brass			
		<b>R</b> Rust <b>HG</b> Hunter Green <b>WB</b> Weathered Bronze <b>WI</b> Weathered Iron <b>GM</b> Graphite Metallic <b>G</b> Verde <b>P</b> Pewter <b>M</b> Mocha <b>OF</b> Olde Finish <b>CSN</b> Natural Copper <b>SS</b> Stainless Steel	



**PROFESSIONAL  
OUTDOOR LIGHTING**

www.VistaPro.com • email@vistapro.com • Fax: (888) 670-VISTA (8478)  
1625 Surveyor Avenue • Simi Valley, CA 93063 • (805) 527-0987 • (800) 766-VISTA (8478)

Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



## SPECIFICATIONS

**FACEPLATE CONSTRUCTION:**

Aluminum, Brass, Copper or Stainless Steel.

**HOUSING CONSTRUCTION:**

Die-cast A360 aluminum.

**FLANGE CONSTRUCTION:**

Aluminum, Brass, Copper or Stainless Steel.

**FINISH:**

Aluminum Housing available with Powder coat finish in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Gray, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

**LENS:**

Textured, high-impact polycarbonate lens.

**FASTENERS:**

All fasteners are stainless steel.

**WIRING:**

Prewired with a ten-foot pigtail of 18-2 SPT1 cable and underground connectors.

**CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838).

**LED:**

Integrated LED Module. 5 Watts.

**ELECTRICAL:**

Input voltage range 9 - 15 VAC.

Low voltage transformer required to operate (sold separately).

## DIMENSIONS

