



PROFESSIONAL  
OUTDOOR LIGHTING

## SPECIFICATION SHEET

Type:

Model:

Project:

### MODEL 9217-LED Landscape Series • Path & Spread Lights

#### FIXTURE SPECIFICATIONS:

##### HOUSING:

Die-cast, copper-free aluminum.

##### STEM:

½" schedule-40 aluminum pipe with ½" NPT.

##### FINISH:

Polyester powder-coat finish available in Black, Verde, Architectural Brick, Architectural Bronze, Light Bronze, Dark Bronze, Granite, Pewter, Terracotta, Rust, Hunter Green, Mocha, Weathered Bronze, Weathered Iron, and White.

##### LENS:

Clear, prismatic, high-impact, polycarbonate spread lens.

##### LAMP TYPE:

High Output LED with Vista exclusive smart-driver, powered to operate for 50,000 hours.

##### ELECTRICAL:

Input voltage range 6–15V AC, regulated to achieve uniform illumination throughout the cable run of fixtures. Integral surge & reverse polarity protection.

##### MOUNTING:

Bottom of stem threaded with ½" NPT. Fixture may be mounted into

threaded hubs in junction boxes, ground stakes, or floor-mounting canopies.

##### FASTENERS:


All fasteners are stainless steel.

##### WIRING:

Prewired with a three-foot pigtail of 18-2 direct-burial cable & underground connectors for a secure connection to supply cable.

All Vista luminaires are **MADE IN U.S.A.**

#### DIMENSIONS:



Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



PROFESSIONAL  
OUTDOOR LIGHTING

## SPECIFICATION SHEET

### MODEL 9217-LED Landscape Series • Path & Spread Lights

#### FIXTURE ORDERING INFORMATION

TO ORDER FIXTURE: Select appropriate choice from each column as in the following example.

**EXAMPLE: PR-9217-B-W-LB2ND**

MOUNTING	MODEL	FINISH	COLOR TEMP	LAMP
PR - ABS ground stake	9217	B - Black G - Verde BR - Architectural Brick Z - Architectural Bronze LZ - Light Bronze DZ - Dark Bronze GT - Granite P - Pewter TC - Terracotta R - Rust HG - Hunter Green M - Mocha WB - Weathered Bronze WI - Weathered Iron W - White	W - Warm N - Neutral C - Cool	LB2ND - 2.5 watt LB5ND - 5 watt  LED - Group B Emitter Qty - 1 Temperature - Warm (W), Neutral (N), Cool (C) Operating voltage range - 6 to 15V.  (Please see lamp order code column on lamp guide, Vista product catalog.)

Fixtures shipped with standard lamp, unless otherwise specified.

Fixtures shipped with specified mounting hardware.

*Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.*