



Cartridge Filter & Filter System

A standard cartridge filter system offering quality, value, and convenience.

The ClearWater II Cartridge Filter and Pump Standard System provides homeowners with everything needed to get their system up and running. It assures them of matched components and optimal performance for years of dependable service.

FEATURES:

- Large filtration, small footprint cartridge filter
- Hi-Flo High Performance Single or Dual Speed Pump
- Large 6" pump trap with clear lid
- Two 1 1/2" diameter hoses with clamps
- Complete fittings package for all connections
- Dual Speed pump meets CEC Title 20 Code



2200 East Sturgis Road, Oxnard CA 93030
Phone 805.981.0262 • Fax 805.981.9403
www.waterwayplastics.com
waterway@waterwayplastics.com

**Designed,
Engineered &
Manufactured
in the USA.**



ClearWater II Cartridge Filter Standard System with Hi-Flo 2-Speed Pump

Part No.	Filter	Filtration Area	Flow Rate	Pump	HP	Volts	Pool Turnover	
							6 Hours	8 Hours
522-5107-3S	FC0757	75 sq. ft.	75 GPM	PH2100-3R	1.0	115	27,000	36,000
522-5127-3S	FC1007	100 sq. ft.	100 GPM	PH2100-3R	1.0	115	36,000	48,000
522-5147-3S	FC1007	100 sq. ft.	100 GPM	PH2150-3R	1.5	115	36,000	48,000
522-5157-3S	FC1257	125 sq. ft.	125 GPM	PH2150-3R	1.5	115	45,000	60,000
522-5167-3S	FC1507	150 sq. ft.	150 GPM	PH2150-3R	1.5	115	54,000	72,000
522-5187-3S	FC2007	200 sq. ft.	150 GPM	PH2150-3R	1.5	115	54,000	72,000
522-5107-6S	FC0757	75 sq. ft.	75 GPM	PH2100-6R	1.0	115	27,000	36,000
522-5127-6S	FC1007	100 sq. ft.	100 GPM	PH2100-6R	1.0	115	36,000	48,000
522-5147-6S	FC1007	100 sq. ft.	100 GPM	PH2150-6R	1.5	115	36,000	48,000
522-5157-6S	FC1257	125 sq. ft.	125 GPM	PH2150-6R	1.5	115	45,000	60,000
522-5167-6S	FC1507	150 sq. ft.	150 GPM	PH2150-6R	1.5	115	54,000	72,000
522-5187-6S	FC2007	200 sq. ft.	150 GPM	PH2150-6R	1.5	115	54,000	72,000

3 foot cord
Twist-Lock plug

3 foot cord
3-wire NEMA (regular) plug

Systems include: 2 hoses (1 1/2" x 6 ft.) • hose fittings, hose clamps, union adapter • 3 ft. cord Twist Lock plug, or 3 ft. cord NEMA plug • one-piece base

ClearWater II Cartridge Filter Standard System with Hi-Flo 1-Speed Pump

Part No.	Filter	Filtration Area	Flow Rate	Pump	HP	Volts	Pool Turnover	
							6 Hours	8 Hours
520-5107-3S	FC0757	75 sq. ft.	75 GPM	PH1100-3R	1.0	115	27,000	36,000
520-5127-3S	FC1007	100 sq. ft.	100 GPM	PH1100-3R	1.0	115	36,000	48,000
520-5147-3S	FC1007	100 sq. ft.	100 GPM	PH1150-3R	1.5	115	36,000	48,000
520-5157-3S	FC1257	125 sq. ft.	125 GPM	PH1150-3R	1.5	115	45,000	60,000
520-5167-3S	FC1507	150 sq. ft.	150 GPM	PH1150-3R	1.5	115	54,000	72,000
520-5187-3S	FC2007	200 sq. ft.	150 GPM	PH1150-3R	1.5	115	54,000	72,000
520-5107-6S	FC0757	75 sq. ft.	75 GPM	PH1100-6R	1.0	115	27,000	36,000
520-5127-6S	FC1007	100 sq. ft.	100 GPM	PH1100-6R	1.0	115	36,000	48,000
520-5147-6S	FC1007	100 sq. ft.	100 GPM	PH1150-6R	1.5	115	36,000	48,000
520-5157-6S	FC1257	125 sq. ft.	125 GPM	PH1150-6R	1.5	115	45,000	60,000
520-5167-6S	FC1507	150 sq. ft.	150 GPM	PH1150-6R	1.5	115	54,000	72,000
520-5187-6S	FC2007	200 sq. ft.	150 GPM	PH1150-6R	1.5	115	54,000	72,000

3 foot cord
Twist-Lock plug

3 foot cord
3-wire NEMA (regular) plug

Systems include: 2 hoses (1 1/2" x 6 ft.) • hose fittings, hose clamps, union adapter • 3 ft. cord Twist Lock plug, or 3 ft. cord NEMA plug • one-piece base

ClearWater II Cartridge Filter Standard System (w/o Hi-Flo Pump)

Part No.	Filter	Flow Area
520-5107	FC0757	75 sq. ft.
520-5127	FC1007	100 sq. ft.
520-5157	FC1257	125 sq. ft.
520-5167	FC1507	150 sq. ft.
520-5187	FC2007	200 sq. ft.

Systems include: 2 hoses (1 1/2" x 6 ft.) • hose fittings, hose clamps, union adapter • one-piece base

